| pnl 2004)   | UNITED STATES<br>DEPARTMENT OF THE INTERIOR   |  | FORM APPROVED<br>OM B No 1004-0137<br>Expires: March 31, 2007<br>5 Lease Serial No.  |  |   |  |
|---|---|--|--|--|---|--|
| BUREAU OF LAND MANAGEMENT   |   |  |  |  |   |  |
| SUNDRY NOTICES AND REPORTS ON WELLS<br>Do not use this form for proposals to drill or to re-enter an<br>abandoned well. Use Form 3160 - 3 (APD) for such proposals.<br>SUBMIT IN TRIPLICATE- Other instructions on reverse side.  |   |  |  | LC-065394-B           6. If Indian, Allottee or Tribe Name   |   |  |
|   |   |  |  |  |   |  |
|   |   |  |  | 7 If Unit or CA/Agreement, Name and/or No  |   |  |
| . Type of Well<br>✓ Oil Well  | Gas Well Other  |  |  | 8. Well Nar  | ne and No.  | $\overline{}$                              |
| 2. Name of Operator Seely Oit Company   |   |  |  | Mescalero Ridge "C" Federal #2 9. API Well No  |   |  |
| 3a         Address         3b.         Phone No. (include area code)           815 W. 10th St., Ft. Worth, TX 76102         817-332-1377  |   |  |  | 30-025-38609   |   |  |
| Location of Well (Footage, See  | 617-552-1577  |  | 10 Field and Pool, or Exploratory Area<br>Mescalero Escarpe (Bone Spring)  |  | /   |  |
| 640'FNL & 990' FWL  |   |  |  | 11 County  | or Parish, State  |  |
| Sec. 18-T18S-R34E   | Unit D  |  |  | Lea Co   | unty, New Mexico 🖊  |  |
| 12. CHECK   | APPROPRIATE BOX(ES) TO  | INDICATE NATURE  | OF NOTICE,   | REPORT, OR   | OTHER DATA  |  |
| TYPE OF SUBMISSION  |   | ТҮРЕ   | OF ACTION  |  |   |  |
|   | Acıdıze   | Deepen   | Production (   | Start/Resume)  | Water Shut-Off  |  |
| Notice of Intent  | Alter Casing  | Fracture Treat   | Reclamation  |  | Well Integrity  |  |
| Subsequent Report   | Casing Repair   | New Construction   | Recomplete   | Abandon  | Other   |  |
| Final Abandonment Notice  | Convert to Injection  | Plug Back  | Water Dispos   |  |   |  |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs MS  | ST on 12/29/07. Drilled 17 1/2'' h  | y, give subsurface locations a<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran  | ted starting date o<br>and measured and<br>n BLM/BIA Req<br>ion or recompletic<br>nts, including rec1  | true vertical depth<br>uired subsequent n<br>n in a new interva<br>amation, have been<br>i<br>L5 lb/ft & 61 lb/  | is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>I, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>(ft 1-55 csg w/ shoe set @ 180   | nes<br>ys<br>nce<br>s                      |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs M2<br>RKB. Cemented w/100   | rectionally or recomplete horizontally<br>in the work will be performed or provid-<br>involved operations. If the operation in<br>Final Abandonment Notices shall be in<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" if<br>0 sxs 35/65 Pozmix w/ 6% gel. 59<br>teed 175 sxs to pit. Cement fell brief.   | y, give subsurface locations i<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>pack to 57'. Run 1'' outsi  | ted starting date o<br>and measured and<br>n BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 54  | true vertical depth<br>aired subsequent r<br>n in a new interva<br>aimation, have been<br>i<br>4.5 lb/ft & 61 lb/<br>class "C" w/ 2  | is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>I, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>ift J-55 csg w/ shoe set @ 180<br>% CoCL Plug down @ 21:48   | nes<br>ys<br>s<br>90'                      |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs M3<br>RKB. Cemented w/ 100<br>MST on 1//3/08. Circula   | rectionally or recomplete horizontally<br>in the work will be performed or provid-<br>involved operations. If the operation is<br>Final Abandonment Notices shall be high for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" H<br>0 sxs 35/65 Pozmix w/ 6% gel, 5%<br>atted 175 sxs to pit. Cement fell b<br>si.   | y, give subsurface locations is<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requirement<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>EED  | ted starting date o<br>and measured and<br>n BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 54  | true vertical depth<br>nired subsequent m<br>n in a new interva<br>aimation, have been<br>i<br>4.5 lb/ft & 61 lb/<br>class ''C'' w/ 2'<br>nent w/ 100 sxs o  | is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>I, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>ift J-55 csg w/ shoe set @ 180<br>% CoCL Plug down @ 21:48   | nes<br>ys<br>s<br>s<br>90'<br>3<br>sle     |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs M3<br>RKB. Cemented w/ 100<br>MST on 1//3/08. Circula   | rectionally or recomplete horizontally<br>in the work will be performed or provid-<br>involved operations. If the operation in<br>Final Abandonment Notices shall be in<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" if<br>0 sxs 35/65 Pozmix w/ 6% gel. 59<br>teed 175 sxs to pit. Cement fell brief.   | y, give subsurface locations is<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requirement<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>EED  | ted starting date o<br>and measured and<br>n BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 54  | true vertical depth<br>nired subsequent m<br>n in a new interva<br>aimation, have been<br>i<br>4.5 lb/ft & 61 lb/<br>class ''C'' w/ 2'<br>nent w/ 100 sxs o  | is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>I, a Forn 3160-4 shall be filed on<br>n completed, and the operator has<br>ft J-55 csg w/ shoe set @ 180<br>% CaCl. Plug down @ 21:48<br>class ''C'' w/ 2% CaCl. Nipp   | nes<br>ys<br>s<br>s<br>90'<br>3<br>3<br>le |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs M3<br>RKB. Cemented w/ 100<br>MST on 1//3/08. Circula   | rectionally or recomplete horizontally<br>in the work will be performed or provid-<br>involved operations. If the operation is<br>Final Abandonment Notices shall be high for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" H<br>0 sxs 35/65 Pozmix w/ 6% gel, 5%<br>atted 175 sxs to pit. Cement fell b<br>si.   | y, give subsurface locations i<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>(ED)  | ted starting date o<br>and measured and<br>n BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 54  | true vertical depth<br>nired subsequent m<br>n in a new interva<br>aimation, have been<br>i<br>4.5 lb/ft & 61 lb/<br>class ''C'' w/ 2'<br>nent w/ 100 sxs o  | is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>I, a Forn 3160-4 shall be filed on<br>n completed, and the operator has<br>ft J-55 csg w/ shoe set @ 180<br>% CaCl. Plug down @ 21:48<br>class ''C'' w/ 2% CaCl. Nipp   | nes<br>ys<br>s<br>s<br>90'<br>3<br>sle     |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs MS<br>RKB. Cemented w/ 100<br>MST on 1//3/08. Circula<br>up & test BOP to 3000 p  | rectionally or recomplete horizontally<br>in the work will be performed or provin<br>involved operations. If the operation in<br>Final Abandonment Notices shall be find<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" find<br>0 sxs 35/65 Pozmix w/ 6% gel, 5%<br>ated 175 sxs to pit. Cement fell bisi.<br>RECEIV<br>JAN 2 3 20<br>HOBBSS   | y, give subsurface locations i<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>(ED)  | ted starting date o<br>and measured and<br>n BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 54  | true vertical depth<br>inred subsequent in<br>in a new interva<br>amation, have been<br>i<br>s.5 lb/ft & 61 lb/<br>class "C" w/ 24<br>hent w/ 100 sxs of<br>ACCEP  | Is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>1, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>fft J-55 csg w/ shoe set @ 180<br>% CaCL. Plug down @ 21:48<br>class "C" w/ 2% CaCL. Nipp<br>TED FOR REC<br>JAN 2 1 2008   | nes<br>ys<br>nce<br>s<br>ole<br><b>ORD</b> |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs MS<br>RKB. Cemented w/ 100<br>MST on 1//3/08. Circula<br>up & test BOP to 3000 p  | rectionally or recomplete horizontally<br>in the work will be performed or provin<br>involved operations. If the operation in<br>Final Abandonment Notices shall be fid<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" fi<br>0 sxs 35/65 Pozmix w/ 6% gel, 5%<br>ited 175 sxs to pit. Cement fell b<br>si.<br><b>RECEIV</b><br>JAN 2 3 20<br><b>HOBBS</b>  | y, give subsurface locations i<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>/ ED  | ted starting date o<br>and measured and<br>n BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 54  | true vertical depth<br>inred subsequent in<br>in a new interva<br>amation, have been<br>i<br>1.5 lb/ft & 61 lb/<br>class ''C'' w/ 20<br>hent w/ 100 sxs of<br>ACCEP<br>BUREA                               | is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>1, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>ft J-55 csg w/ shoe set @ 180<br>% CaCl. Plug down @ 21:48<br>class "C" w/ 2% CaCl. Nipp<br>PTED FOR REC<br>JAN 2 1 2008   | nes<br>ys<br>nce<br>s<br>ole<br><b>ORD</b> |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs MS<br>RKB. Cemented w/ 100<br>MST on 1//3/08. Circula<br>up & test BOP to 3000 p  | rectionally or recomplete horizontally<br>in the work will be performed or provin<br>involved operations. If the operation in<br>Final Abandonment Notices shall be fid<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" fi<br>0 sxs 35/65 Pozmix w/ 6% gel, 5%<br>ited 175 sxs to pit. Cement fell b<br>si.<br><b>RECEIV</b><br>JAN 2 3 20<br><b>HOBBS</b>  | y, give subsurface locations i<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>/ ED  | ited starting date o<br>and measured and<br>1 BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 5-<br>owed by 400 sxs<br>ide csg & re-cen                      | true vertical depth<br>inred subsequent in<br>in a new interva<br>amation, have been<br>i<br>1.5 lb/ft & 61 lb/<br>class ''C'' w/ 20<br>hent w/ 100 sxs of<br>ACCEP<br>BUREA                               | Is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>1, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>fft J-55 csg w/ shoe set @ 180<br>% CaCL. Plug down @ 21:48<br>CaCL. Plug down @ 21:48 | nes<br>ys<br>nce<br>s<br>ole<br><b>ORD</b> |
| <ul> <li>If the proposal is to deepen d<br/>Attach the Bond under which<br/>following completion of the<br/>testing has been completed<br/>determined that the site is real<br/>Spudded @ 1900 hrs MS<br/>RKB. Cemented w/ 100<br/>MST on 1//3/08. Circula<br/>up &amp; test BOP to 3000 p</li> <li>4. Thereby certify that the fo<br/>Name (<i>Printed/Typed</i>)<br/>David L. Hend</li> </ul>   | rectionally or recomplete horizontally<br>in the work will be performed or provin<br>involved operations. If the operation in<br>Final Abandonment Notices shall be find<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" find<br>0 sxs 35/65 Pozmix w/ 6% gel, 5%<br>inted 175 sxs to pit. Cement fell bisi.<br>RECEIV<br>JAN 2.3.20<br>HOBBSS<br>regoing is true and correct<br>erson  | y, give subsurface locations is<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>/ED<br>08<br>08<br>CCCD  | uted starting date o<br>and measured and<br>h BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 5-<br>owed by 400 sxs<br>ide csg & re-cen                      | true vertical depth<br>inred subsequent r<br>n in a new interva<br>amation, have been<br>i<br>4.5 lb/ft & 61 lb/<br>class "C" w/ 24<br>hent w/ 100 sxs of<br>ACCEP<br>BUREA<br>dent<br>01/09/2008          | Is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>1, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>fft J-55 csg w/ shoe set @ 180<br>% CaCL. Plug down @ 21:48<br>CaCL. Plug down @ 21:48 | nes<br>ys<br>nce<br>s<br>ole<br><b>ORD</b> |
| <ul> <li>If the proposal is to deepen d<br/>Attach the Bond under which<br/>following completion of the<br/>testing has been completed<br/>determined that the site is real<br/>Spudded @ 1900 hrs MS<br/>RKB. Cemented w/ 100<br/>MST on 1//3/08. Circula<br/>up &amp; test BOP to 3000 p</li> <li>4. Thereby certify that the fo<br/>Name (<i>Printed/Typed</i>)<br/>David L. Hend<br/>Signature Dawt</li> </ul>  | rectionally or recomplete horizontally<br>in the work will be performed or provin<br>involved operations. If the operation in<br>Final Abandonment Notices shall be if<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" if<br>0 sxs 35/65 Pozmix w/ 6% gel. 59<br>atted 175 sxs to pit. Cement fell b<br>si.<br><b>RECEIV</b><br>JAN 2 3 20<br><b>HOBBS</b><br>regoing is true and correct<br>erson  | y, give subsurface locations i<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>/ ED<br>08<br>CCCD<br>Title Exec<br>Date<br>FEDERAL OR ST/  | euted starting date o<br>and measured and<br>h BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 5-<br>owed by 400 sxs<br>ide csg & re-cen<br>cutive Vice Pres | true vertical depth<br>inred subsequent p<br>n in a new interva<br>amation, have been<br>v<br>4.5 lb/ft & 61 lb/<br>class "C" w/ 24<br>nent w/ 100 sxs of<br>ACCEP<br>BUREA<br>dent<br>01/09/2008<br>E USE | is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>1, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>fft J-55 csg w/ shoe set @ 180<br>% CaCL. Plug down @ 21:48<br>class "C" w/ 2% CaCL. Nipp<br>TED FOR REC<br>JAN 2 1 2008<br>JAN 2 1 2008<br>JAN D FLAND MANAGEMER<br>RLSBAD FIELD OFFICE   | nes<br>ys<br>nce<br>s<br>ole<br><b>ORD</b> |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs MS<br>RKB. Cemented w/ 100<br>MST on 1//3/08. Circula<br>up & test BOP to 3000 p<br>4. Thereby certify that the fo<br>Name ( <i>Printed/Typed</i> )<br>David L. Hend<br>Signature David L. Hend<br>Signature David L. Hend  | rectionally or recomplete horizontally<br>in the work will be performed or provin<br>involved operations. If the operation in<br>Final Abandonment Notices shall be find<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" find<br>0 sxs 35/65 Pozmix w/ 6% gel, 5%<br>inted 175 sxs to pit. Cement fell bisi.<br>RECEIV<br>JAN 2.3.20<br>HOBBSS<br>regoing is true and correct<br>erson<br>THIS SPACE FOR F<br>cattached Approval of this notice of<br>gal or equitable title to those rights in | y, give subsurface locations i<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requireme<br>hole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>/ ED<br>08<br>CCCD<br>Title Exec<br>Date<br>FEDERAL OR ST/<br>does not warrant or   | euted starting date o<br>and measured and<br>h BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 5-<br>owed by 400 sxs<br>ide csg & re-cen<br>cutive Vice Pres | true vertical depth<br>inred subsequent p<br>n in a new interva<br>amation, have been<br>v<br>4.5 lb/ft & 61 lb/<br>class "C" w/ 24<br>nent w/ 100 sxs of<br>ACCEP<br>BUREA<br>dent<br>01/09/2008<br>E USE | Is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>1, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>fft J-55 csg w/ shoe set @ 180<br>% CaCL. Plug down @ 21:48<br>CaCL. Plug down @ 21:48 | nes<br>ys<br>nce<br>s<br>ole<br><b>ORD</b> |
| If the proposal is to deepen d<br>Attach the Bond under which<br>following completion of the<br>testing has been completed<br>determined that the site is rea<br>Spudded @ 1900 hrs MS<br>RKB. Cemented w/ 100<br>MST on 1//3/08. Circula<br>up & test BOP to 3000 p<br>4. Thereby certify that the fo<br>Name (Printed/Typed)<br>David L. Hend<br>Signature David L. Hend<br>Signature David L. Hend<br>pproved by<br>onditions of approval, if any, ar<br>ertify that the applicant holds leg<br>hich would entitle the applicant | rectionally or recomplete horizontally<br>in the work will be performed or provin<br>involved operations. If the operation in<br>Final Abandonment Notices shall be find<br>dy for final inspection.)<br>ST on 12/29/07. Drilled 17 1/2" find<br>0 sxs 35/65 Pozmix w/ 6% gel, 5%<br>inted 175 sxs to pit. Cement fell bisi.<br>RECEIV<br>JAN 2.3.20<br>HOBBSS<br>regoing is true and correct<br>erson<br>THIS SPACE FOR F<br>cattached Approval of this notice of<br>gal or equitable title to those rights in | y, give subsurface locations is<br>de the Bond No. on file with<br>results in a multiple complet<br>filed only after all requirement<br>sole to 1800' RKB. Ran<br>% salt & 0.2% FL52 foll-<br>back to 57'. Run 1'' outsi<br>/ ED<br>08<br>08<br>CCD<br>Title Exect<br>Date<br>FEDERAL OR ST/<br>does not warrant or<br>in the subject lease Office | ted starting date o<br>and measured and<br>h BLM/BIA Req<br>ion or recompletic<br>nts, including recl<br>43 jts 13 3/8'' 54<br>owed by 400 sxs<br>ide csg & re-cen<br>ce tree Pres       | true vertical depth<br>inred subsequent in<br>in a new interva<br>amation, have been<br>i<br>1.5 lb/ft & 61 lb/<br>class "C" w/ 2 chent w/ 100 sxs of<br>ACCEP<br>BUREA<br>dent CAI<br>01/09/2008<br>E USE | is of all pertinent markers and zor<br>eports shall be filed within 30 day<br>1, a Form 3160-4 shall be filed on<br>n completed, and the operator has<br>fft J-55 csg w/ shoe set @ 180<br>% CaCl. Plug down @ 21:48<br>class ''C'' w/ 2% CaCl. Nipp<br>PTED FOR REC<br>JAN 2 1 2008<br>JUMM<br>U OF LAND MANAGEME<br>RLSBAD FIELD OFFICE   | nes<br>ys<br>nce<br>s<br>ole<br>ORD<br>ENT |

N

.

. .