

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Minerals and Natural Resources

Form C-103
May 27, 2004

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

APR 08 2008
HOBBS OCD

WELL API NO.30-025-38304
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-1519-2
7. Lease Name or Unit Agreement Name ENCORE 22 STATE COM
8. Well Number 001
9. OGRID Number 189951
10. Pool name or Wildcat VACUUM;ATOKA-MORROW, NORTH

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
ENCORE OPERATING, L.P.

3. Address of Operator
777 MAIN STREET, STE. 1400 FORT WORTH, TX. 76102

4. Well Location
Unit Letter H : 1730 feet from the NORTH line and 1000 feet from the EAST line
Section 22 17S Township 34E Range NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4041

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type 115 Depth to Groundwater N/A Distance from nearest fresh water well N/A Distance from nearest surface water N/A

Pit Liner Thickness: 12 mil Below-Grade Tank: Volume 14000 bbls; Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ENCORE OPERATING, L.P. 3/31/2008 9:30 AM WITH 17 1/2" BIT. DRILLED TO 480' AND RAN 13 3/8 48# H-40 CASING TO 480'. CEMENTED W/ 500 SX OF CLASS C W/ 2% CACL2 & .125% CELLO-FLAKE AT 14.8 PPG W/ WATER RATIO OF 6.35 GPS YEILD OF 1.35 FT/SK. CIRC 17 BLS/71 SX TO PIT. TEST TO 500 PSI HELD GOOD. PICK UP 12 1/4 BIT. ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

ENCORE OPERATING, L.P. SPUD 3/31/2008 9:30 AM WITH 17 1/2" BIT. DRILLED TO 480' AND RAN 13 3/8 48# H-40 CASING TO 480'. CEMENTED W/ 500 SX OF CLASS C W/ 2% CACL2 & .125% CELLO-FLAKE AT 14.8 PPG W/ WATER RATIO OF 6.35 GPS YEILD OF 1.35 FT/SK. CIRC 17 BLS/71 SX TO PIT. TEST TO 500 PSI HELD GOOD. PICK UP 12 1/4 BIT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ann Burdette Wiley TITLE REGULATORY MANAGER DATE 4/4/2008

Type or print name ANN BURDETTE WILEY E-mail address: awiley@encoreacq.com Telephone No. 817-877-9955

For State Use Only

APPROVED BY: Chris Williams TITLE OCD DISTRICT SUPERVISOR/GENERAL MANAGER DATE APR 16 2008
Conditions of Approval (if any):