


Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico RECEIVED Minerals and Natural Resources Oil Conservation Division MAY 08 2008 220 South St. Francis Dr. Santa Fe, NM 87505 HOBBS OCL		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-38667		5. Indicate Type of Lease STATE ☐ FEE ☒	
		State Oil & Gas Lease No. N/A			
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well. OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____		7. Lease Name or Unit Agreement Name Payday			
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER		8. Well No #004			
2. Name of Operator Apache Corporation		9. Pool name or Wildcat Blinebry Oil & Gas			
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224					
4. Well Location Unit Letter <u>L</u> : <u>2310</u> Feet From The <u>South</u> Line and <u>990</u> Feet From The <u>West</u> Line Section <u>24</u> Township <u>20S</u> Range <u>38E</u> NMPM Lea County					
10. Date Spudded 03/20/2008	11. Date T.D. Reached 03/29/2008	12. Date Compl. (Ready to Prod) 05/01/2008	13. Elevations (DF& RKB, RT, GR, etc) 3,573'	14. Elev. Casinghead	
15. Total Depth 7300'	16. Plug Back T.D. 6450' RBP	17. If Multiple Compl. How Many Zones? NA	18. Intervals Drilled By X	Rotary Tools	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 6036-6308' (Blinebry Oil & Gas)				20. Was Directional Survey Made No	
21. Type Electric and Other Logs Run DLL-MG, CSITT, SGR, CNPD				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1618'	12-1/4"	750 sx / circ	
5-1/2"	17#	7248'	7-7/8"	1300 sx / TOC 1100'	CBL
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE
					2-7/8"
					DEPTH SET 6351'
					PACKER SET
26. Perforation record (interval, size, and number) Blinebry: 6036-6308' (2 JSPF, 45 holes) Tubb: 6543-6888' (2 JSPF, 45 holes) RBP @ 6450'			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.		
			DEPTH INTERVAL		
			AMOUNT AND KIND MATERIAL USED		
			6036-6308' 3Kgal 15%HCl, 41Kgal pad + 82K# 20/40		
			6543-6888' 3Kgal 15%HCl, 40Kgal pad + 82K# 20/40		
28. PRODUCTION					
Date First Production 05/01/2008		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - Rod Pump		Well Status (Prod. or Shut-in) Producing	
Date of Test 05/04/2008	Hours Tested 24 hours	Choke Size	Prod'n For Test Period	Oil - Bbl 11	Gas - MCF 72
				Water - Bbl. 131	Gas - Oil Ratio 6545
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.
					Oil Gravity - API - (Corr) 38.0
29. Disposition of Gas (Sold, used for fuel, vented, etc) Sold					Test Witnessed By Apache Corporation
30. List Attachments Deviation Report, C-102, C-103, C-104 (Logs mailed 4/23/2008)					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature 		Printed Name Sophie Mackay		Title Engineering Tech	
E-mail Address sophie.mackay@apachecorp.com		Date 05/06/2008			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2906'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 3139'	T. Devonian	T. Menefee	T. Madison
T. Queen 3701'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 4030'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4277'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5566'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 6024'	T. Gr. Wash	T. Morrison	T.
T. Tubb 6536'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6866'	T. Bone Springs	T. Entrada	T.
T. Abo 7095'	T. Rustler 1583'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology