JUN-18-2008 WED 02:45 PM mack energy

P. 02

Form C-144

June 16, 2008

District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tabks, submit to the appropriate NMOCD District Office. For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

	stem. Below-Grade Tank, or PI-0000;
Proposed Alternative Method	Permit or Closure Plan Application
Type of action: X Permit of a pit, closed-loop	system, below-grade tank, or proposed alternative method p system, below-grade tank, or proposed alternative method
	individual pit, closed-loop system, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of l	liability should operations result in pollution of surface water, ground water or the mply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: <u>Mack Energy Corporation</u>	OGRID #: 013837
Address: P.O. Box 960 Artesia, NM 88211	
Facility or well name: <u>BLee State</u> # 1	
API Number: 30.025.30303	OCD Permit Number: 331054
U/L or Qtr/Qtr Section Township	35 Range 35E County: LCA, NM
Center of Proposed Design: Latitude	Longitude NAD: [] 1927 [] 1983
Surface Owner: 🗖 Federal 🕅 State 🗖 Private 🗍 Tribal Trust or Indian	Allotment
Pit: Subsection F or G of 19.15.17.11 NMAC	Closed-loop System: Subsection H of 19.15.17.11 NMAC
Temporary: 🔲 Drilling 🛄 Workover	Drying Pad 🖾 Tanks 🕅 Haul-off Bins 🗆 Other
Permanent 🗋 Emergency 🔲 Cavitation	Lined Unlined
Lined Unlined	Liner type: Thicknessmil LLDPE HDPE PVC
Liner type: Thickness mil 🗌 LLDPE 🗍 HDPE 🗋 PVC	Other
Other String-Reinforced	Seams: 🗌 Welded 🗋 Factory 🗋 Other
Seams: 🛄 Welded 🛄 Factory 🗖 Other	Volume:bblyd ³
Volume:bbl Dimensions: Lx Wx D	Dimensions: Length x Width
Below-grade tank: Subsection I of 19,15,17.11 NMAC	Fencing: Subsection D of 19.15.17.11 NMAC
Volume:bbl	Chain link, six feet in height, two strands of barbed wire at top
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between one and
Tank Construction material:	four feet
Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11 NMAC
□ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen I Netting Other
☐ Visible sidewalls and liner	Monthly inspections
□ Visible sidewalls only	Signs: Subsection C of 19.15.17.11 NMAC
□ Other	12'x24', 2' lettering, providing Operator's name, site location, and
Liner type: Thicknessmil 🔲 HDPE 🛄 PVC	emergency telephone numbers
Other	Signed in compliance with 19.15.3.103 NMAC
Alternative Method:	Administrative Approvals and Exceptions:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.
or approval.	Please check a box if one or more of the following is requested, if not leave blank:
	\square Administrative approval(s); Requests must be submitted to the
	appropriate division district or the Santa Fe Environmental Bureau office for
	consideration of approval.
	Environmental Bureau office for consideration of approval.

D .	00
Ρ.	113
1.1	00

Siting Criteria (regarding permitting): 19.15.17.10 NMAC		
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed- loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	🗌 Yes 🗌 No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	🗋 Yes 🗌 No	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	□ Yes □ No □ NA	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	U Yes No NA	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗋 Yes 🗋 No	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🛄 No	
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗖 Yes 🗋 No	
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	🔲 Yes 🗋 No	
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	🗋 Yes 🗌 No	
Within a 100-year floodplain. - PEMA map	🗋 Yes 🗋 No	
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N	D/4/	
attached.	cuments are	
 Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.15 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.15 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Ptan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 	5 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:		
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are utached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.15 Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Previously Approved Design (attach copy of design) API Number:		

.

.

Oil Conservation Division

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.	documents are
Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.15 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment	
Certified Engineering Design Plans - based upon the appropriate requirements of 19,15,17,11 NMAC	
Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan	
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 	
Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Emergency Response Plan	
Oil Field Waste Stream Characterization	
Monitoring and Inspection Plan Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Proposed Closure: 19.15.17.13 NMAC	······································
Type: Drilling Workover E Emergency Cavitation Permanent Pit E Below-grade Tank Closed-loop System	Alternative
Proposed Closure Method: 🔲 Waste Excavation and Removal	
On-site Closure Method (only for temporary pits and closed-loop systems) In-place Burial I On-site Trench Burial	
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for c	onsideration)
Siting Criteria (regarding on-sife closure methods only): 19.15.17.10 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from	
office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10	
Innarc for guiaance.	
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	U Yes I No
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Y=5 □ No □ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).	🗌 Yes 🛄 No
- Topographic map; Visual inspection (certification) of the proposed site	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🔲 Yes 🗂 No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application, - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	🗖 Yes 🗌 No
Within incorporated municipal boundaries or within a defined municipal first protor well field covered under a municipal of the	Yes 🗖 No
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	
Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification many Tenegraphic many Viscol is a single state of the second state of th	🗌 Yes 🗌 No
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine.	
 Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗋 Yes 🗋 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society: Topographic man 	
Society; Topographic map	🗌 Yes 🛄 No
Within a 100-year floodplain, - FEMA map	🗋 Yes 🗌 No
Form C-144 Oil Conservation Dansion	

Oil Conservation Division

Page 3 of 4

JUN-18-2008 WED 02:45 PM mack energy

.

FAX NO. 15057469539

.

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	Ľ
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17 13 NMAC	
Waste Removal Closure For Closed-loop Systems That Utilize Haul-off Bins Only: (19 15.17.13.D NMAC) Instructions: Please indentify the or facilities for the disposal of liquids, drilling fluids and drill cuttings. Disposal Facility Name: Cortrolled Recovery Inc. Disposal Facility Permit Number: R-9166	facility
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please in by a check mark in the box, that the documents are attached.	dicate,
 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved Soil Cover Design - based upon the appropriate of Subsection H of 19.15.17.13 NMAC)
 Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC 	
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief Name (Print):	
Signature: Jerry a. Shendt Date: 6-18-08	
e-mail address: jerrys@mackenergycorp.com Telephone: (575) 748-1288	
OCD Appraval: Permut Application (including closure plan) Closure Plan (only)	
OCD Representative Signature:	
Approval Date: Approval Date:	
Title: Approval Date: Approval Date: $P_1 - 0000$,	2
Title:	2
Title:	2
Title:	2 eck
Title:	2 cck
Title:	2 eck
Title:	2 eck
Title:	2
Title:	2
Title:	2

P. 06

Mack Energy Closed Loop System Design Plan

Equipment list,

- 2-414 Swaco Centrifuges
- 2-4 screen Mongoose shale shakers
- 2-250 BBL tanks to hold fluid
- 2- CRI Bins with track system
- 2- 500 BBL frac tanks for fresh water
- 2- 500 BBL frac tanks for brine water

Operation and Maintenance

Closed Loop equipment will be inspected daily by each tour and any necessary maintenance performed Any leak in system will be repaired and/or contained immediately OCD notified within 48 hours Remediation process started

Closure Plan

During drilling operations all liquids, drilling fluids and cuttings Will be hauled off via CRI(Controlled Recovery Incorporated Permit R-9166).