District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144 June 24, 2008

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

## Pit, Closed-Loop System, Below-Grade Tank, or P - DDO 2D Proposed Alternative Method Permit or Closure Plan Application

Type of action: XX Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per i	ndividual pit, closed-loop system, below-grade tank or alternative request	
	iability should operations result in pollution of surface water, ground water or the  oply with any other applicable governmental authority's rules, regulations or ordinances.	
Operator: ConocoPhillips Company	OGRID #: 217817	
Address: <u>3300 N "A" St., Bldg, 6, Midland, TX 79705</u>		
Facility or well name: MCA Unit #391		
API Number:30-025-38853		
U/L or Qtr/Qtr H Section 25 Township 17		
<u>-</u>	NAD: X 1927 ☐ 1983	
Surface Owner: X Federal State Private Tribal Trust or Indian Allotment		
Pit: Subsection F or G of 19.15.17.11 NMAC	X Closed-loop System: Subsection H of 19.15.17.11 NMAC	
Temporary: Drilling Workover	Drying Pad Tanks X Haul off Bins Other	
Permanent Binergency Cavitation Steel Pit	Lined Unlined	
Lined Unlined	Liner type: Thicknessmil	
Liner type: Thicknessmil	☐ Other	
Other String-Reinforced	Seams: Welded Factory Other	
Seams: Welded Factory Other	Volume:bblyd <sup>3</sup>	
Volume:bbl Dimensions: L x W x D	Dimensions: Lengthx Width	
Below-grade tank: Subsection I of 19.15.17.11 NMAC	Fencing: Subsection D of 19.15.17.11 NMAC	
Volume:bbl	☐ Chain link, six feet in height, two strands of barbed wire at top	
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between one and	
Tank Construction material:	four feet	
Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11 NMAC	
☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other	
☐ Visible sidewalls and liner	☐ Monthly inspections	
☐ Visible sidcwalls only	Signs: Subsection C of 19.15.17.11 NMAC	
☐ Other	12'x24', 2' lettering, providing Operator's name, site location, and	
Liner type: Thicknessmil	emergency telephone numbers	
Other	☐ Signed in compliance with 19,15,3.103 NMAC	
Alternative Method:	Administrative Approvals and Exceptions:	
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration	Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
of approval.	Please check a box if one or more of the following is requested, if not leave	
	blank:	
	Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for	
	consideration of approval.	
	Exception(s): Requests must be submitted to the Santa Fc Environmental Bureau office for consideration of approval.	

String Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applies to temporary, emergency, or cavitation pits and below-grade tanks)  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applies to permanent pits)  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978. Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No	
Within 500 feet of a wetland.	☐ Yes ☐ No	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	<b>E</b> (00   100	
Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Ycs ☐ No	
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No	
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.    Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC   Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC   Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC   Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.13 NMAC		
Previously Approved Design (attach copy of design) API Number: or Permit Number:		
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC  X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  NMAC		
Previously Approved Design (attach copy of design) API Number:		

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Fach of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.    Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC     Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC     Climatological Factors Assessment     Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC     Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC     Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC     Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC     Quality Control/Quality Assurance Construction and Installation Plan     Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC     Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC     Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan     Emergency Response Plan     Oil Field Waste Stream Characterization     Monitoring and Inspection Plan     Erosion Control Plan     Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC     Proposed Closure: 19.15.17.13 NMAC		
Type: X Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Alternative		
Proposed Closure Method: Waste Excavation and Removal  Waste Removal (Closed-loop systems only)  On-site Closure Method (Only for temporary pits and closed-loop systems)  In-place Burial On-site Trench Burial  Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)		
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC		
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.		
Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA	
Ground water is between 50 and 100 feet below the bottom of the buried waste  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No	
Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within 300 feer from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Ycs ☐ No	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No	
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No	
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No	

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC		
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC  Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC		
Waste Removal Closure For Closed-loop Systems That Utilize Haul-off Bins Ouly: (19.15.17.13.D NMAC) Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings.		
Disposal Facility Name: Controlled Recovery, Inc.  Disposal Facility Permit Number: R-9166  On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate,		
by a check mark in the box, that the documents are attached.   Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.13 NMAC   Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC   Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.13 NMAC   Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC   Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC   Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC   Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)   Soil Cover Design - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC   Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC		
Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.		
Name (Print): Celeste G. Dale Title: Regulatory Specialist		
Signature: Oblest A Alle Date: 06/26/08		
e-mail address: celeste.g.dale@conocophillips.com Telephone: 432-688-6884		
OCD Approval: Permit Application (including closure plan) Closure Plan (only)		
OCD Representative Signature: Approval Date:		
Title: Seologiste OCD Permit Number: PI-00020		
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC  Closure Completion Date:		
Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternative Closure Method If different from approved plan, please explain.		
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)		
On-site Closure Location: Latitude Longitude NAD: 1927 1983		
Operator Closure Certification:  I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.		
bellet. Talso telet, that the provide company with an approved the state of the sta		
Name (Print): Title:		

ConocoPhillips Company
Closed Loop System Design, Operating and Maintenance, and Closure Plan

Well: MCA 391

Date: 26-June-2008

ConocoPhillips proposes the following plan for design, operating and maintenance, and closure of our proposed closed loop system for the above named well:

We propose to use a closed loop system with steel pits, haul-off bins, and frac tanks for containing all
cuttings, solids, mud, water, brine, and liquids. We will not dig a pit, nor will we use a drying pad, nor will
we build an earth pit above ground level, nor will we dispose of or bury any waste on location.

All drilling waste and all drilling fluids (fresh water, brine, mud, cuttings, drill solids, cement returns, and any other liquid or solid that may be involved) will be contained on location in the rig's steel pits or in hauloff bins or in frac tanks as needed. The intent is as follows:

- We propose to use the rigs's steel pits for containing and maintaining the drilling fluids.
- We propose to remove cuttings and drilled solids from the mud by using solids control equipment and to contain such cuttings and drilled solids on location in haul-off bins.
- We propose that any excess water that may need to be stored on location will be stored in frac tanks.
- 2. Cuttings and solids will be removed from location in haul-off bins by an authorized contractor and disposed of at an authorized facility. For this well, we propose the following disposal facility:

Controlled Recovery Inc, 4507 West Carlsbad Hwy, Hobbs, NM 88240, P.O. Box 388 Hobbs, New Mexico 88241 Toll Free Phone: 877.505.4274, Local Phone Number: 432-638-4076

The physical address for the plant where the disposal facility is located is Highway 62/180 at mile marker 66 (33 miles East of Hobbs, NM and 32 miles West of Carlsbad, NM).

The Permit Number for CRI is R9166

A photograph showing the type of haul-off bins that will be used is attached.

- Mud will be transported by vacuum truck and disposed of at Controlled Recovery Inc at the facility described above.
- 4. Fresh Water and Brine will be hauled off by vacuum truck and disposed of at an authorized salt water disposal well. We propose the following for disposal of fresh water and brine as needed:
  - Nabors Well Services Company, 3221 NW County Rd, Hobbs, NM 88240, PO 5208 Hobbs, NM, 88241, Permit SWD 092. (Well Location: Section 3, T19S R37E)
  - Basic Energy Services, PO Box 1869 Eunice, NM 88231 Phone Number 575 394 2545, Facility located at Hwy 18, Mile Marker 19, Eunice, NM.

Steven O. Moore
Staff Drilling Engineer
ConocoPhillips Company
600 North Dairy Ashford, Room # 2WL-13022
Houston, TX 77079-1175
Office Phone 832 486 2459
Cell Phone 281 467 7596

