Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office May 27, 2004 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 District II 30-025-38396 OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease District III 1220 South St. Francis Dr. STATE | 1000 Rio Brazos Rd, Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV 1220 S St Francis Dr , Santa Fe, NM 87505 V-5560 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH Merle State Unit PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well Gas Well Other 14 2. Name of Operator 9. OGRID Number Yates Petroleum Corporation 025575 3. Address of Operator 10. Pool name or Wildcat 105 S. 4th Street, Artesia, NM 88210 Wolfcamp 4. Well Location 1980 feet from the 660 feet from the West line Unit Letter L South line and 13 Township 10S Range 34E **NMPM** Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4171'GR Pit or Below-grade Tank Application or Closure Pit type _____ Depth to Groundwater ____ Distance from nearest fresh water well Distance from nearest surface water Below-Grade Tank: Volume bbls; Construction Material Pit Liner Thickness: 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK □ PLUG AND ABANDON REMEDIAL WORK ALTERING CASING □ **TEMPORARILY ABANDON** CHANGE PLANS COMMENCE DRILLING OPNS.□ PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL \Box OTHER: Intermediate Csq OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 6/05/08 Reached TD 9187'. 6/08/08 Set 5-1/2" 15.5# J-55 & 17# HCP-110 csg @ 9187'. Float collar set @ 9142'. Cemented w/700 sx Interfill "H" + 0.1% HR-7 (yld 2.48, wt 11.9). Tailed in w/440 sx 50/50 Poz + 0.4% CFR-3 + 0.25%/bbl D-Air 3000 + 0.4% LAP-1 + 1%/bbl salt (yld 1.31, wt 14.2). JN 1 A 2003

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-

For State Use Only
APPROVED BY:

Conditions of Approval (if any):

Conditions of Approval (if any):