Submit 3 Copies To Appropriate District Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resourc	WELL API NO. June 16, 2008
1625 N French Dr., Hobbs, NM 88240 District II	OIL CONSERVATION DIVISION	30-025-39003
1301 W. Grand Ave, Artesia, NM 88210 District III	1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE FEE
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
District IV 1220 S. St Francis Dr., Santa Fe, NM	· ·	. VO-6845
87505 SUNDRY NOTI	CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSE DIFFERENT RESERVOIR. USE "APPLICE"	SALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A CATION FOR PERMIT" (FORM C-101) FOR SUCH	
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well 🛛 Other	8. Well Number 002
2. Name of Operator	/	9. OGRID Number
Yates 3. Address of Operator	S Petroleum Corporation	025575 10. Pool name or Wildcat
	ourth Street, Artesia NM 88210	X-4 Ranch Mississippian, West (Gas)
4. Well Location		
Unit Letter P: 660 feet from the South line and 660 feet from the East line		
Section No. 8 Township 1995 105 Range 33E 34 ENMPM Lea County		
The state of the s	11. Elevation (Show whether DR, RKB, RT, C 4232' GR	R, etc.)
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF IN PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	PLUG AND ABANDON ☐ REMEDIA CHANGE PLANS ☐ COMMEN	SUBSEQUENT REPORT OF: WORK
OTHER:	☐ OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
Yates Petroleum Corporation wishes to change the casing and cement program as follows: Change Surface Hole to 14 ¾, casing to 11 ¾, set at 400, Intermediate Hole to 11, casing 8 5/8, set at 4200, Production Hole to 7 7/8, casing to 5 ½ set to 12,515. This is a new proposed depth. Surface casing will be cemented with 275 sacks and circulated to surface. Intermediate casing will be cemented with 1150 sacks and circulated to surface. The production casing will be cemented with 1300 sacks with the top of cement being approximately 7,300.		
AEGE		BEGENED
"". 1	2008	
HOBB	SOCD	HOBBS OCD
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
$O \land \neq \emptyset$		
SIGNATURE Clifty	TITLE Regulatory Age	nt DATE July 9, 2008
Type or print nameClifton May	E-mail address:	PHONE: _575-748-4347
For State Use Only	In .	1111 7 5 00-
SIGNATURE		