

Submit 2 Copies To Appropriate District  
Office  
District I  
1625 N French Dr., Hobbs, NM 88240  
District II  
1301 W Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S St Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
April 10, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-38503
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VA-3080
7. Lease Name or Unit Agreement Name W. Bishop State
8. Well Number #1
9. OGRID Number 246804
10. Pool name or Wildcat Bishop Canyon; San Andres, West

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS)

1. Type of Well: ☒ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Quest Cherokee, LLC

3. Address of Operator  
210 Park Ave., Suite 2750, Oklahoma City, OK 73102

4. Well Location

Unit Letter C: 990 feet from the North line and 2310 feet from the West line

Section 9 Township 18S Range 38E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
GLE 3656 ft.

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒ XX  
CASING/CEMENT JOB ☐

OTHER:

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms, [www.emnr.state.nm.us/oed](http://www.emnr.state.nm.us/oed).

April 22, 2008

The well was plugged as follows

CIBP @ 4750' w/ 35' of cement to cover open perforations 4758 to 4800'  
Circulate the hole with pre-mixed 9.5# plugging mud

25 sack Class C neat cement plug pumped at 2646' (2399-2646) to cover Base of salt at 2600'

35 sack Class C 2% CaCl cement plug pumped at 1986' to cover 8 5/8" casing shoe at 1913 and top of salt @ 1860', This plug was  
tagged @ 1632' (1632' to 1986')

sx at 60' to surface (6' to 60')

The 5 1/2" and 8 5/8" casings will be cut off 6' below ground level and a plate showing the typical dry hole marker data will be welded on  
top of both casings. The cellar boards will be removed and the cellar filled in. All lease equipment and the fence will be removed from  
location. Caliche will be scraped up and hauled from location and the location will be re-seeded.

SIGNATURE Richard Marlin TITLE Vice President DATE 4/23/08

TYPE OR PRINT NAME Richard Marlin E-MAIL: rmarlin@grsp.net PHONE: 405-702-7480  
For State Use Only

APPROVED BY: Chris Williams OC DISTRICT SUPERVISOR/GENERAL MANAGER TITLE DATE JUL 15 2008  
Conditions of Approval (if any):

RECEIVED

APR 28 2008

HOBBS OCD