Form C-144 June 24, 2008

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Road, Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, M 87503

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD

District Office.

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Instructions: Please submit one application (Form C-144) per th	nuivinuut pii, cioseu-toop system, vetow-graue tank or unernutive request	
Please be advised that approval of this request does not relieve the operator of lise environment. Nor does approval relieve the operator of its responsibility to com	ability should operations result in pollution of surface water, ground water or the ply with any other applicable governmental authority's rules, regulations or ordinances.	
Operator:Edge Petroleum Operating Company, Inc	OGRID #:224400	
Address: _1301Travis Suite 2000 Houston, TX 77002		
Facility or well name: _Souhteast Lusk 27 Federal #1		
API Number: _30-025-38678	OCD Permit Number: <u>P1-00173</u>	
U/L or Qtr/QtrN Section 27 Township 19S	Range 32E County: Lea	
Center of Proposed Design: Latitude	Longitude NAD: ☐1927 ☐ 1983	
Surface Owner: Federal State Private Tribal Trust or Indian	Allotment	
☐ Pit: Subsection F or G of 19.15.17.11 NMAC	☐ Closed-loop System: Subsection H of 19.15.17.11 NMAC	
Temporary: Drilling Workover	☐ Drying Pad ☐ Tanks ☒ Haul-off Bins ☐ Other	
☐ Permanent ☐ Emergency ☐ Cavitation ☐ Steel Pit	☐ Lined ☐ Unlined	
☐ Lined ☐ Unlined	Liner type: Thicknessmil	
Liner type: Thicknessmil	Other	
Other String-Reinforced	Seams: Welded Factory Other	
Seams: Welded Factorý Other	Volume:bblyd³	
Volume: bbl Dimensions: L x W x D	Dimensions: Lengthx Width	
Below-grade tank: Subsection I of 19.15.17.11 NMAC	Fencing: Subsection D of 19.15.17.11 NMAC	
Volume:bbl	☐ Chain link, six feet in height, two strands of barbed wire at top	
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between one and	
Tank Construction material:	four feet	
☐ Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11 NMAC	
☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	☐ Screen ☐ Netting ☐ Other	
☐ Visible sidewalls and liner	☐ Monthly inspections	
☐ Visible sidewalls only	Signs: Subsection C of 19.15.17.11 NMAC	
Other	12'x24', 2' lettering, providing Operator's name, site location, and	
Liner type: Thicknessmil	emergency telephone numbers	
Other	☐ Signed in compliance with 19.15.3.103 NMAC	
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave	
	blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval	

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☐ NA	
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No	
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No	
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No	
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No	
Within a 100-year floodplain FEMA map	☐ Yes ☐ No	
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:		
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Previously Approved Design (attach copy of design) API Number:		

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	cuments are		
### Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment	·		
Proposed Closure: 19.15.17.13 NMAC	_		
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank Closed-loop System	Alternative		
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)			
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.			
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA		
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA		
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No		
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes No		
Within a 100-year floodplain FEMA map	☐ Yes ☐ No		

Waste Excavation and Removal Closure Plan Checklists (10.15.17.12.NMAC)
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Euch of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.
☐ Protocols and Procedures - based upon the appropriate requirements of 10.15.17.12.2024.6
U Continuation Sampling Plan (if applicable) - based upon the appropriate requirements of C. 1 and C. 2 and C.
Supposed the first transfer and telling the first transfer and doll make and doll make and
LJ 3011 Backfill and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specifications - based months appropriate manifestation and Cover Design Specification and Cover Design Specificati
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC
Waste Removal Closure For Closed-loop Systems That Utilize Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please indentify the facilities for the disposal of liquids, drilling fluids and drill cuttings.
Character to the state of the s
Disposal Facility Name: CRI Disposal Facility Pennit Number: R-9166 NM - 0 1 - 000
On-Site Closure Plan Checklist: (19.15.17.13:NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate by a check mark in the box, that the documents are attached
by a check mark in the box, that the documents are attached.
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Encility Name and Permit Numbers (for limits, delline)
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subservice 14 of 10.15 (13.2).
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19,15,17,13 NMAC
Site Reclamation Plan - hased upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC
Opening to the state of the sta
Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Rate of Print ?
Name (Print): Ryan Price Title: St. Petroleum Engineer Signature: 1/14/08
Simon Kura N
Date: 1/14/08
1001
c-mail address: 1911 and edge pet com Telephone: 713-335-9808
OCD Approval: Permit Application (including closure plan) Closure Plan (only)
Closure Plan (only)
OCD Representative Signature: Chies Williams Approval Date: 1/16/08
Approval Date: 7/16/08
Title: Vest Seperves
OCI) Permit Number: P[-U] 3
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC
Closure Completion Date:
Ciosale Metaod:
☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method
If different from approved plan, please explain.
Closure Report Attachment Charliet, Instruction C.
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check
LJ Proof of Closure Notice
Proof of Deed Notice (if applicable)
☐ Plot Plan
Confirmation Sampling Analytical Results
Waste Material Sampling Analytical Popule
Ulsposal Facility Name and Permit Number
☐ Soft Backfilling and Cover Installation
L.J. Ke-vegetation Application Rates and Southern Touchestern
Site Recaination (Photo Documentation)
On-site Closure Location: Latitude
Operator Closure Certification: Longitude NAD: 1927 1983
hereby certify that the information and the last th
hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
MIDE (PRINT)
Title:
ognature;
Dute:
-mail address:
-mail address: Telephone:
-mail address:

of the other dientification

Buckeye

Edge Petroleum Operating Company, Inc. Southeast Lusk 27 Federal #1 Closed Loop Mud System

Design

Drilling mud will circulate through a closed system consisting of steel pits on the surface, mud pumps, piping on the surface to the rotating head, and return piping from the bell nipple back to the steel pits. Solids will be removed from the mud in the steel pits using the following equipment:

- 1) 2 shale shakers will be installed with 110-250 mesh screens. These shale shakers should remove solids down to 65 micron diameter. All return drilling mud will flow across the shale shakers.
- 2) A 6T4 mud cleaner will be installed to further remove solids to the 25 micron level. Drilling mud will be circulated through the mud cleaner using a 5x6x12 75 hp pump. This pump will generate the optimal pressure for the mud cleaner cones to process the solids.
- 3) A 518 centrifuge will pick up a portion of the effluent from the mud cleaner. The centrifuge will remove solids to the 10 micron level. The centrifuge will remove solids down to the 1 micron level after adding the dewatering unit, as discussed below.
- 4) A dewatering unit will add polymer to the flow stream entering the centrifuge to flocculate the solids. Flocculation increases the effective particle size of the solids, enhancing the performance of the centrifuge to remove solids down to the 1 micron level.
- 5) Roll-off bins (20 cubic yards per bin) and rails will be installed next to the steel pits so that the solids removed from the shale shakers, mud cleaner, and centrifuge fall directly into a bin. Once a bin is full, it is picked up by a truck and hauled to disposal. An empty bin is moved under the solids control equipment along the rail so that the solids control equipment can operate continuously.

Operation and Maintenance

Personnel dedicated exclusively to operating and maintaining the solids control equipment will be on site 24 hours per day while drilling. The solids control personnel will monitor the shale shakers, mud cleaner, centrifuge, dewatering unit, and all associated pumps and piping to make sure the equipment is functioning correctly. If equipment problems are identified, the solids control personnel will coordinate repair or replacement of the equipment. The solids control personnel will also monitor the level of solids in the roll-off bins and arrange for trucks to pick up the bins when they are filled.

Closure Plan

Cuttings and other solids will be hauled off to a permitted landfill according to OCD guidelines. Liquids will be re-used to the extent possible, but if liquids need to be disposed, they will also be hauled to a permitted disposal facility. Liquids to be temporarily stored on site will be placed in 500 bbl "frac" tanks.

For the Lusk 27-1 well, both solid waste and liquid waste will be taken to the Controlled Recovery, Inc. (CRI) "Halfway Facility" between Carlsbad and Hobbs.

NM-0:-0006