District I Energy, Miner	e of New Mexico	Form C-103
1625 N. French Dr. Hobbs, NM 88240	rals and Natural Resources	May 27. 2004 WELL API NO.
District 11 OIL CONCL	DVATION DIVISION	30 025 38927
1501 W. Oland MVC, Milosla, 140 00210	ERVATION DIVISION outh St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd Aztec NM 87410		STATE FEE X
District IV 1220 & St Francis Dr., Santa Fe, NM 87505	a Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORT (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (F PROPOSALS.)	DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name Jalmat Field Yates Sand Unit
1. Type of Well: Oil Well X Gas Well Other	r /	8. Well Number 234
2. Name of Operator Melroce Operating Company		9. OGRID Number
Melrose Operating Company	/	184860
3. Address of Operator		I 0. Pool name or Wildcat
1000 W. Wilshire #223, Oklahoma City, OK 73116	5	Jalmat; Tan-Yates-7 Rvrs
4. Well Location Unit Letter P 688 feet from	1 South 1: 1 104	50 East Fast
	the South line and 100	
Section 2 Township	· / · · · · · · · · · · · / / · _ / · / / · _ / / · _ / / / · _ / / / /	NMPM Lea County
I I. Elevation (Sho) 3579' GR	w whether Dl~ RKB, RT GR, etc	9
Pit or Below-erade Tank Application or Closure	<u></u>	I
	m nearest fresh water well Dis	stance from nearest surface water
Pit Liner Thickness: Inil Below-Grade Tank		nstruction Material
12. Check Appropriate Box to		
PERFORM REMEDIAL WORK PLUG AND ABANI TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPI OTHER:		
	early state all pertinent details, an	d give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 110 or recompletion.	3. For Multiple Completions: At	ttach wellbore diagram of proposed completion
of starting any proposed work). SEE RULE 110	4#, J55 new STC casing, set @ 4 sted to 1000 psi for 30 minutes, h o run casing. 55, LTC new casing to 4176'. Cea	429'. Cemented casing with 375 sx Cl C 2% neld.
of starting any proposed work). SEE RULE 110 or recompletion. 7-29-08: Spudded well, drill 12 l/4" hole. Ran 8 5/8", 2- CaCl, yield 1.3, circulated 4 sx to pit. WOC 18 hrs. Tes 8-1-08: Reached total depth of 4177'. Circulated hole to 8-2-08: RIH & ran open hole logs. Ran 5 l/2", 15.5#, J5 2% CaCl cement, 2.3 yield, tailed with 300 sx Cl C, 2%	4#, J55 new STC casing, set @ 4 sted to 1000 psi for 30 minutes, h o run casing. 55, LTC new casing to 4176'. Cea	429'. Cemented casing with 375 sx Cl C 2% neld.
of starting any proposed work). SEE RULE 110 or recompletion. 7-29-08: Spudded well, drill 12 I/4" hole. Ran 8 5/8", 2 CaCl, yield 1.3, circulated 4 sx to pit. WOC 18 hrs. Tes 8-1-08: Reached total depth of 4177'. Circulated hole to 8-2-08: RIH & ran open hole logs. Ran 5 I/2", 15.5#, J5 2% CaCl cement, 2.3 yield, tailed with 300 sx Cl C, 2% casing to 1000 psi for 30 minutes.	4#, J55 new STC casing, set @ 4 sted to 1000 psi for 30 minutes, h o run casing. 55, LTC new casing to 4176'. Cer 6 CaCl 1.3 yield. Circulated 56 s	429'. Cemented casing with 375 sx Cl C 2% neld.
of starting any proposed work). SEE RULE 110 or recompletion. 7-29-08: Spudded well, drill 12 l/4" hole. Ran 8 5/8", 2 CaCl, yield 1.3, circulated 4 sx to pit. WOC 18 hrs. Tes 8-1-08: Reached total depth of 4177'. Circulated hole to 8-2-08: RIH & ran open hole logs. Ran 5 l/2", 15.5#, J5 2% CaCl cement, 2.3 yield, tailed with 300 sx Cl C, 2% casing to 1000 psi for 30 minutes.	4#, J55 new STC casing, set @ 4 sted to 1000 psi for 30 minutes, h o run casing. 55, LTC new casing to 4176'. Ce: 6 CaCl 1.3 yield. Circulated 56 s	429'. Cemented casing with 375 sx Cl C 2% neld.
of starting any proposed work). SEE RULE 110 or recompletion. 7-29-08: Spudded well, drill 12 I/4" hole. Ran 8 5/8", 2- CaCl, yield 1.3, circulated 4 sx to pit. WOC 18 hrs. Tes 8-1-08: Reached total depth of 4177'. Circulated hole to 8-2-08: RIH & ran open hole logs. Ran 5 I/2", 15.5#, J5 2% CaCl cement, 2.3 yield, tailed with 300 sx Cl C, 2% casing to 1000 psi for 30 minutes.	4#, J55 new STC casing, set @ 4 sted to 1000 psi for 30 minutes, h o run casing. 55, LTC new casing to 4176'. Ce 6 CaCl 1.3 yield. Circulated 56 s CENNED 3 - 8 2008 BS OCD	429'. Cemented casing with 375 sx Cl C 2% held
of starting any proposed work). SEE RULE 110 or recompletion. 7-29-08: Spudded well, drill 12 I/4" hole. Ran 8 5/8", 2 CaCl, yield 1.3, circulated 4 sx to pit. WOC 18 hrs. Tes 8-1-08: Reached total depth of 4177'. Circulated hole to 8-2-08: RIH & ran open hole logs. Ran 5 I/2", 15.5#, J5 2% CaCl cement, 2.3 yield, tailed with 300 sx Cl C, 2% casing to 1000 psi for 30 minutes.	4#, J55 new STC casing, set @ 4 sted to 1000 psi for 30 minutes, h o run casing. 55, LTC new casing to 4176'. Ce: 6 CaCl 1.3 yield. Circulated 56 s CEIVED S - 8 2008 BS OCD	429'. Cemented casing with 375 sx Cl C 2% held. mented 5 1/2" casing with 550 sx lead Cl C, x to pit. Rig released. WOC 24+ hrs. Tested
of starting any proposed work). SEE RULE 110 or recompletion. 7-29-08: Spudded well, drill 12 l/4" hole. Ran 8 5/8", 2 CaCl, yield 1.3, circulated 4 sx to pit. WOC 18 hrs. Tes 8-1-08: Reached total depth of 4177'. Circulated hole to 8-2-08: RIH & ran open hole logs. Ran 5 l/2", 15.5#, J5 2% CaCl cement, 2.3 yield, tailed with 300 sx Cl C, 2% casing to 1000 psi for 30 minutes.	4#, J55 new STC casing, set @ 4 sted to 1000 psi for 30 minutes, h o run casing. 55, LTC new casing to 4176'. Ce: 6 CaCl 1.3 yield. Circulated 56 s CENNED S - 8 2008 BS OCD	429'. Cemented casing with 375 sx Cl C 2% held. mented 5 1/2" casing with 550 sx lead Cl C, x to pit. Rig released. WOC 24+ hrs. Tested
of starting any proposed work). SEE RULE 110 or recompletion. 7-29-08: Spudded well, drill 12 I/4" hole. Ran 8 5/8", 2: CaCl, yield 1.3, circulated 4 sx to pit. WOC 18 hrs. Tes 8-1-08: Reached total depth of 4177'. Circulated hole to 8-2-08: RIH & ran open hole logs. Ran 5 I/2", 15.5#, J5 2% CaCl cement, 2.3 yield, tailed with 300 sx Cl C, 2% casing to 1000 psi for 30 minutes.	4#, J55 new STC casing, set @ 4 sted to 1000 psi for 30 minutes, h o run casing. 55, LTC new casing to 4176'. Ce 6 CaCl 1.3 yield. Circulated 56 s CEIVED COD SOCO BSSOCO PSSOCO nplete to the best of my knowledg DCD guidelines ⊠ a general permit	429'. Cemented casing with 375 sx Cl C 2% neld

,,