

RECEIVED

RECEIVED

Form 3160-5
(April 2004)

AUG - 6 2008

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No 1004-0137
Expires March 31, 2007

HOBBS OGD

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1 Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator Apache Corporation

3a Address
3300 North "A" Street, Suite 7-150 Midland, Texas 79705

3b Phone No (include area code)
432-683-6511

4 Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit D, 330' FNL & 330' FWL, Section 12, T-21-S, R-37-E

5 Lease Serial No

NMLC 032096B

6 If Indian, Allottee or Tribe Name

7 If Unit or CA/Agreement, Name and/or No
East Blinberry Drinkard Unit No 32

8 Well Name and No

9 API Well No

30-025-06542

10 Field and Pool, or Exploratory Area
Eunice; Blinberry-Tubb-Drinkard, N

11 County or Parish, State

Lea, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompletable horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletable in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

See attached current and proposed plugged wellbore diagrams

Set CIBP @ 5,730'
Circulate plugging mud, pump 25 sx @ 5,730'
Pump 25 sx C cmt @ 3,199'
Pump 25 sx C cmt @ 2,520'
Perf & sqz 35 sx C cmt @ 1,520' - 1,420' WOC & TAG
Perf & Sqz 75 sx C cmt @ 313' to surface
Cut off wellhead and anchors, install dry hole marker.

Add Plug: @ 5352' (25 sx) covers
Top of Glorietta

Chg Plug: @ 2520' to 2570'
WOC Tag (120' plug)

Perf & Sqz: Both 5 1/2" & 7 5/8" @ 313'
Circ both in/out to surf.

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

14 I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

James F. Newman P.E.

Title P&A Manager, Basic Energy Services 432.687.1994

Signature

Date

07/17/2008

APPROVED

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by Chris Williams

Title

Office

AUG 3 2008

**JAMES A. AMOS
SUPERVISOR EPS**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

(Instructions on page 2)

CURRENT WELLBORE SKETCH Apache Corporation



Date July 24, 2008

RKB @ _____
DF @ _____
GL @ _____

Lease & Well No .
Legal Description :

County .
Field .
Date Spudded .
API Number
Status:

East Blinbry, Drinkard Unit #32
Unit Letter D, 330' FNL & 330' FWL, Section 12,
T-21-S, R-37-E
Lea State New Mexico
Eunice, Blinbry-Tubb-Drinkard, N
30-025-06542

10-3/4" csg @ 263' cmt'd w/ 250 sx

11" hole

Top Salt @ 1,520'

Base Salt @ 2,520'

7-5/8" 24# csg @ 3,149' cmt'd w/ 1,255 sx

6-3/4" hole

open perforations

5,780 - 5,812'
5,830 - 5,881'

5-1/2" 15.5# csg @ 5,897'
cmt'd w/ 362 sx

PROPOSED PLUGGED WELLBORE SKETCH Apache Corporation



Date July 24, 2008

RKB @ _____
DF @ _____
GL @ _____

Lease & Well No
Legal Description

County
Field
Date Spudded
API Number
Status

East Blinbry Drinkard Unit #32
Unit Letter D, 330' FNL & 330' FWL, Section 12,
T-21-S, R-37-E
Lea State New Mexico
Eunice, Blinbry-Tubb-Drinkard, N
30-025-06542
Proposed Plugged

10-3/4" csg @ 263' cmt'd w/ 250 sx

Perf & Sqz 75 sx C cmt @ 313' to surface

Top Salt @ 1,520'

Perf & sqz 35 sx C cmt @ 1,520 - 1,420' WOC & TAG

Base Salt @ 2,520'

Pump 25 sx C cmt @ 2,520'

7-5/8" 24# csg @ 3,149' cmt'd w/ 1,255 sx

Pump 25 sx C cmt @ 3,199'

6-3/4" hole

Set CIBP @ 5,730'

Circulate plugging mud, pump 25 sx @ 5,730'

open perforations

5,780 - 5,812'

5,830 - 5,881'

5-1/2" 15.5# csg @ 5,897'

cmt'd w/ 362 TOC @ 1,564' calc

PROPOSED PLUGGING PROCEDURE

- 1) Set CIBP @ 5,730'
- 2) Circulate plugging mud, pump 25 sx @ 5,730'
- 3) Pump 25 sx C cmt @ 3,199'
- 4) Pump 25 sx C cmt @ 2,520'
- 5) Perf & sqz 35 sx C cmt @ 1,520 - 1,420' WOC & TAG
- 6) Perf & Sqz 75 sx C cmt @ 313' to surface

Capacities

4 1/2" 9 5# csg	10 960	ft/ft3	0.0912	ft3/ft
5 1/2" 15.5# csg	7 483	ft/ft3	0.1336	ft3/ft
5 1/2" 17# csg	7 661	ft/ft3	0.1305	ft3/ft
7" 23# csg	4 524	ft/ft3	0.221	ft3/ft
7 3/4" 26 4# csg	3 775	ft/ft3	0.2648	ft3/ft
8 3/4" 24# csg	2 797	ft/ft3	0.3575	ft3/ft
8 3/4" 28# csg	2 853	ft/ft3	0.3505	ft3/ft
10 3/4" 40 5# csg	1 815	ft/ft3	0.5508	ft3/ft
7 1/8" openhole	2 957	ft/ft3	0.3382	ft3/ft
8 3/4" openhole	2 395	ft/ft3	0.4176	ft3/ft
12 1/4" openhole	1 222	ft/ft3	0.8185	ft3/ft

BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972

Permanent Abandonment of Federal Wells
Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. **Dry Hole Marker:** All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. **Subsequent Plugging Reporting:** Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. **Trash:** All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.