

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised June 10, 2003

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-36432
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Shelley 34 State
8. Well Number 003
9. OGRID Number 023230
10. Pool name or Wildcat Skaggs; Drinkard (57000)

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Tom Brown, Inc.

3. Address of Operator  
P O Box 2608, Midland, TX 79702

4. Well Location  
Unit Letter B : 990 feet from the North line and 1700 feet from the East line  
Section 34 Township 19S Range 37E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3606 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐


CASING TEST AND CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/29/2003 Spud Well @ 20:00

10/30/2003 Drill 12-1/4" hole to 1430'. Ran 34 jt of 8-5/8 24#, J-55 csg (Total length 1441 set @ 1435') Pump 20 bbls FW ahead. Cement w/ 435 sx of Haliburton Light Premium Plus + 1/4# sx flocelo + 6# salt, 12.5 ppg. Tail in w/ 205 sx Premium Plus + 2% Calcium Chloride, 14.8 ppg, 1.345yld. Displace w/ 87 bbl brine water. Circ 80 sx to ph. 3831' Cut off conductor and 8-5/8 csg and install head. NU BOP



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Diane Kuykendall TITLE Operations Asst/Tech DATE 11/03/03

Type or print name Diane Kuykendall E-mail address: dkuykendall@tombrown.com Phone No. 432-688-9773

(This space for State use)

APPROVED BY Harry W. Wink TITLE OC FIELD REPRESENTATIVE II / STAFF MANAGER DATE NOV 10 2003

Conditions of approval, if any