

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		RECEIVED State of New Mexico Department of Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 HOBBS OGD		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-38664 ✓		5. Indicate Type of Lease STATE ☐ FEE ☒ ✓	
		State Oil & Gas Lease No. N/A		7. Lease Name or Unit Agreement Name Big Kick ✓	
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____		b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER _____		8. Well No. 002 ✓	
2. Name of Operator Apache Corporation ✓ 873		3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224		9. Pool name or Wildcat House; Blinebry, South ✓ 33 225	
4. Well Location Unit Letter C : 790 Feet From The North Line and 2310 Feet From The West Line Section 13 Township 20S Range 38E NMPM Lea County					
10. Date Spudded 05/17/2008	11. Date T.D. Reached 05/27/2008	12. Date Compl. (Ready to Prod.) 06/26/2008	13. Elevations (DF& RKB, RT, GR, etc.) 3,557'	14. Elev. Casinghead	
15. Total Depth 7320'	16. Plug Back T.D. 6514' RBP	17. If Multiple Compl. How Many Zones? NA	18. Intervals Drilled By X	Rotary Tools	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 6053-6401' (House; Blinebry, S)				20. Was Directional Survey Made No	
21. Type Electric and Other Logs Run DLL-MG, SGR, CSITT, CN/PhD				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1604'	12-1/4"	750 sx / circ	
5-1/2"	17#	7320'	7-7/8"	1370 sx / TOC @ 540'	CBL
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE
					2-7/8"
					6419'
26. Perforation record (interval, size, and number) Blinebry: 6053-6401' (2 JSPF, 54 holes) - producing Tubb: 6614-6821' (2 JSPF, 45 holes) - RBP @ 6514' Drinkard: 6981-7076' (2 JSPF, 45 holes) - RBP @ 6935'			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 6053-6401 2Kgal 15%HCl, 44Kgal SS-25 + 82K# 20/40 6614-6821 2Kgal 15%HCl, 39Kgal SS-25 + 82K# 16/30 6981-7076 2Kgal 15%HCl, 43Kgal SS-35 + 64K# 16/30		
28. PRODUCTION					
Date First Production 06/26/2008		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - Rod Pump		Well Status (Prod or Shut-in) Producing	
Date of Test 07/05/2008	Hours Tested 24 hours	Choke Size	Prod'n For Test Period	Oil - Bbl 25	Gas - MCF 60
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl. 134
				Gas - Oil Ratio 2400	
				Oil Gravity - API - (Corr.) 37.7	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold					Test Witnessed By Apache Corporation
30. List Attachments Inclination Report, C-102, C-103, C-104 (Logs mailed 6/6/08)					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature Sophie Mackay		Printed Name Sophie Mackay		Title Engineering Tech	
E-mail Address sophie.mackay@apachecorp.com				Date 07/10/2008	

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2896'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 3685'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4280'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5598'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 6045'	T. Gr. Wash	T. Morrison	T.
T. Tubb 6538'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6861'	T. Bone Springs	T. Entrada	T.
T. Abo 7110'	T. Rustler 1550'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology