

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-37231
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. NM13279
7. Lease Name or Unit Agreement Name Bandit 15 Fed Com
8. Well Number 2
9. OGRID Number 20165
10. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator  
Samson Resources Company

3. Address of Operator  
200 N. Loraine ST., Ste 1010, Midland, TX 79701

4. Well Location  
Unit Letter J : 1980 feet from the S line and 1980 feet from the E line  
Section 15 Township 20S Range 33E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3580' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: Test Atoka ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

POH w/ pkr.  
Set CIBP @ 13605'. Dump 35' cmt.  
Set CIBP @ 13331'. Dump 35' cmt. Test casing to 2500 psi.  
Perf Atoka @ 13096' - 13106'  
Acidz Atoka (13096' - 13106') w/ 2100 gal 15%. Swab dry.  
Perf Atoka @ 12864' - 12888'.  
Test. Wet. Flwd 30 BWPH.  
Shut in.

No H2S.

RECEIVED

AUG 21 2008  
HOBBS OCD

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kenny Krawietz TITLE \_\_\_\_\_ DATE 08-19-08

Type or print name Kenny Krawietz E-mail address: kkrawietz@samson.com PHONE: 432-686-6337

For State Use Only

APPROVED BY: Chris Williams TITLE OC DISTRICT SUPERVISOR/GENERAL MANAGER DATE AUG 25 2008

Conditions of Approval (if any):