

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
Revised June 10, 2003

WELL API NO.
30-025-38876

5. Indicate Type of Lease
STATE ☐ FEE ☒

State Oil & Gas Lease No. N/A

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER

1b. Type of Completion:
NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER

2. Name of Operator
Apache Corporation

3. Address of Operator
6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224

4. Well Location
Unit Letter N : 330 Feet From The South Line and 2250 Feet From The West
Section 15 Township 22S Range 37E NMPM Lea County

10. Date Spudded
06/10/2008

11. Date T D. Reached
06/19/2008

12. Date Compl. (Ready to Prod.)
07/21/2008

13. Elevations (DF& RKB, RT, GR, etc.)
3377' GR

14. Elev. Casinghead

15 Total Depth
6700'

16. Plug Back T.D.
5930' RBP

17. If Multiple Compl. How Many Zones?
NA

18. Intervals Drilled By
X

Rotary Tools

Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name
5426-5674' (Blinebry O&G)

20. Was Directional Survey Made
No

21. Type Electric and Other Logs Run
SD/DSN, DLL-MG, Borehole Volume Plot, BSAT

22. Was Well Cored
No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24#	1170'	12-1/4"	650 sx / circ	
5-1/2"	17#	6700'	7-7/8"	1150 sx / TOC@2600'	CBL

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-7/8"	5893'	

26. Perforation record (interval, size, and number)
Blinebry: 5426-5674' (2 JSPF, 53 holes) Producing
Tubb: 5976-6100' (2 JSPF, 39 holes) RBP @ 5930'
Drinkard: 6398-6504' (2 JSPF, 48 holes) RBP @ 6320'

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
5426-5674	3Kgal 15%HCl, 36Kgal SS-25 + 82K# 20/40
5976-6100	3Kgal 15%HCl, 36Kgal SS-25 + 82K# 20/40
6398-6504	3Kgal 15%HCl, 39Kgal SS-35 + 60K# 20/40

28. PRODUCTION

Date First Production
07/21/2008

Production Method (Flowing, gas lift, pumping - Size and type pump)
Pumping - Rod Pump

Well Status (Prod. or Shut-in)
Producing

Date of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
07/31/2008	24 hours			6	112	157	18,667

Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)
						35.8

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
Sold

Test Witnessed By
Apache Corporation

30. List Attachments
Inclination Report, C-102, C-103, C-104 (Logs mailed 7/3/08)

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature
E-mail Address

Printed Name
Name Sophie Mackay

Title
Engineering Tech

Date
08/14/2008

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2578'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2800'	T. Devonian	T. Menefee	T. Madison
T. Queen 3325'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3603'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3871'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5047'	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 5459'	T. Gr. Wash	T. Morrison	T.
T. Tubb 5960'	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6279'	T. Bone Springs	T. Entrada	T.
T. Abo 6518'	T. Rustler 1123'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology