District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.
For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

## Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

	ply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: Majosa Oparating INC	ogr <b>i</b> 8#: 184860
Address: 1000 W. Wilshire Suite 223 DKIGh Facility or well name: Walmat Field Yote and U	oma City, DK. 73116
Facility or well name: Want Field Yote Jand Us	vd 180
API Number: 30-025-38925 38870	OCD Permit Number:
	S Range 35 E County: Lla
Center of Proposed Design: Latitude N32.39749	Longitude <u>W /03 , 32-359</u> NAD: <b>▼</b> 1927 ☐ 1983
Surface Owner:  Federal Kastate  Private Tribal Trust or Indian	Allotment Elw 3598
☑ Pit: Subsection F or G of 19.15.17.11 NMAC	Closed-loop System: Subsection H of 19.15.17.11 NMAC
Temporary: 🔀 Drilling 🗌 Workover	Drying Pad Tanks Haul-off Bins Other
☐ Permanent ☐ Emergency ☐ Cavitation ☐ Steel Pit	☐ Lined ☐ Unlined
☑ Lined □ Unlined	Liner type: Thicknessmil
Liner type: Thickness 20 mil LLDPE 🛚 HDPE 🗆 PVC	☐ Other
Other String-Reinforced	Seams:  Welded  Factory Other
Seams: Welded  Factory Other	Volume:bblyd³
Volume: 2900 50 Dimensions: L 100 x W 40 x D 20	Dimensions: Lengthx Width
Below-grade tank: Subsection I of 19.15.17.11 NMAC	Fencing: Subsection D of 19.15.17.11 NMAC
Volume:bbl	☐ Chain link, six feet in height, two strands of barbed wire at top
Type of fluid:	Four foot height, four strands of barbed wire evenly spaced between one and
Tank Construction material:	four feet
☐ Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11 NMAC
☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other
☐ Visible sidewalls and liner	☐ Monthly inspections
☐ Visible sidewalls only	Signs: Subsection C of 19.15.17.11 NMAC
Other	12'x24', 2' lettering, providing Operator's name, site location, and
Liner type: Thicknessmil	emergency telephone numbers
Other	☐ Signed in compliance with 19.15.3.103 NMAC
Alternative Method: Submittal of an exception request is required. Exceptions must be	Administrative Approvals and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to
submitted to the Santa Fe Environmental Bureau office for consideration	19.15.17 NMAC for guidance.
of approval.	Please check a box if one or more of the following is requested, if not leave blank:
	Administrative approval(s): Requests must be submitted to the
	appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval.
	☐ Exception(s): Requests must be submitted to the Santa Fe
	Environmental Bureau office for consideration of approval

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-	
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes 🛛 No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes 🖾 No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes 🔀 No ☐ NA
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applies to permanent pits)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes 🔀 No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes 🔁 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes 【 No
<ul> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	☐ Yes 【 No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes 🗓 No
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	Yes 🗷 No
Within a 100-year floodplain FEMA map	☐ Yes 🔀 No
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the dattached.    Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC   Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.17   Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC   Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	.9 NMAC
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC	1967
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached.  Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	f 19.15.17.9
Previously Approved Design (attach copy of design) API Number:	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC	
Hydrogeologic Report - based upon the requirements of Panagraph (1) of Subsection B of 19.15.17.9 NMAC   Sining Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.11 NMAC   Curried Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC   Dike Processon and Simetural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Dike Processon and Simetural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Diality Control/Quality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Diality Control/Quality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Diality Control/Quality Assurance Construction   Plans		ocuments are
Siting Criteria Compilance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC   Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Carlo Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Carlo Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Carlo Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Carlo Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Carlo Design - based upon the appropriate requirements of 19.15.17.12 NMAC   Carlo Design - based upon the appropriate requirements of 19.15.17.13 NMAC   Carlo Design - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the upon the appropriate requirements of 19.15.17.13 NMAC   Closure Plan - based upon the	☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC   County Control Plant   Nature   Plant		
Lines Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality Control(Quality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Prebaird and Overtopoling Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nuisance or Hazardous Ostora, including 14.5, revention Plan   Exercise Plan   Prevention Pl	Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC	
Clear Specifications and Compatibility Assessment - bised upon the appropriate requirements of 19.15.17.11 NMAC   Quality Control(Quality Assumence Construction and Installation Plants of 19.15.17.12 NMAC   Prechand and Overtoping Prevention Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Prechand and Overtoping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Construction   Control Plan   Emergency Reposters Plant   Proposed Closure Plan - Plants of University   Proposed Closure Method:   Waste Exercaviation and Removal   Glosure Method:   Waste Exercaviation and Removal   Glosure Plants   Proposed Closure Method:   Waste Exercaviation and Removal   Glosure Plants   Proposed Closure Method:   Waste Exercaviation and Removal   Glosure Plants   Proposed Closure Method:   Waste Exercaviation and Removal   Glosure Plants   Proposed Closure Method:   Waste Exercaviation and Removal   Glosure Plants   Proposed Closure Method:   Waste Exercaviation and Removal   Glosure Plants   Proposed Closure Method:   Waste Exercaviation and Removal   Glosure Plants   Proposed Closure Method:   Waste Exercaviation and Removal   Glosure Plants		
Quality Centrol/Quality Assurance Construction and Installation Plan		
Ground water is between 50 and 100 feet below the bottom of the buried waste.	Quality Control/Quality Assurance Construction and Installation Plan	
Musiance or Hazardois Odors, including H <sub>2</sub> S, Prevention Plan		
Ground water is between 50 and 100 feet below the bottom of the buried waste.		
Gold Picked Waste Stream Characterization   Monitoring and Inspection Plan   Closure Plan   Closure Plan   Section Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Glosure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Proposed Closure: 19.15.17.13 NMAC   Type: ☑ Drilling ☐ Workover ☐ Emergency ☐ Cavitation ☐ Permanent Pit ☐ Below-grade Tank ☐ Closed-loop System ☐ Alternative Proposed Closure Method: ☐ Waste Removal ☐ Waste Removal ☐ Closed-loop systems only) ☐ On-site Closure Method (Only for temporary pits and closed-loop systems) ☐ ☐ In-place Burial ☑ On-site Trench Burial ☐ On-site Trench Burial ☐ On-site Trench Burial ☐ On-site Trench Burial ☐ On-site Proposed Steptises on the Submitted to the Santa Fe Environmental Bureau for consideration) ☐ Indicate the Submitted Instructions: Each stifing criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided before. Requests regarding changes to certain stifing criteria are private administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search, USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search, USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  No lake for the State Engineer - iWATERS database search, USGS; Data obtained		
Type: [2] Drilling   Workover   Emergency   Cavitation   Permanent Pit   Below-grade Tank   Closed-loop System   Alternative   Proposed Closure Method:   Waste Excavation and Removal   Waste Removal (Closed-loop systems only)		
Proposed Closure Method:		<b>-</b>
Waste Removal (Closed-loop systems only)	•	_ Alternative
On-site Closure Method (Only for temporary pits and closed-loop systems)     Langea Burlai   &   On-site Tench Burlai   On-site Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)   Instructions: Each stiding criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain stiling criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10   NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes No No No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes No No No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes No No No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes No No No Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   Yes No No No Office of the State Engineer - iWATERS database; which is not obtained from nearby wells   Yes No No No Office of the State Engineer - iWATERS database; visual inspection (errification) of the proposed site   Yes No No No Office of the State Engineer - iWATERS database; visual inspection (certification) of the proposed site   Yes No No No Office of the State Engineer - iWATERS database; visual		
In-place Burial \( \begin{align*}{2} \be		
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)		
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo, Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within 100 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within 100 horizontal feet of a wetl		nsideration)
source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000	Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	
the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet form a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within 500 feet of a wetland.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within 100-year floodplain.		
office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10  NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Within an Within 100 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within an unstable area.  Engineering measure		
### ACF or guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within 1000 horizontal feet of a private, domestic fresh water well or spring in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  Within 1000 horizontal feet of any other fresh water wel		
Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of initial application.  Within 1000 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application.  Within incorporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of initial application.  Within 1000 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application.  Yes M No  Pres No  Within 1000 horizontal feet of a private, domestic fresh water well or spring, in exis		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
Ground water is between 50 and 100 feet below the bottom of the buried waste  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map, Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of initial application.  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Within 500 feet of a wetland.  Within 500 feet of a wetland.  Within 500 feet of a wetland.  Within an Within 400 wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within an unstable area.  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Within 500 feet for a wetland.  Within 500 feet for a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	- NW Office of the State Engineer - TWATERS database search, USOS, Data obtained from hearby wens	LXL NA
Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site in existence at the time of initial application.  Within 500 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Within 500 feet of a wetland.  Within 500 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Within 500 feet of a wetland.  Within 500 feet of a wetland.  Within 500 feet of a wetland.  Within 600 feet of a wetland.  Within 600 feet of a wetland.  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	₩ NA
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	Ground water is more than 100 feet below the bottom of the buried waste.	⊠ Yes□ No
lake (measured from the ordinary high-water mark).   Topographic map; Visual inspection (certification) of the proposed site   Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.   Visual inspection (certification) of the proposed site; Aerial photo; Satellite image   Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.   NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site   Yes ☒ No within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.   Written confirmation or verification from the municipality; Written approval obtained from the municipality   Yes ☒ No within 500 feet of a wetland.   US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site   Yes ☒ No within the area overlying a subsurface mine.   Yes ☒ No within an unstable area.   Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map   Yes ☒ No within a 100-year floodplain.		
lake (measured from the ordinary high-water mark).   Topographic map; Visual inspection (certification) of the proposed site   Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.   Visual inspection (certification) of the proposed site; Aerial photo; Satellite image   Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.   NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site   Yes ☒ No within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.   Written confirmation or verification from the municipality; Written approval obtained from the municipality   Yes ☒ No within 500 feet of a wetland.   US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site   Yes ☒ No within the area overlying a subsurface mine.   Yes ☒ No within an unstable area.   Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map   Yes ☒ No within a 100-year floodplain.	Within 200 feet of a continuously florid and	
- Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		L Yes LEN NO
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological  Society; Topographic map  Within a 100-year floodplain.		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological  Society; Topographic map  Within a 100-year floodplain.		Yes 🔼 No
watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	Visual inspection (certification) of the proposed site, Aerial photo, Saterite image	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		Yes 🔀 No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological  Society; Topographic map  Within a 100-year floodplain.	- NW Office of the State Engineer - TWATERS database; Visual Inspection (certification) of the proposed site	
adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological  Society; Topographic map  Within a 100-year floodplain.	Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes X No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.  □ Yes ☑ No		-
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.	- Written confirmation or verification from the municipality; Written approval obtained from the municipality	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.  □ Yes ☑ No	Within 500 feet of a wetland.	☐ Yes 🏗 No
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. □ Yes ☑ No	- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain. □ Yes ☑ No	Within the area overlying a subsurface mine	□ Vool® N-
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.  □ Yes ☑ No		☐ res [2]- No
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain.		
Society; Topographic map  Within a 100-year floodplain.		<b></b>
Within a 100-year floodplain. ☐ Yes 🔀 No		∐ Yes Lyd No
	Society, ropographic map	
	Within a 100-year floodplain.	☐ Yes 🔀 No

	estructions. Each of the following items must be attached to the
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) In closure plan. Please indicate, by a check mark in the box, that the documents are a protocols and Procedures - based upon the appropriate requirements of 19.15.  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and dri Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection I Site Reclamation Plan - based upon the appropriate requirements of Subsection I	Intrached. 17.13 NMAC rements of Subsection F of 19.15.17.13 NMAC Il cuttings) quirements of Subsection H of 19.15.17.13 NMAC of 19.15.17.13 NMAC in G of 19.15.17.13 NMAC
Waste Removal Closure For Closed-loop Systems That Utilize Haul-off Bins On or facilities for the disposal of liquids, drilling fluids and drill cuttings.  Disposal Facility Name:	ly: (19.15.17.13.D NMAC) Instructions: Please indentify the Juctuly Disposal Facility Permit Number:
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the	following items must be attached to the closure plan. Please indicate.
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of Size Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.  Protocols and Procedures - based upon the appropriate requirements of 19.15.  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Size Naste Material Sampling Plan - based upon the appropriate requirements of Size Soil Cover Design - based upon the appropriate requirements of Subsection High Re-vegetation Plan - based upon the appropriate requirements of Subsection I Site Reclamation Plan - based upon the appropriate requirements of Subsection I	rements of 19.15.17.10 NMAC Subsection F of 19.15.17.13 NMAC opriate requirements of 19.15.17.11 NMAC 17.13 NMAC irements of Subsection F of 19.15.17.13 NMAC ubsection F of 19.15.17.13 NMAC ill cuttings or in case on-site closure standards cannot be achieved) of 19.15.17.13 NMAC of 19.15.17.13 NMAC
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate	and complete to the best of my knowledge and belief.
Name (Print): CAM (SOB) in 5	Title:
Signature: Conkollis	Date: 8/25/08
e-mail address:	Telephone: 575-390-4677
OCD Approval: Permit Application (including closure plan) Closure Plan	
OCD Representative Signature:	(only)  Approval Date: 8.29.08
OCD Representative Signature:  ENVIRONMENTAL ENCINEED	
OCD Representative Signature: ENVIRONMENTAL ENGINEER	Approval Date: 8°. 29 . 08
OCD Representative Signature:  ENVIRONMENTAL ENGINEER  Closure Report (required within 60 days of closure completion): Subsection K	Approval Date: 8.29.08  OCD Permit Number: of 19.15.17.13 NMAC
OCD Representative Signature:  ENVIRONMENTAL ENGINEER  Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternative  If different from approved plan, please explain.	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
OCD Representative Signature:  ENVIRONMENTAL ENGINEER  Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
OCD Representative Signature:  ENVIRONMENTAL ENGINEER  Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
OCD Representative Signature:  ENVIRONMENTAL ENGINEER  Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
OCD Representative Signature:  ENVIRONMENTAL ENGINEER  Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
OCD Representative Signature:  ENVIRONMENTAL ENGINEER  Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternative  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
OCD Representative Signature:  ENVIRONMENTAL ENGINEER  Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternative If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)	Approval Date: 8.29.08  OCD Permit Number:
Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude Longitud	Approval Date: 8.29.08  OCD Permit Number:  of 19.15.17.13 NMAC  Closure Completion Date:
Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)	Approval Date: 8.29.08  OCD Permit Number:
Closure Report (required within 60 days of closure completion): Subsection K  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternative  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan  Confirmation Sampling Analytical Results  Waste Material Sampling Analytical Results  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)  On-site Closure Certification:  I hereby certify that the information and attachments submitted with this closure retered.	Approval Date: 8.29.08  OCD Permit Number:
Title:    ENVIRONMENTAL ENGINEER	Approval Date: 8.29.08  OCD Permit Number:
Closure Report (required within 60 days of closure completion):  Closure Method:  Waste Excavation and Removal On-Site Closure Method Alternation  If different from approved plan, please explain.  Closure Report Attachment Checklist: Instructions: Each of the following item mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable)  Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude  Coperator Closure Certification: I hereby certify that the information and attachments submitted with this closure repeblief. I also certify that the closure complies with all applicable closure requirements.	Approval Date: 8.29.08  OCD Permit Number:

# **Blade Services LLC**

Phone # (575) 390-5004 Hobbs, NM 88240

August 24, 2008

Melrose Operating Company 1000 W. Wilshire, Suite 223 Oklahoma City, OK 73116

Attn: Mr. Cam Robbins Production Supervisor

RE: Work Plan For Pit Closure Located at Jalmat Field Yates Sand, Unit # 187; U/L A Sec 13, T22S and R35E, API #30-025-38873 of Lea County, New Mexico

Dear Mr. Robbins:

Blade Services LLC, Inc. would like to take this time to thank you and Melrose Operating Co., for the opportunity to provide our professional services. Attached you will find our work plan and cost for the above listed site.

If you have any questions and/or need more data in regards to projects please call at any time. You can reach me at 575-390-5004

Sincerely,

Rick Navarrette, Sr. Project Manager

Blade Services LLC

### Summary/Overview

The Jalmat Field Yates Sand unit site should be completed and remediated in accordance with the standards of the NMOCD. Pit closure of the temporary drilling pit will be addressed accordingly.

The potential contaminates of concern are mid to high-level concentrations of production water and drill cuttings circulated into a temporary drilling pit from well bore.

The lands primary use is domestic pasture for ranching and the production of oil and gas.

The USGS-OCD water map for this area shows the depth to ground water to be in the 250' range BGS.

Pursuant to the standards of the NMOCD, the clean up level for this site will be at <5,000ppm of TPH, <50ppm for BTEX and chlorides less than <500ppm.

The following scope of work was based on data from our site visit and the requirements of the NMOCD for site clean up.

### Scope of Work for Entombment and site reclamation

**Note**: Melrose Operating Co. has requested for Blade Services, LLC., to remove and remediate reserve pit drill cuttings for pit closure. Melrose has also requested that Blade Services submit a copy of results and reclamation plan to NMOCD for entombment of impacted soils.

- ✓ First Blade Services will call One-Call for line spot clearance before any excavation at the site is started.
- ✓ Blade Services will mobilize to the site located in the area Southwest of Eunice, NM equipment and personnel necessary to start and complete the site remediation as required to get the site back into compliance.

- ✓ Blade Services will have Ricky Navarrette delineate the site vertical and horizontal for chloride's to determine the extent of impacted soil. Samples will then be sent to Trace Analysis lab for analysis. Once analysis are sent back with the results NMOCD will then be contacted for approval before any capping or pit closure is resumed. Due to the size of reserve pit, Blade Services will split the site into quadrants testing 25% of impacted soils. Blade Services will test the vertical; starting one foot from mud removal into deep bury pit.
- ✓ Blade Services LLC., will then start excavation of impacted soil for on-site deep bury pit. Impacted soils will then be mixed on a 3 to 1 ratio, then taking a grab sample from mixture and taking sample to Trace Analysis for a paint filtration testing method. Once method is determined that mixture has passed and approved by OCD. Mixture will then be placed in an approved reinforced 20ml poly liner from West Texas plastics for entombment. The entombment pit will be approximately 100x40x20 foot deep; which will hold 2,900 cubic yards of material. Once all contents are placed in entombment pit; Blade Services will cap pit with an approved 20ml poly liner from West Texas Plastics. Then pit will be backfilled so that contents are 4 foot below ground level.
- ✓ Blade Services will have Ricky Navarrette field screen the site during the excavation and once the levels have dropped below NMOCD guidelines, final samples will be personally taken to Trace Analysis lab for analysis.
- ✓ If site does not clear NMOCD guidelines on the 3 to 1 mix ratio; this will be determined with a paint filter testing method at Trace Analysis. Blade Services will then submit a request for waste removal to the NMOCD office. Then waste material will be transferred to (Sundance Disposal) or and approved NMOCD disposal site.
- ✓ Once all of the remediation criteria has been met for site closure and compliance, the site will be backfilled with clean material from the site. The site will be contoured with a slight crown to prevent the ponding of any rain water and reseeded; with the

proper seed according to the NMOCD. Vegetative cover will equal 70% of the native perennial vegetative cover consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons or until successful growth is established.

✓ Trench burial pit will be marked by an approved steel maker, no less than four inches in diameter, cemented in a hole three feet deep in the center of the onsite burial. The marker will be flushed with the ground to allow access of the active well pad and for safety concerns. The marker will include a threaded collar to be used for future abandonment. The top of the marker will contain a welded steel plate 12" square that indicates the onsite burial of the temporary pit. The plate will be easily removable and a four foot tall riser will be threaded into the top of the collar marker and welded around the base with the operator's information. The operator's information will include the following: Operator name, ease name, well name and number, unit number, section, township, range and an indicator that the marker is an onsite burial location.

9.	Once all of the closure criteria have been met, a final closure report will be
	prepared by Blade Services. This report will include a summary of
	remediation operations, findings on-site and lab analysis, site maps and
	project photos.

If you have any questions and/or need more data in regards to this project please call 575-390-5004 at any time.

Sincerely,

Rick Navarette,

Sr. Project Manager Blade Services LLC.

Pil Nama

			66	\$	
900 9228 8466			65E. 2281 4L 661	65E.	
100 100 100 100 100 100 100 100 100 100			801 W 3 S	V513	
	4		,		
017	tous,		3,000		
	£.		1,0339), Charles		
		/ DD /			
100 100 100			98.9 98.68 5hL		e destribution de l'année de l'an
18. 1 8.8 .68.7			18 S.		
01 M N 18			SO EN		
	•				
		·			
				1	
				1	^ >
7					
)/			191		
10		000		U 0	
1658 1678 13		-2.5e 0h2e: 25468	858 h78:	558= 1168: 1168:	
•		35:		103 201	
	65	N. CY	2	7 И	
90/	,				
2/31		,		081	
			•	* NS	
L*				<u>Ur</u>	•
					•


Print - Maps Page 1 of 1



### Melrose Operating Inc.

- 1. **JFYSU #179**
- 2. JFYSU #180
- 3. **JFYSU #185**
- 4. JFYSU #187





### Melrose Operating Inc.

- 1. **JFYSU #179** Unit D,Sec13,T22S,R35E API#30-025-38869
- 2. **JFYSU #180** Unit C,Sec13,T22S,R35E API #30-025-38925
- 3. **JFYSU #185**
- 4. JFYSU #187

