FORMAPPROVED

		Æ INTERIOR	,	OM B No. 1004-0137 Expires: March 31, 2007		
	BUREAU ( AND MANAGEMENT		1	5. Lease Serial No. NMLC031621B		
SUNDRY NOTICES AND REPORTS ON WELLS					Allottee or Tribe Name	
	is form for proposals ell. Use Form 3160 - 3			6. II Indian,	Allottee of Thoe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well Gas Well Other				8. Well Nar	ne and No.	
2 NameofOperator John H. Hendrix Corporation				Britt B-18 No. 1  9. API Well No		
3a Address 3b. PhoneNo. (include area code)				30-025-		
P. O. Box 3040 Midland TX 79702-3040 (432)684-6631				10. Field and Pool, or Exploratory Area Eunice - Monument 11 County or Parish, State Lea County, NM		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)						
660' FNL & 660' FWL, Sec. 18, T20S, R37E						
12. CHECK AI	PPROPRIATE BOX(ES)	TO INDICATE NATU	RE OF NOTICE, RE	EPORT, OF	OTHER DATA	
TYPE OF SUBMISSION TYPE OF ACTION						
X Notice of Intent	Acidize AlterCasing	Deepen FractureTreat	Production (Star	t/Resume)	Water Shut-Off Well Integrity Other	
Subsequent Report	Casing Repair Change Plans	New Construction Plug and Abandon	Recomplete Temporarily Aba	andon	Ottici	
Final Abandonment Notice	Convert to Injection	PlugBack	Water Disposal			
determined that the site is read The following is an initia once operations are star	y for final inspection) I plan to P&A the sub rted Any changes wi	ject well. Condition ill be approved by the	s may change ne BLM.		een completed, and the operator has	
1. Set CIBP @ 3450' to cover perfs. 3496 - 3656'. Spot 35 sx. cement plug on to of CIBP.					RECEIVED	
<ol> <li>Mix &amp; spot 10# P&amp;A mud fr. 3400' to surface.</li> <li>Set 25 sx. plug (150') 75' below to 75' above base of salt which is 2298'. Note Cement top behind 5-1/2" csg. is 1960'.</li> <li>Set 25 sx. plug (150') 75 below to 75' above top of salt at 1175'. Csg. leak @</li> </ol>					<sub>AR</sub> - 9 2006	
650' was repaired in 1959'. Bottom of this squeeze is @ 1210'. Top of squeeze is unknown.  5. Perf. squeeze holes @ 358' & attempt to circ. cement to surface for 7-5/8" - 10-3/4" annulus & 5-1/2" x 7-5/8" annulus leaving 5-1/2" csg. full of cement.  6. Remove wellhead & install P&A marker.					DLAND, TX	
14. I hereby certify that the fore Name (Printed/Pyged) Ronnie H. Westbrook	-	Title	Vice President			
Signature Signature	in AMen	The Date	02/21/2006			
4	THIS SPACE FOR	R FEDERAL OR S	TATE OFFICE	USE		
Approved by L=5 13 at Conditions of approval, if any, are certify that the applicant holds legi	attached Approval of this no	otice does not warrant or	itle P.E.	1	Date 3/2/06.	
which would entitle the applicant	to conduct operations thereo	on	Office			
States any false, fictitious or frau	tle 43 U S C Section 1212, madulent statements or represen	ake it a crime for any person itations as to any matter w	thin its jurisdiction.	to make to an PPROV	y department or agency of the United  ALSUBJECT TO	
(Instructions on page 2)			<u> </u>		TATELY	

GENERAL REQUIREMENTS
AND SPECIAL STIPULATIONS **ATTACHED**