RECEIVEL

OCD-HOBBS Form 3160-5 FORM APPROVED TED STATES OM B No. 1004-0137 Expires: March 31, 2007 (April 2004) BARTMENT OF THE INTERIOR I LAND MANAGEMENT 5. Lease Serial No. LC-032096-B NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE- Other instructions on reverse side. 1. Type of Wel X Öil Well Gas Well 8. Well Name and No. LOCKHART "B-35" 2. Name of Operator APACHE CORPORATION 9. API Well No. 39037 30 · O= 3a Address 6120 SOUTH YALE SUITE 1500 3b. Phone No. (include area code) TULSA, OKLAHOMA 74136-4224 ---918=491=4954 ----10. Field and Pool, or Exploratory Area EUNICE BLINEBRY TUBB DRINK.-NORTH 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 330' FNL & 330' FEL SECTION 35 T21S-R37E LEA CO. NEW MEXICO 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Acidize Deepen Production (Start/Resume) Water Shut-Off XX Notice of Intent Alter Casing Fracture Treat Reclamation Well Integrity Casing Repair Recomplete New Construction Subsequent Report Change Plans Plug and Abandon Temporarily Abandon Final Abandonment Notice Convert to Injection Plug Back Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 1. APACHE CORPORATION requests the approval to test the B.O.P. on-their LOCKHART "B-35" # 9 to 2000 PSI. Testing to be done by a third party. The maximum anticipated bottom hole pressures in the BLINEBRY, TUBB, & DRINKARD are estimated to be 1600PSI, 1700 PSI, and 1800 PSI respectively. This is supported by a 24 hour shutin test performed on 09/05/08 indicating less than 1000 PSI bottom hole pressure after a 24 hour shutin pressure on the LOCKHART "A-27" # 12. 2. APACHE CORPORATION also requests the approval to change the cementing on the surface casing as follows: Cement with 450 Sx. of Class "C" cement +4% Bentonite + 3% Salt+ 3#/Sx. LCM + 0.125#/Sx. of Cello Flakes Mix @ 13.5 PPG. Yield 1.77, circulate cement to surface. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Joe T. Janjes Title Permit Eng. Signature Date 09/17/08 USF SPACE FOR FEDERAL OR STATE OFFICE BUREAU OF LAND MANAGEMENT Title CARLSBAD FIELD OFFICE Conditions of approval, if any, are attached. Approval of this notice does not warrant or cerufy that the applicant holds legal or equitable title to those rights in the subject lease Office which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United

States any false, fictuous or fraudulent statements or representations as to arry matter within its jurisdiction.



Form 3160-5 (April 2004) UNITED STATES SEP 2 6 2008

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 200

April 2004) D	EPARTMENT OF THE INTERIOR	Expires: March 31, 2007
В	UREAU OF LAND MANAGEMENT	5. Lease Serial No.
SUNDRY	NOTICES AND REPORTS ON WELLS	LC-032096-B
Do not use this form for proposals to drill or to re-enter an		6. If Indian, Allottee or Tribe Name
abandoned we	II. Use Form 3160 - 3 (APD) for such proposals.	
SUBMIT IN TRIPLICATE- Other Instructions on reverse side.		7. If Unit or CA/Agreement, Name and/or No
1. Type of Well Gas Well Other		8. Well Name and No.
2. Name of Operator APACHE CORPORATION		LOCKHART "B-35" # 9
		9. API Well No.
3a. Address 6120 SOUTH YALE SUITE 1500 3b. Phone No. (include area code)		10. Field and Pool, or Exploratory Area
TULSA, OKLAHOMA 74136-4224 918-491-4954		EUNICE BLINEBRY TUBB DRINK NORTH
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		11. County or Parish, State
330' FNL & 330' FEL SECTION:35 T21S-R37E		
		LEA CO. NEW MEXICO
12. CHECK A	PROPRIATE DOX(ES) TO INDICATE NATURE OF NOTKE,	REPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION		
	Acidize Deepen Production (S	start/Resume) Water Shut-Off
XX Notice of Intent	Alter Casing Fracture Treat Reclamation	Well Integrity
Subsequent Report	Casing Repair New Construction Recomplete	Other
<u> </u>	Change Plans Plug and Abandon Temporarity	Abandon
Final Abandonment Notice	Convert to Injection Plug Back Water Dispose	al .
If the proposal is to deepen dire Attach the Bond under which to following completion of the im	ed Operation (clearly state all pertinent details, including estimated starting date of ectionally or recomplete horizontally, give subsurface locations and measured and the work will be performed or provide the Bond No. on file with DLM/BIA. Requivolved operations. If the operation results in a multiple completion or recompletion at Abandonment Notices shall be filed only after all requirements, including reclay for final inspection.)	true vertical depths of all pertinent markers and zones. ired subsequent reports shall be filed within 30 days n in a new interval, a Form 3160-4 shall be filed once
# 9 to 2000.	RATION requests the approval to test the PSI. Testing to be done by a third party	•
are estimated by a 24 hour	enticipated bottom hole pressures in the it to be 1600PSI, 1700 PSI, and 1800 PSI is shutin test performed on 09/05/08 indicate after a 24 hour shutin pressure on the	respectively. This is supported ating less than 1000 PSI bottom

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Title Permit Eng. Joe T. Janies Signature Date 09/17/08 Space for federal or state office use 19 zooo Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or JAMES A. AMOS certify that the applicant holds legal or equitable title to those rights in the subject lease Office SUPERVISOR-EPS which would entitle the applicant to conduct operations thereon

2. APACHE CORPORATION also requests the approval to change the cementing on the surface casing as follows: Cament with 450 Sx. of Class "C" cement +4% Bentonite + 3% Salt+ 3#/Sx. LCM + 0.125#/Sx. of Cello Flakes Mix @ 13.5 PPG. Yield 1.77, circulate cement

Title IS U.S.C. Section 1001 and Title 43 U.S.C. Section 1712, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictioious or fraudulent statements or representations as to any matter within its jurisdiction.

to surface.