

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		RECEIVED JUN 08 2003 HOBBS OGD		State of New Mexico Oil and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG						[REDACTED]	
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐					7 Lease Name or Unit Agreement Name VACUUM GRAYBURG SAN ANDRES UNIT		
b. Type of Completion NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF ☐ WELL OVER BACK RESVR. ☐ OTHER ☐							
2 Name of Operator CHEVRON U S A INC					8. Well No 228		
3 Address of Operator 15 SMITH ROAD, MIDLAND, TEXAS 79705					9 Pool name or Wildcat VACUUM GRAYBURG SAN ANDRES		
4 Well Location Unit Letter I 2180 Feet From The SOUTH Line and 690 Feet From The EAST line Section 21 Township 18-S Range 34-E NMPM County LEA							
10. Date Spudded 03-12-08	11 Date T.D. Reached 3-30-08	12 Date Compl (Ready to Prod.) 04-29-08	13 Elevations (DF& RKB, RT, GR, etc.) 3984'	14. Elev Casinghead			
15 Total Depth 5010'	16 Plug Back T.D. 4916'	17 If Multiple Compl. How Many Zones?	18 Intervals Drilled By	Rotary Tools	Cable Tools		
19 Producing Interval(s), of this completion - Top, Bottom, Name 4222-4727' GRAYBURG SAN ANDRES					20. Was Directional Survey Made YES		
21 Type Electric and Other Logs Run CBL, PLATFORM EXPRESS, SPECTRAL GR					22 Was Well Cored NO		
23. CASING RECORD (Report all strings set in well)							
CASING SIZE	WEIGHT LB /FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED		
11.75	42	453	14.75	830 SX	245 SX CIRC		
8.625	24	3189	11	1400 SX	375 SX CIRC		
5.5	15.5	5000	7.875	700 SX			
24. LINER RECORD							
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	25. TUBING RECORD		
					SIZE	DEPTH SET	PACKER SET
					2 7/8"	5000'	
26. Perforation record (interval, size, and number) 4740-55, 4758-78, 4796-4822, 4826-38, 4842-62, 4600-08, 4616-20, 4622-25, 4632-36, 4640-44, 4648-54, 4668-75, 4678-83, 4691-94, 4700-07, 4718-274469- 4586, 4222-34, 4238-46, 4274-86, 4298-4320, 4326-32, 4344-60, 4364-70, 4375-79, 4395-4404				27 ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 4600-4727' ACIDIZE W/3100 GALS 15% HCL 4222-4404' ACIDIZE W/5000 GALS ACID			
28. PRODUCTION							
Date First Production 05-13-08		Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING - SUB PUMP			Well Status (Prod or Shut-in) PROD		
Date of Test 05-21-08	Hours Tested 24 HRS	Choke Size	Prod'n For Test Period	Oil - Bbl 60	Gas - MCF 28	Water - Bbl 190	Gas - Oil Ratio 469
Flow Tubing Press.	Casing Pressure	Calculated 24- Hour Rate	Oil - Bbl	Gas - MCF	Water - Bbl	Oil Gravity - API - (Corr.)	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD						Test Witnessed By	
30. List Attachments							
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief							

Signature *Denise Pinkerton*

Printed
Name

Denise Pinkerton Title Regulatory Specialist

Date 06-05-2008

E-mail Address leakejd@chevron.com

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 1463	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 1524	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt 2634	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2776	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 3140	T. Devonian	T. Menefee	T. Madison
T. Queen 3679	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3963	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4257	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
------	----	----------------------	-----------	------	----	----------------------	-----------

