

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Albuquerque, NM 87106
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.30-025-38510
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. OG-379-9
7. Lease Name or Unit Agreement Name ENCORE "28" STATE COM
8. Well Number 001
9. OGRID Number 189951
10. Pool name or Wildcat KEMNITZ;ATOKA-MORROW,

11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4092
--

Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/>
Pit type 115 Depth to Groundwater N/A Distance from nearest fresh water well N/A Distance from nearest surface water N/A
Pit Liner Thickness: 12 mil Below-Grade Tank: Volume 14000 bbls; Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

DRILL 8 3/4" TO 13,400' TD. RUN 256 JOINTS OF 306 JOINTS OF 5-1/2 23# P-110 LTS CASING SET AT 13,390' BJ CEMENT 1ST STAGE. 750 GAL MUD CLEAN, 515 SX 50:50:10 H" BY 775 SX 61:15:11 "C". PLUG DOWN AT 13:15 10-9-2008 FLOAT HELD." DROP BOMB, OPEN DV TOOL. CIRCULATE 196 SX CEMENT OFF DV TOOL TO ROLL OFF CAR. CIRCULATE FOR WOC. BJ CEMENT 2ND STAGE. 790 SX 50:40:10 H" BY 100 SX "H". CLOSE DV TOOL AT 2100 10-9-2008. DID NOT CIRCULATE CEMENT RIG UP GRAY WIRE LINE RUN TEMPERATURE SURVEY. TOC @ 2658'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ann Burdette Wiley TITLE REGULATORY MANAGER DATE 10/13/2008

Type or print name ANN BURDETTE WILEY E-mail address: awiley@encoreacq.com Telephone No. 817-877-9955

For State Use Only

APPROVED BY: Petroleum Engineer TITLE PETROLEUM ENGINEER DATE OCT 17 2008

Conditions of Approval (if any):