

OCD-HOBBS

FORM 3163 UNITED STATES SEPTEMBER 101 DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS		ŧ	FORM APPROVED OM B No. 1004-0135 Expires: January 31, 2004 5. Lease Serial No.
		5. Lease Serial No. NM 12412	
Do not use this form for proposals to drill or to re-enter an			6. If Indian, Allottee or Tribe Name
abandoned well. Use Form 3160 - 3 (APD) for such proposals.		N/A	
SUBMIT IN TRIPLICATE- Other instructions on reverse side. 1 Type of Well Gas Well Gas Well Gother 2. Name of Operator Edge Petroleum Operating Company, Inc.,			7. If Unit or CA/Agreement, Name and/or No. N/A
			8. Well Name and No.
			Southeast Lusk 27 #1 9. API Well No.
3a Address 1301 Travis, Suite 2000 Houston, TX 44002 3b. Phone No. (include a 713-335-9808 4. Location of Well (Footage, Sec., T., R, M, or Survey Description)			30-025-38678 10. Field and Pool, or Exploratory Area
			Lusk, Bone Springs, South
487' FSL & 1980' FWL Sec/ 27, T- 19S, R- 32E	\checkmark		11. County or Parish, State Lea Co. NM
	PPROPRIATE BOX(ES) TO INDICATE	NATURE OF NOTICE	
TYPE OF SUBMISSION	TROUMIE DON(LD) TO HIDIOLITE	TYPE OF ACTION	
Notice of Intent	Acidize Deepen Alter Casing Fracture	Production	(Start/Resume) Water Shut-Off m Well Integrity
✓ Subsequent Report		nstruction Recomplete	
Final Abandonment Notice	Change Plans Plug and Convert to Injection Plug Back	Abandon Temporarily Abandon casing & cmt. Water Disposal	
	for final inspection.)	i an requirement, menses, p	clamation, have been completed, and the operator has
PRODUCTION CASING 10-2-08 Ran 5 1/2" 20# P- Float shoe, 1 jt. 5 set depth of 7,795' Cement tail w/ 450	& CEMENT -110 flush jt. casing as follows: -1/2" 20# P-110 flush jt. csg., float collar, 2 Cement lead w/ 185 sx 50:50 Poz "H" ci 0 sx 50:50 Poz "H" cmt. + 2% D20 + 5% D	mt. + 10% D20 + 5% D44 D44 + 1 pps D42 + 0.25 pps	, 38 jts 5 1/2" csg., 1 marker & 108 jts. 5 1/2" csg., + 1 pps D42 + 0.2% D46, Wt 11.8, Yield- 2.48. 1 D29, Wt 14.2, Yield- 1.36. 1 sx cmt. ND, install tbg. head, release rig @ 22:00
PRODUCTION CASING 10-2-08 Ran 5 1/2" 20# P- Float shoe, 1 jt. 5 set depth of 7,795' Cement tail w/ 450 Displace w/ 172 bl	& CEMENT -110 flush jt. casing as follows: -1/2" 20# P-110 flush jt. csg., float collar, 2 Cement lead w/ 185 sx 50:50 Poz "H" ci 0 sx 50:50 Poz "H" cmt. + 2% D20 + 5% D	mt. + 10% D20 + 5% D44 D44 + 1 pps D42 + 0.25 pps	+ 1 pps D42 + 0.2% D46, Wt 11.8, Yield- 2.48. D29, Wt 14.2, Yield- 1.36.
PRODUCTION CASING 10-2-08 Ran 5 1/2" 20# P- Float shoe, 1 jt. 5 set depth of 7,795' Cement tail w/ 450 Displace w/ 172 bi hrs. 14. I hereby certify that the foreg Namey Printed/Typed)	& CEMENT -110 flush jt. casing as follows: 1/2" 20# P-110 flush jt. csg., float collar, 2 '. Cement lead w/ 185 sx 50:50 Poz "H" ci 0 sx 50:50 Poz "H" cmt. + 2% D20 + 5% E bls fresh wtr., bump plug w/ 3000 psi, float	emt. + 10% D20 + 5% D44 D44 + 1 pps D42 + 0.25 pps at held OK. Circulated 60 s	+ 1 pps D42 + 0.2% D46, Wt 11.8, Yield- 2.48. is D29, Wt 14.2, Yield- 1.36. sx cmt. ND, install tbg. head, release rig @ 22:00
PRODUCTION CASING 10-2-08 Ran 5 1/2" 20# P- Float shoe, 1 jt. 5 set depth of 7,795' Cement tail w/ 450 Displace w/ 172 bi hrs. 14. I hereby certify that the foreg Name (Printed/Typed)	& CEMENT -110 flush jt. casing as follows: 1/2" 20# P-110 flush jt. csg., float collar, 2 ''. Cement lead w/ 185 sx 50:50 Poz "H" ci 0 sx 50:50 Poz "H" cmt. + 2% D20 + 5% E bls fresh wtr., bump plug w/ 3000 psi, floa	mt. + 10% D20 + 5% D44 D44 + 1 pps D42 + 0.25 pps	+ 1 pps D42 + 0.2% D46, Wt 11.8, Yield- 2.48. is D29, Wt 14.2, Yield- 1.36. sx cmt. ND, install tbg. head, release rig @ 22:00
PRODUCTION CASING 10-2-08 Ran 5 1/2" 20# P- Float shoe, 1 jt. 5 set depth of 7,795' Cement tail w/ 450 Displace w/ 172 bi hrs. 14. I hereby certify that the foreg Namey Printed/Typed)	de CEMENT -110 flush jt. casing as follows: 1/2" 20# P-110 flush jt. csg., float collar, 2 '. Cement lead w/ 185 sx 50:50 Poz "H" ci 0 sx 50:50 Poz "H" cmt. + 2% D20 + 5% E bls fresh wtr., bump plug w/ 3000 psi, float going is true and correct angela@rkford.com	Title Consultant 432-	+ 1 pps D42 + 0.2% D46, Wt 11.8, Yield- 2.48. s D29, Wt 14.2, Yield- 1.36. sx cmt. ND, install tbg. head, release rig @ 22:00
PRODUCTION CASING 10-2-08 Ran 5 1/2" 20# P- Float shoe, 1 jt. 5 set depth of 7,795' Cement tail w/ 450 Displace w/ 172 bl hrs. 14. Thereby certify that the foreg Name (Printed/Typed) Angela Lightner	& CEMENT -110 flush jt. casing as follows: 1/2" 20# P-110 flush jt. csg., float collar, 2 '. Cement lead w/ 185 sx 50:50 Poz "H" ci 0 sx 50:50 Poz "H" cmt. + 2% D20 + 5% E bls fresh wtr., bump plug w/ 3000 psi, float	Title Consultant 432-	+ 1 pps D42 + 0.2% D46, Wt 11.8, Yield- 2.48. s D29, Wt 14.2, Yield- 1.36. sx cmt. ND, install tbg. head, release rig @ 22:00
PRODUCTION CASING 10-2-08 Ran 5 1/2" 20# P- Float shoe, 1 jt. 5 set depth of 7,795' Cement tail w/ 450 Displace w/ 172 bl hrs. 14. I hereby certify that the foreg Name (Printed/Typed) Angela Lightner Signature Signature	& CEMENT 110 flush jt. casing as follows: 1/2" 20# P-110 flush jt. csg., float collar, 2 ". Cement lead w/ 185 sx 50:50 Poz "H" ci 0 sx 50:50 Poz "H" cmt. + 2% D20 + 5% D bls fresh wtr., bump plug w/ 3000 psi, float going is true and correct angela@rkford.com THIS SPACE FOR FEDERA	Title Consultant 432-d Date L OR STATE OFFICE Title	+ 1 pps D42 + 0.2% D46, Wt 11.8, Yield- 2.48. s D29, Wt 14.2, Yield- 1.36. sx cmt. ND, install tbg. head, release rig @ 22:00
PRODUCTION CASING 10-2-08 Ran 5 1/2" 20# P- Float shoe, 1 jt. 5 set depth of 7,795' Cement tail w/ 450 Displace w/ 172 bl hrs. 14. I hereby certify that the foreg Name (Printed/Typed) Angela Lightner Signature Signature Approved by Conditions of approval, if any, are a	de CEMENT 110 flush jt. casing as follows: 1/2" 20# P-110 flush jt. csg., float collar, 2 ". Cement lead w/ 185 sx 50:50 Poz "H" cit of sx 50:50 Poz "H" cit of sx 50:50 Poz "H" cit	Title Consultant 432- Date L OR STATE OFFICE Title ant or	+ 1 pps D42 + 0.2% D46, Wt 11.8, Yield- 2.48. s D29, Wt 14.2, Yield- 1.36. sx cmt. ND, install tbg. head, release rig @ 22:00 682-0440 office 10/05/2008 CEPTED FOR RECORI