

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-025-36299
5. Indicate Type of Lease	STATE ☐ FEE ☒
State Oil & Gas Lease No.	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐	7. Lease Name or Unit Agreement Name Fred Turner Jr. B
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER ☐	8. Well No. 4
2. Name of Operator Amerada Hess Corporation	9. Pool name or Wildcat West Nadine Tubb, Skaggs Drinkard, West Nadine Paddock-Blinebry
3. Address of Operator P.O. Box 840 Seminole, Texas 79360	

4. Well Location Unit Letter J : 1400 Feet From The South Line and 1900 Feet From The East Line				
Section 17	Township 20S	Range 38E	NMPM	Lea County
10. Date Spudded 7/2/2003	11. Date T.D. Reached 7/20/2003	12. Date Compl. (Ready to Prod.) 10/6/2003	13. Elevations (DF& RKB, RT, GR, etc.) 3558'	14. Elev. Casinghead
15. Total Depth 7150'	16. Plug Back T.D. 7132'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name (47400), 6450'-6768' West Nadine Tubb (47530), 6936'-7049' Skaggs Drinkard (57000)				20. Was Directional Survey Made Yes
21. Type Electric and Other Logs Run Platform Express Three Detector Litho-Density Compensated Neutron Platform Express High Resolution Laterolog Array				22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	1547'	11"	650 sx Class C	
5 1/2"	17#	7150'	7 7/8"	970 sx Class C/450 sx Class H	

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	7155'	
26. Perforation record (interval, size, and number) Perf w/4" csg guns @ 3 SPF 6936'-6944', 6951'-6956', 6978'-6982', 6998'-7006', 7008'-7022' and 7044'-7049'				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 6946'-6992' Acidized w/1500 gal. 15% HCL Acid 6936'-7049' Acidized w/6000 gal. 15% HCL Acid 5930'-6768' Acidized w/4000 gal. 15% HCL Acid & treated			

28. PRODUCTIONw/111,300 gal spectrafac 35# xl borate & 252,000# 16/30 snc.							
Date First Production 10/6/2003		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping: 25-200 RHBC 20-4-S-0 Pump			Well Status (Prod. or Shut-in) Producing		
Date of Test 10/25/2003	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 175	Gas - MCF 245	Water - Bbl. 67	Gas - Oil Ratio 1400
Flow Tubing Press. 165	Casing Pressure 240	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold						Test Witnessed By	

30. List Attachments C-102, C-103, C-104, Deviation Survey, Logs Note: Refer to Administrative Order DHC No. HOB-0059			
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief			
Signature Carol J. Moore	Printed Name Carol J. Moore	Title Senior Advisor	Date 10/25/2003

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	1492'
T. Salt	1596'
B. Salt	2600'
T. Yates	2746'
T. 7 Rivers	
T. Queen	
T. Grayburg	3732'
T. San Andres	4060'
T. Glorieta	5420'
T. Paddock	5569'
T. Blinebry	5915'
T. Tubb	6434'
T. Drinkard	6760'
T. Abo	7071'
T. Wolfcamp	
T. Penn	
T. Cisco (Bough C)	

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____
T. _____
T. _____

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS
OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
0	1492	1492	Red Beds
1492	1596	104	Anhydrite
1596	2600	1004	Salt
2600	4060	1460	Dolomite, Sand, Anhydrite
4060	7071	3011	Dolomite
7071	7096	25	Limestone
7096	7150	54	Dolomite

From	To	Thickness In Feet	Lithology

Clear