Form 3160 (August 2007)	UNITED STATES	•			1	FORM	APPROVED	,	
DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT					OMB NO. 1004-0135 Expires. July 31, 2010				
OCT 2 9 2006 RY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					5. Lease Serial No. NMLC029405B				
					6. If Indian, Allottee or Tribe Name				
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7	7 If Unit or CA/Agreement, Name and/or No			
1 Type of Well					8.	8. Well Name and No. GC FEDERAL 4			
Oil Well Gas Well Other 2. Name of Operator Contact KANICIA R CARRILLO					9	9 API Well No			
COG OPERATING LLC E-Mail kcarrillo@conchoresources com					30-025-35935				
3a Address 550 WEST TEXAS AVENUE MIDLAND, TX 79701	Ph: 432-685-4	MALJAM/				R;YESO, WEST			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State					
Sec 19 T17S R32E 1775FSL 2310FWL					EDDY COUNTY COUNTY, NM				
12. CHECK APP	ROPRIATE BOX(ES) TO	INDICATE N	ATURE OF	NOTICE	E, REPO	ORT, OR OTHE	R DATA		
TYPE OF SUBMISSION	TYPE OF ACTION				N				
□ Notice of Intent	□ ^{Acidize}	⊠ Deeper		_		(Start/Resume)		Shut-Off	
Subsequent Report	Alter Casing Casing Repair	□ Fractur	e Treat onstruction	_	lamatio complete		□ Well I □ Other		
Final Abandonment Notice	,		_			orarily Abandon			
	Convert to Injection			Back					
13 Describe Proposed or Completed Op If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final Adetermined that the site is ready for the determined that the site is ready for the complete of the com	ally or recomplete horizontally, gork will be performed or provide to operations. If the operation resubandonment Notices shall be filedinal inspection.) & set @ 5908?.PBTD @ 6 to 6209?.TIH to 6213?. Te & shoe. New formation 62 TD 7028?. 3#, L-80 ULTFJ csg. Set @ tool. Drop plug and close Idea. Etr. Drilled out DV Tool. Tag.	ive subsurface loc- he Bond No. on fil ilts in a multiple of d only after all request 6211'. Pump 10 est csg & squee 80 - 6292. Drill 7024?. Cmt v DV tool. gged PBTD @	ations and meas e with BLM/BL completion or rec presents, inclu- or sxs Class (exze to 300psi new formation v/75 sxs Class	completion ding reclan C w/2% (for 30 m on to 640 ass C. PD	ue verticed subset in a new nation, h CaCl. S in. 33'.	al depths of all pertiquent reports shall be interval, a Form 316 ave been completed, queeze	nent markers filed within 50-4 shall be	and zones 30 days filed once	
	Electronic Submission #6 For COG O	3686 verified by PERATING LLC	, sent to the I	Hobbs					
Name (Printed/Typed) KANICIA R CARRILLO		Ti	Title REGULATO		ACCEPTED FOR RECORD				
Signature (Electronic S	Submission)	D	ate 10/08/2	2008	AUU.	EPIED FUI	K KEU	ואט	
	THIS SPACE FO	R FEDERAL	OR STATE	OFFICE	USE				
Approved By		T	itle			001 17 57%a	2008 Date		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office		BUREAU OF LAND MANAGEMENT				
Title 18 U.S C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U S.C. Section 1212, make it a c statements or representations as t	crime for any perso o any matter withi	n knowingly and its jurisdiction	ıd willfu <u>lly.</u> 1.	to make	to any department of	agency of th	e United.	

Additional data for EC transaction #63686 that would not fit on the form

32. Additional remarks, continued

08/04/08 Acidize w/2500 gals 15% HCL. Frac w/61,524 gal 20# lightning; 63,847# 16/30 Ottawa sand, 27,635# 16/30 Siberprop sand.
08/06/08 RIH w/BP & set @ 6160?. Perf @ 6330' - 6530', 2 SPF, 32 holes. 08/12/08 Acidize w/2500 gals 15% HCL. Frac w/44,855 gal 20# lightning; 41,517# 16/30 sand, 9,205# Siberprop.
08/15/08 RIH w/BP @ set @ 6280?. Perf @ 6210' - 5980, 2 SPF, 32 holes. 08/16/08 Acidize w/2500 gals 15% HCL. Frac w/54,810 gal 20# lightning; 57,042# 16/30 sand, 6,135# Siberprop.
08/19/08 TIH & drill out plugs. PBTD 6965'.
08/21/08 RIH w/173 jts 2 7/8? tbg, SN @ 5534?. RIH w/2-3/8?x20?x2" RHTC pump. Hang well on.