Submit 3 Copies To Appropriate District Office State of New Mex	
District I Energy, Minerals and Natur 1625 N. French Dr., Hobbs, NM 88240	ral Resources Revised March 25, 1999 WELL API NO.
District II 1301 W. Grand Avenue, Artesia, NM 88210 OIL CONSERVATION	DIVISION 30-25-36141
District III 1220 South St. Fram 1000 Rio Brazos Rd., Aztec, NM 87410	5 Indicate Type of Lease
District IV Santa Fe, NM 87	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLU DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOI PROPOSALS.)	7. Lease Name or Unit Agreement Name: SOUTHLAND ROYALTY "A"
1. Type of Well: Oil Well ☑ Gas Well ☐ Other	
2. Name of Operator APACHE CORPORATION	8. Well No. 15
3. Address of Operator 6120 S. YALE, SUITE 1500 TULS	SA,OK 74136 9. Pool name or Wildcat PENROSE SKELLY;GRAYBURG
4. Well Location	
Unit Letter Q : 2460 feet from the SOUTH line and 990 feet from the EAST line	
Section 4 Township 21S Range 37E NMPM County LEA 10. Elevation (Show whether DR, RKB, RT, GR, etc.)	
3469 GR 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON	SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS. PLUG AND
PULL OR ALTER CASING MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB
OTHER:	OTHER: RUN SURF. & PROD. CSG; REL. RIG
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.	
2/9/2003 MIRU CAPSTAR RIG #8. SPUD 12-1/4" HOLE AT 3:00 PM 2/9/03. DRILL & SURVEY 170 412'. RIH W/8-5/8" 24# J55 CASING. CEMENT SHOE @ 412' W/ 325 SX CLASS C + 2% CACL + 0.125 #/SX CELLO FLAKE=78 BBLS 14.8 PPG SLURRY, YIELD=1.35 CF/SX. CIRC 93 SX CMT TO PIT. WOC.	
2/10/03 - 2/14/03 DRILL & SURVEY F/ 412' - 4067'.	
2/15/2003 DRILL F/ 4067' - 4150'. CIRC, RAN LOGS. RIH W/ 5-1/2" 17# J55 CASING W/ 17 CENTRALIZERS. CEMENT SHOE @ 4150' W/ 500 SX 50:50 POZ:CLASS C W/10% GEL + 5% SALT + 0.125 #/SX CELLO FLAKE + 0.003 GPS FP-6L=217 BBLS 11.8 PPG SLURRY, YIELD=2.44 CF SX. TAIL W/ 250 SX 50:50 POZ:CLASS C + 5% SALT + 2% GEL + 0.003 GPS FP-6L= 57 BBLS 14.2 PPG SLURRY, YIELD+1.29 CF/SX. CIRC 126 SX CMT TO PIT. WOC. RELEASED RIG @ 1:00 AM 2/16/03.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE	
Type or print name LARRY E. RADER	Telephone No. (918) 491-4900
(This space for State ORIGINAL SIGNED BY GARY W. WINK	
APPPROVED BY OC FIELD REPRESENTATIVE II/STAFFIMENA Conditions of approval, if any:	GER DATE FEB 2 7 200