

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

RECEIVED SEP 29 2008 HOBBS (II)		OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-29207 ✓	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☒		5. Indicate Type of Lease STATE ☐ FEE ☒	
2. Name of Operator Chevron U.S.A. Inc. ✓		6. State Oil & Gas Lease No.	
3. Address of Operator 15 Smith Road, Midland, TX 79705		7. Lease Name or Unit Agreement Name Weir, C. H. -A- ✓	
4. Well Location Unit Letter <u>J</u> : <u>2310</u> feet from the <u>South</u> line and <u>1650</u> feet from the <u>East</u> line Section <u>12</u> Township <u>20S</u> Range <u>37E</u> NMPM Lea County ✓		8. Well Number 16 ✓	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3557'		9. OGRID Number 4323 ✓	
		10. Pool name or Wildcat Weir Blinebry East	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/5/1999 - MIRU, Pooh w/pump & rods
5/6/1999 - Pooh w/tbg, set CIBP @5637'
5/10/1999 - MIRU Key 119, set Whipstock, mill window from 5624'-5630'
5/11/1999 through 5/18/1999 - Drill lateral from 5630'-7493'
5/19/1999 - Release Key 119
5/29/1999 - Acdz Blinebry at 5947'-5949', 6134'-6136', 6875'-6877', 7032'-7034', only got 4200 gals 20% HCL
6/4/1999 - Put on pump, whipstock left in hole
1/25/2000 through 2/13/2000 - Pulled whipstock, attempted to clean out vertical wellbore. Unable to get down csg, peeled at whipstock

2/28/2000 - 8 bo, 24 mcfpg, 1 bw

BHL - 2529' FSL & 1859' FWL

Spud Date: 5/5/1999 Rig Release Date: 2/13/2000

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Wendi Kingston TITLE Regulatory Team Lead DATE 9/26/2008

Type or print name Wendi Kingston E-mail address: wendikingston@chevron.com PHONE: 432-687-7826

For State Use Only

APPROVED BY: ZA Skaggs TITLE PETROLEUM ENGINEER DATE NOV 19 2008

Conditions of Approval (if any): Drinkard

Results of Directional Survey

API number:	30-025-29207		
OGRID:		Operator:	CHEVRON U S A INC
		Property:	C H WEIR A # 16

surface	ULSTR:	J	12	T	20S	R	37E
			2290	FSL	1410	FEL	

BH Loc	ULSTR:	K	12	T	20S	R	37E
			2509	FSL	3181	FEL	

	MD	N/S	E/W	VD
	5624	-4.10	-26.30	5623.4
TOP PERFS/OH	5624	-4.10	-26.30	5623.40
	5633	-4.00	-26.50	5632.40
	7455	215.30	-1733.60	5746.00
BOT PERFS/OH	7493	219.10	-1771.00	5740.70
	7493	219.10	-1771.00	5740.70

NEXT TO LAST	7455	215.30	-1733.60	5746.00
LAST READING	7493	219.10	-1771.00	5740.70
TD	7493	219.10	-1771.00	5740.70

Surface Location	2290	FS	1410	FE
Projected BHL	2509	FS	3181	FE
Location of				
Top Perfs/OH	2286	FS	1436	FE
Bottom Perfs/OH	2509	FS	3181	FE

SUMMARY of Subsurface Locations

Surface Location	J-12-20S-37E	2290	FS	1410	FE	Vert. Depth
Top Perfs/OH	J-12-20S-37E	2286	FS	1436	FE	5623.40
Bottom Perfs/OH	K-12-20S-37E	2509	FS	3181	FE	5740.70
Projected TD	K-12-20S-37E	2509	FS	3181	FE	5740.70

Scientific Drilling

SDI Survey Report

Company: Texaco E & P, Inc.
 Field: Weir (Blinberry East)
 Site: Lea County, New Mexico
 Well: C H. Weir "A" #16H
 Wellpath: Lateral #1

Date: 7/1/1999 Time: 12.13:44 Page: 1
 Co-ordinate(NE) Reference: Site: Lea County, New Mexico, Grid North
 Vertical (TVD) Reference: SITE 0.0 above Mean Sea Level
 Section (VS) Reference: Site (0.0E,0.0N,277.3Az)
 Survey Calculation Method: Minimum Curvature

Survey: Survey #1

Start Date: 5/11/1999

Company:
 Tool: Gyro

Engineer:

Survey

MD ft	Incl deg	Azim deg	TVD ft	N/S ft	E/W ft	DLS d/100ft	VS ft	CLsA deg	CLsD ft
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.0	0.00	0.0
100.0	0.06	21.10	100.0	0.0	0.0	0.06	0.0	21.10	0.1
200.0	0.09	61.45	200.0	0.1	0.1	0.06	-0.1	38.27	0.2
300.8	0.12	39.56	300.8	0.3	0.2	0.05	-0.2	43.74	0.4
400.4	0.08	19.92	400.4	0.4	0.3	0.05	-0.3	39.81	0.5
501.0	0.14	310.74	501.0	0.5	0.3	0.13	-0.2	25.82	0.6
600.7	0.25	276.56	600.7	0.7	0.0	0.16	0.1	356.13	0.7
700.3	0.72	244.85	700.3	0.4	-0.8	0.53	0.9	296.37	0.9
801.0	0.92	237.06	801.0	-0.3	-2.1	0.23	2.0	261.82	2.1
900.1	1.27	237.72	900.1	-1.3	-3.7	0.35	3.5	250.26	3.9
1000.9	1.44	236.20	1000.8	-2.6	-5.7	0.17	5.3	245.21	6.2
1100.8	1.92	232.70	1100.7	-4.3	-8.0	0.49	7.4	241.70	9.1
1200.4	2.12	232.63	1200.2	-6.5	-10.8	0.20	9.9	239.20	12.6
1300.9	2.05	230.30	1300.7	-8.7	-13.7	0.11	12.5	237.47	16.2
1400.0	2.28	234.38	1399.7	-11.0	-16.7	0.28	15.1	236.53	20.0
1501.0	1.85	229.39	1500.6	-13.2	-19.5	0.46	17.7	235.85	23.6
1600.4	1.45	225.06	1600.0	-15.2	-21.6	0.42	19.5	234.95	26.4
1700.5	1.19	231.85	1700.1	-16.7	-23.4	0.30	21.1	234.40	28.7
1800.9	0.93	243.41	1800.4	-17.7	-24.9	0.33	22.5	234.56	30.6
1900.8	0.61	258.86	1900.3	-18.2	-26.2	0.38	23.6	235.17	31.9
2000.1	0.57	267.20	1999.6	-18.3	-27.2	0.10	24.6	236.00	32.8
2101.3	0.35	284.39	2100.8	-18.3	-28.0	0.25	25.4	236.85	33.4
2200.5	0.29	281.35	2200.0	-18.1	-28.5	0.06	26.0	237.53	33.8
2300.4	0.29	293.10	2299.9	-18.0	-29.0	0.06	26.5	238.17	34.1
2401.0	0.28	74.50	2400.5	-17.8	-29.0	0.53	26.5	238.40	34.0
2500.7	0.23	56.45	2500.2	-17.7	-28.6	0.09	26.1	238.30	33.6
2601.0	0.30	65.87	2600.5	-17.4	-28.2	0.08	25.7	238.25	33.1
2700.8	0.23	48.16	2700.3	-17.2	-27.8	0.11	25.4	238.25	32.7
2800.6	0.30	68.41	2800.1	-17.0	-27.4	0.12	25.0	238.23	32.2
2900.5	0.09	19.26	2900.0	-16.8	-27.1	0.25	24.8	238.24	31.9
3000.4	0.08	352.64	2999.9	-16.6	-27.1	0.04	24.8	238.44	31.8
3100.4	0.14	3.53	3099.9	-16.5	-27.1	0.06	24.8	238.74	31.7
3200.3	0.21	349.04	3199.8	-16.2	-27.1	0.08	24.9	239.23	31.6
3300.9	0.24	354.10	3300.4	-15.8	-27.2	0.04	25.0	239.90	31.4
3400.5	0.41	337.72	3400.0	-15.2	-27.3	0.19	25.2	240.89	31.3
3500.1	0.50	320.31	3499.6	-14.6	-27.8	0.16	25.7	242.32	31.4
3600.3	0.67	319.28	3599.8	-13.8	-28.4	0.17	26.5	244.13	31.6
3700.5	0.71	309.93	3700.0	-12.9	-29.3	0.12	27.4	246.16	32.0
3800.3	0.67	313.28	3799.8	-12.1	-30.2	0.06	28.4	248.08	32.5
3900.7	0.54	315.82	3900.2	-11.4	-30.9	0.13	29.2	249.77	33.0
4001.5	0.52	324.43	4001.0	-10.7	-31.5	0.08	29.9	251.27	33.3
4100.6	0.55	322.22	4100.1	-9.9	-32.1	0.04	30.6	252.77	33.6
4200.7	0.48	320.47	4200.2	-9.2	-32.6	0.07	31.2	254.19	33.9
4300.4	0.20	345.27	4299.9	-8.8	-33.0	0.31	31.6	255.12	34.1
4400.4	0.18	344.45	4399.9	-8.4	-33.0	0.02	31.7	255.68	34.1
4501.0	0.25	336.47	4500.5	-8.1	-33.2	0.08	31.9	256.31	34.1
4600.2	0.10	0.26	4599.7	-7.8	-33.3	0.16	32.0	256.81	34.2
4700.9	0.12	5.38	4700.4	-7.6	-33.3	0.02	32.0	257.12	34.1

SUR: J-12-20s-37e, 2290/S & 1410/E
 BHL: K-12-20s-37e, 2509/S & 3181/E
 API #30-025-29207

Scientific Drilling

SDI Survey Report

Company: Texaco E & P, Inc.
 Field: Weir (Blinberry East)
 Site: Lea County, New Mexico
 Well: C H. Weir "A" #16H
 Wellpath: Lateral #1

Date: 7/1/1999
 Co-ordinate(NE) Reference: Site. Lea County, New Mexico, Grid North
 Vertical (TVD) Reference: SITE 0.0 above Mean Sea Level
 Section (VS) Reference: Site (0.0E,0.0N,277.3Az)
 Survey Calculation Method: Minimum Curvature

Page: 2

Survey

MD ft	Incl deg	Azim deg	TVD ft	N/S ft	E/W ft	DLS d/100ft	VS ft	Cl.sA deg	Cl.sD ft
4800.0	0 19	24.82	4799.5	-7.4	-33.2	0.09	32.0	257.51	34.0
4900.7	0 39	51.12	4900.2	-7.0	-32.8	0.23	31.7	257.99	33.6
5000.5	0 53	57.07	5000.0	-6.5	-32.2	0.15	31.1	258.55	32.8
5101.4	0 47	51.75	5100.9	-6.0	-31.5	0.08	30.5	259.19	32.0
5200.1	0 56	66.13	5199.6	-5.6	-30.7	0.16	29.8	259.73	31.2
5300.9	0.71	79.14	5300.4	-5.2	-29.6	0.21	28.7	259.96	30.1
5400.8	0.51	64.98	5400.2	-4.9	-28.6	0.25	27.8	260.21	29.1
5500.4	0 74	74.17	5499.8	-4.6	-27.6	0.25	26.8	260.58	28.0
5590.0	0.60	63.26	5589.4	-4.2	-26.6	0.21	25.9	261.02	27.0
5624.0	0.60	63.26	5623.4	-4.1	-26.3	0.00	25.6	261.25	26.6
5633.0	2.70	277.00	5632.4	-4.0	-26.5	35.74	25.8	261.40	26.8
5643.0	5.40	277.00	5642.4	-3.9	-27.2	27.00	26.5	261.80	27.5
5653.0	8.20	273.00	5652.3	-3.8	-28.4	28.38	27.7	262.32	28.6
5663.0	11.70	271.50	5662.2	-3.8	-30.1	35.09	29.4	262.88	30.3
5673.0	14.90	280.60	5671.9	-3.5	-32.4	38.15	31.7	263.84	32.6
5683.0	18.30	284.20	5681.5	-2.9	-35.2	35.51	34.5	265.33	35.3
5693.0	21.70	285.90	5690.9	-2.0	-38.5	34.49	37.9	267.05	38.5
5728.0	33.60	281.00	5721.8	1.7	-54.2	34.59	54.0	271.74	54.3
5760.0	44.80	279.60	5746.6	5.2	-74.1	35.11	74.2	274.04	74.3
5792.0	55.80	278.90	5767.0	9.2	-98.4	34.42	98.8	275.33	98.8
5820.0	65.60	274.70	5780.7	12.0	-122.6	37.35	123.1	275.60	123.2
5852.0	76.00	274.30	5791.2	14.4	-152.7	32.52	153.3	275.38	153.4
5884.0	86.30	272.90	5796.1	16.4	-184.2	32.48	184.8	275.07	184.9
5915.0	88.70	275.00	5797.5	18.5	-215.1	10.28	215.7	274.91	215.9
5947.0	90.40	276.40	5797.7	21.7	-246.9	6.88	247.7	275.02	247.9
5978.0	91.30	277.10	5797.3	25.3	-277.7	3.68	278.7	275.21	278.9
6010.0	90.10	276.80	5796.9	29.2	-309.5	3.87	310.7	275.39	310.8
6041.0	90.10	275.70	5796.8	32.6	-340.3	3.55	341.7	275.47	341.8
6073.0	91.30	275.00	5796.4	35.5	-372.1	4.34	373.7	275.46	373.8
6105.0	90.40	275.00	5796.0	38.3	-404.0	2.81	405.6	275.42	405.8
6136.0	89.30	274.70	5796.0	41.0	-434.9	3.68	436.6	275.38	436.8
6168.0	88.60	274.70	5796.6	43.6	-466.8	2.19	468.6	275.33	468.8
6199.0	88.20	277.10	5797.5	46.8	-497.6	7.85	499.5	275.37	499.8
6231.0	87.90	278.50	5798.6	51.1	-529.3	4.47	531.5	275.51	531.8
6263.0	85.40	280.30	5800.5	56.3	-560.8	9.62	563.4	275.73	563.6
6294.0	80.50	281.40	5804.3	62.1	-591.0	16.19	594.1	276.00	594.3
6326.0	80.00	281.00	5809.7	68.2	-622.0	1.99	625.6	276.26	625.7
6358.0	80.30	280.60	5815.1	74.1	-652.9	1.55	657.1	276.48	657.1
6390.0	80.30	280.60	5820.5	79.9	-683.9	0.00	688.5	276.67	688.6
6421.0	83.00	281.40	5825.0	85.8	-714.0	9.08	719.2	276.85	719.2
6452.0	86.70	282.40	5827.8	92.2	-744.2	12.36	749.9	277.06	749.9
6484.0	91.60	282.80	5828.3	99.1	-775.5	15.36	781.8	277.29	781.8
6515.0	96.30	282.80	5826.2	106.0	-805.6	15.16	812.5	277.49	812.5
6547.0	97.30	281.40	5822.4	112.6	-836.7	5.35	844.2	277.67	844.2
6579.0	97.70	281.40	5818.2	118.9	-867.8	1.25	875.8	277.80	875.9
6610.0	98.00	280.60	5814.0	124.8	-897.9	2.73	906.5	277.91	906.5
6642.0	98.80	280.30	5809.3	130.5	-929.1	2.67	938.1	278.00	938.2
6674.0	97.70	278.20	5804.7	135.6	-960.3	7.35	969.7	278.04	969.8
6705.0	96.80	277.50	5800.8	139.8	-990.8	3.67	1000.5	278.03	1000.6
6736.0	93.30	277.10	5798.1	143.7	-1021.4	11.36	1031.4	278.01	1031.5
6768.0	89.00	276.80	5797.4	147.6	-1053.1	13.47	1063.4	277.98	1063.4
6799.0	88.60	275.70	5798.1	151.0	-1084.0	3.77	1094.3	277.93	1094.4

Scientific Drilling

SDI Survey Report

Company: Texaco E & P, Inc.
Field: Weir (Blinbry East)
Site: Lea County, New Mexico
Well: C. H. Weir "A" #16H
Wellpath: Lateral #1

Date: 7/1/1999 **Time:** 12:13 44 **Page:** 3
Co-ordinate(NE) Reference: Site. Lea County, New Mexico, Grid North
Vertical (TVD) Reference: SITE 0.0 above Mean Sea Level
Section (VS) Reference: Site (0.0E,0.0N,277.3Azi)
Survey Calculation Method: Minimum Curvature

Survey

MD ft	Incl deg	Azim deg	TVD ft	N/S ft	E/W ft	DLS d/100ft	VS ft	CLsA deg	CLsD ft
6831.0	89.30	275.00	5798.6	154.0	-1115.8	3.09	1126.3	277.86	1126.4
6863.0	90.80	274.70	5798.6	156.7	-1147.7	4.78	1158.3	277.77	1158.3
6895.0	91.40	275.00	5798.0	159.4	-1179.6	2.10	1190.3	277.69	1190.3
6926.0	91.70	274.70	5797.2	162.0	-1210.5	1.37	1221.2	277.62	1221.2
6957.0	90.50	275.50	5796.6	164.7	-1241.3	4.65	1252.2	277.56	1252.2
6989.0	90.80	275.70	5796.2	167.9	-1273.2	1.13	1284.2	277.51	1284.2
7020.0	91.70	275.00	5795.5	170.8	-1304.0	3.68	1315.1	277.46	1315.2
7052.0	92.90	275.00	5794.2	173.5	-1335.9	3.75	1347.1	277.40	1347.1
7084.0	93.90	275.40	5792.4	176.4	-1367.7	3.36	1379.0	277.35	1379.0
7115.0	95.00	274.70	5789.9	179.2	-1398.5	4.20	1409.9	277.30	1409.9
7146.0	95.70	275.40	5787.1	181.9	-1429.2	3.19	1440.7	277.25	1440.7
7177.0	95.20	276.80	5784.1	185.2	-1459.9	4.78	1471.6	277.23	1471.6
7210.0	96.60	276.80	5780.7	189.0	-1492.5	4.24	1504.4	277.22	1504.4
7241.0	97.50	276.80	5776.9	192.7	-1523.0	2.90	1535.2	277.21	1535.2
7272.0	98.10	276.40	5772.7	196.2	-1553.6	2.32	1565.9	277.20	1565.9
7304.0	98.70	276.10	5768.0	199.7	-1585.0	2.09	1597.5	277.18	1597.5
7336.0	98.50	276.10	5763.2	203.0	-1616.5	0.62	1629.2	277.16	1629.2
7367.0	98.60	276.10	5758.6	206.3	-1647.0	0.32	1659.8	277.14	1659.8
7399.0	98.30	276.10	5753.9	209.6	-1678.4	0.94	1691.5	277.12	1691.5
7430.0	98.10	275.70	5749.5	212.8	-1709.0	1.43	1722.1	277.10	1722.2
7455.0	98.10	275.70	5746.0	215.3	-1733.6	0.00	1746.9	277.08	1746.9
7493.0	98.00	276.10	5740.7	219.1	-1771.0	1.07	1784.5	277.05	1784.5