Sew Mexico Off Censervation Division, District MAPPROVED 1625 N. French Drive DEPARTMENT OF THE INTERIOR NM 88246 5. Lease Serial No. DEC USUNDRY NOTICES AND REPORTS ON WELLS LC-068474 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to re-enter an POR SOM Dell. Use Form 3160-3 (APD) for such proposals. 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse side. 1. Type of Well Oil Well Gas Well X Other 8. Well Name and No. Drickey Queen Sand Unit #24 2. Name of Operator 9. API Well No. CELERO ENERGY II. LP 3b. Phone No. (include area code) 30-005-00968 3a. Address 400 W. Illinois, Ste. 1601 Midland TX 79701 (432)686-1883 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Caprock Queen 11. County or Parish, State 660 South 1980 West ·Chaves UL: N, Sec: 3, T: 14S, R: 31E MM 12. CHECK APPROPRIATE BOX(ES)TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION **TYPE OF ACTION** Acidize Deenen Production (Start/Resume) Water Shut-Off ☐ Notice of Intent AlterCasing X Well Integrity FractureTreat Reclamation Casing Repair X OtherReactivate New Construction Recomplete X Subsequent Report Change Plans Plug and Abandon J Temporarily Abandon injector Final Abandonment Notice ☐ Convert to Injection ☐ Plug Back → Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 9/29-11/13/08 Reactivate abandoned injection well. MIRU. Replaced WH. Fished 2 3/8" IPC inj tbg & pkr out of WB. CO well to 2705'. Repaired 8 5/8" casing at the surface. DO/milled out 5 1/2" csg from 2661' - 3045'. Ran csg inspection log, bad casing. Milled out 5 1/2" csg in preparation to run 4" liner. Poured a total of 39 sx of sand and 80 gal of sand down WB to PB Queen open hole. Tagged top of sand @ 3011'. Pumped six pills of LCM material to achieve circulation, unsuccessful. Isolated 5 1/2" csg leak from 2152' - 2310'. Washed top of sand down to 3033'. Ran 53 jts of 4" 9.5# ultra flush jt csg from 3,005' to surface. Cmtd 4" liner w/ 350 sx Class C cmt w/additives. DO cmt to 3005'. Ran CBL, TOC @ 2750'. Pumped 350 sx Class C neat cmt down 4"x5 1/2" csg annulus. Ran CBL, had little cmt. Pumped 350 sx Class C cmt w/ additives down 4" x 5 1/2" csg annulus. Ran CBL, TOC @ 2450'. DO 5 1/2" csg shoe & CO well to 3064'. DO well to new TD @ 3090'. Ran GR/CCL/CN log but could not get down below 2965'. Ran 2 3/8" workstring & AD-1 pkr. Set pkr @ 2929'. Acdzd Queen open hole (3044' - 3090') w/ 2,000 gal 7.5% NEFE acid, 500 gal toluene mix, and 500# rock salt @ 5.5 BPM & 320 psi avg STP. Swabbed load back. POOH w/ 2 3/8" workstring & pkr. Ran 2 3/8" 4.7# J-55 IPC inj tbg & Arrowset pkr. Set pkr @ 2976'. Pressured up 315 psi & ran good chart for 30 mins. SI while waiting on battery to be Original chart sent to OCD Hobbs. Order No. R-1128 (2/12/58 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Lisa Hunt Title Regulatory Analyst Signature 11/20/2008 Date ACCEPTED FOR INS GORGE FOR FEDERAL OR STATE OFFICE USE Approve Accepted For Record Only! Conditions of approval stary, are anadred Approval of this notice does not warrant or Subject To Returning Well To Continuous certify that the applicant holds legal or equitable title to those rights in the subject lease Injection And Keeping Well On Continuous which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1804 and Pitte 10 S.E. Section 12 I2, make it a crime for any persor States any false, hours or representations as to any matter v Injection Or Plugging Well With An Approved Plugging Program!

(Instructions on page 2)

## CELERO ENERGY

DATE: Mar. 18, 2008 FIELD: Caprock BY: **GSA** LEASE/UNIT: **Drickey Queen Sand Unit** WELL: 24 **COUNTY:** Chaves STATE: New Mexico Location: 660' FSL & 1980' FWL, Sec 3N, T14S, R31ECM KB = 4436'SPUD: 10/54 COMP: 10/54 GL = **CURRENT STATUS: Injector** API = 30-005-00968Original Well Name: Government B #14 PRE WÜRKOVER 8-5/8" 22.7#/ft @ 373" cmt'd. w/ 200 sx cmt. TOC @ surface (calc). 2-3/8" IPC tbg and packer @ 2500' TOC @ 990' +/- (calc) 5-1/2" 14# @ 3033' cmt'd. w/ 300 sx (DNC) Top of Queen @ 3044': Queen: 3044' - 3064' (10-54) PBTD - 3064' TD - 3064'

5/20/2008

DQSU #24.xls

## CELERO ENERGY

DATE: Nov. 19, 2008 FIELD: Caprock BY: **JEA** LEASE/UNIT: **Drickey Queen Sand Unit** WELL: 24 **COUNTY:** Chaves STATE: **New Mexico** Location: 660' FSL & 1980' FWL, Sec 3N, T14S, R31ECM KB = 4,436'SPUD: 10/54 COMP: 10/54 GL = CURRENT STATUS: Injector API = 30-005-00968Original Well Name: Government B #14 POST WORKOVER 8-5/8" 22.7#/ft @ 373' cmt'd. w/ 200 sx cmt. TOC @ surface (calc). Pumped 700 sx Class C cement down 4" x 5 1/2" casing annulus. TOC 5 1/2" casing @ 990' +/- (calc) 2-3/8"/4.7#/J-55 IPC injection tbg with Arrowset pkr set @ 2976'. TOC 4" liner @ 2450' +/- (CBL) 4" 9.5# ultra flush joint liner from 3005' to surface, cmt'd w/ 350 sx Class C cmt (DNC). 5 1/2" 14# @ 3033' emt'd. w/ 300 sx (DNC) Top of Queen @ 3044': Queen Open Hole: 3044' - 3064' (10-54) Queen Open Hole: 3044' - 3090' (10-08) PBTD - 3090' TD - 3090' 11/20/2008 DQSU #24R

