Submit 3 Copies To Appropriate District Office       State of New Mexico         District I       Energy, Minerals and Natural Resources         1625 N. French Dr., Hobbs, NM 88240       District II         District II       OIL CONSERVATION DIVISION         1301 W. Grand Avenue, Artesia, NM 88210       District III         1300 Rio Brazos Rd., Aztec, NM 87410       District IV         1220 S. st. Francis Dr., Santa Fe, NM 87505       Santa Fe, NM 87505	Form C-103 Revised March 25, 1999 WELL API NO. 30-025-36144 5. Indicate Type of Lease STATE FEE 5 6. State Oil & Gas Lease No. 7. Lease Name or Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)         1. Type of Well:         Oil Well       Gas Well    Other	Phillips
2. Name of Operator Petroleum Technical Services Company	8. Well No. 1
3. Address of Operator 3000 N. Garfield, Ste 290 Midland, TX 79705	9. Pool name or Wildcat
4. Well Location	
Unit Letter E : 1980 feet from the North line and 330 feet from the West line	
Section 19 Township 19-S Range 39-E	NMPM Lea County
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3577' GR	
11. Check Appropriate Box to Indicate Nature of Notice NOTICE OF INTENTION TO: SU PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	BSEQUENT REPORT OF:
PULL OR ALTER CASING MULTIPLE CASING TEST COMPLETION CASING TEST	ABANDONMENT
OTHER: OTHER: Con	tinue Drilling and Testing Operations
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.	
<ol> <li>Mudded up hole with 10.1 PPG salt gel mud.</li> <li>Drilled to 7058' and took DST#1, 6930'-7058'.</li> <li>Drilled to 7556' and took DST#2, 7432'-7556'.</li> </ol>	to Plugging of the Well Bore. er bond is retained until ration is completed.
<ul> <li>5. Drilled to 7708'. Ran open hole logs by Schlumberger.</li> <li>6. Ran 4-1/2" drill pipe to 7700' and spotted 40 sack cement plug to 7600'</li> <li>7. Spotted 40 sack cement plug from 5650' to 5550'. Spotted 50 sack cement plug from 3746' to 3634'. Spotted 75 sack cement plug from 1790' to 1558'. WOC for 4 hours and tagged plug at 1555'. Spotted 35 sack cement plug at 400' to 300'.</li> </ul>	by Halliburton.
Spotted 20 sack cement plug at 60' to surface.	
Well Plugged and Abandoned 3/03/03.	16 02 67 av 20
I hereby certify that the information above is true and complete to the best of my knowl SIGNATURE	edge and belief. DATE 3/7/03
Type or print name Don C. Bennett	Telephone No. (915) 684-6603
(This space for State use)       ORIGINAL SIGNED BY         APPPROVED BY       GARY W. WINKLE         Conditions of approval, if any:       OC FIELD REPRESENTATIVE II/STAFF MANAGER	

a v