Submit 3 Copies To Appropriate District Office District I 1625 N. French Dr., Hobbs NA 893 10 District II CONSERVATION DIVIS	WELL API NO.
1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 1220 South St. Francis D Santa Fe, NM 87505 87410 District IV	5 Indicate Type of Lease
1220 S St. Francis Dr., Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG E DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SI PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	SOUTH JUSTIS UNIT
Name of Operator LEGACY RESERVES OPERATING LP	8. Well Number B-19 / 9. OGRID Number 240974 /
3. Address of Operator P.O. BOX 10848 MIDLAND, TX 79702	10. Pool name or Wildcat JUSTIS-BLINEBRY-TUBB-DRINKARD
4. Well Location Unit LetterC _:660feet from theNORTH line and2310feet from theWestline. / Section 23	
water	
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
TEMPORARILY ABANDON CHANGE PLANS COMM	SUBSEQUENT REPORT OF: DIAL WORK
OTHER: 13. Describe proposed or completed operations. (Clearly state all estimated date of starting any proposed work). SEE RULE 111 diagram of proposed completion or recompletion. ESTIMATED START DATE. 1/15/09 1 MIRU plugging company. NU 2000# minimum BOP	The Oil Conservation Division Must be notified 24 hours prior to the beginning of plugging operations
2 RIH w/ tbg to 5100'. 3 Plug #1 (Producing Formation Plug) Spot 25 sxs (20 sxs +5 sxs excess) from 5100'-4950'=150'. WOC Tag plug 4 Circ hole w/ 9 0 PPG mud laden fluid (25 sxs x 50 # gel / 100 bbs brine) 5 POH tbg to 2500' 6 Plug #2 (Casing Plug) Spot 25 sxs (20 sxs +5 sxs excess) from 2500-2350=150' WOC. Tag plug	
7 RIH w/ tbg to 970' 8 Plug #3- (Salt Top Plug) Spot 25 sxs (20 sxs +5 sxs excess) from 970-820=150' WOC. Tag plug 9 POH tbg to 60' 10 Plug #4 - (Surface Plug) Pump 10 sxs (8 sxs +2sxs excess) from 60'-0'. 11 POH tbg. 12 Top off cement to surface 13 Cut off well head Weld on dry hole marker Backfill cellar. Clean location.	
Use Class "C" Cement Notify NMOCD-Hobbs (575-393-6161) 24 hrs. prior to commencing	operation.
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.	
SIGNATURE Kurwin TITLE: Senior Engineer	DATE: 12/17/08
Type or print name Kent Williams E-mail address: For State Use Only	Telephone No. (432) 689-5200
APPROVED BY: Conditions of Approval (if any): TITLE	DATEDATEDATEDATE

.

WELLBORE SCHEMATIC

