

N.M. Oil Cons. Division

1625 N. French Dr.

Hobbs, NM 88240

Form 3160-5
(September 2001)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB No. 1004-0135
Expires January 31, 2004

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

APACHE CORPORATION

3a. Address TWO WARREN PLACE, SUITE 1500

6120 S. YALE TULSA, OK 74136

3b. Phone No. (include area code)

(918) 491-4900

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

SEC. 8-T21S-R37E

1365' FSL, 1310' FEL

5. Lease Serial No.

NM 90161

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

HAWK B-1 #32

9. API Well No.

30-025-36158

10. Field and Pool, or Exploratory Area

PENROSE SKELLY; GRAYBURG

11. County or Parish, State

LEA

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice☐ Acidize☐ Alter Casing☐ Casing Repair☐ Change Plans☐ Convert to Injection☐ Deepen☐ Fracture Treat☐ New Construction☐ Plug and Abandon☐ Plug Back☐ Production (Start/Resume)☐ Reclamation☐ Recomplete☐ Temporarily Abandon☐ Water Disposal☐ Water Shut-Off☐ Well Integrity☒ Other SPUD; SET SURF

CSG; TD; SET PROD.

CSG.

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

PLEASE SEE ATTACHED DRILLING HISTORY.

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

LARRY E. RADER

Title TECHNICAL COORDINATOR-DRILLING

Signature

Date 3/3/03

ACCEPTED FOR RECORD

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

(ORIG. SGD) DAVID R. GLASS

Title

Date


Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

GWW



RECEIVED

2003 MAR -5 AM 10: 01

BUREAU OF LAND MGMT.
ROSWELL OFFICE

BUREAU OF LAND MGMT.
ROSWELL OFFICE

2003 MAR -5 PM 3: 58

RECEIVED

OPERATOR: APACHE CORPORATION
WELL: HAWK B-1 #32
API# 30-025-36158
LEASE S/N: NM-90161

2/22/2003 MIRU CAPSTAR RIG #8. SPUD 12-1/4" HOLE AND DRILL & SURVEY TO 410'. RIH W/ 8-5/8" 24# J55 CASING. RIH W/ 8-5/8" 24# J55 ST&C CASING. CEMENT SHOE @ 410' W/ 325 SX CLASS C + 2% CACL + 0.125 #/SX CELLO FLAKE =78 BBLs 14.8 PPG SLURRY, YIELD=1.35 CF/SX. CIRC. 83 SX CMT TO PIT. WOC.

2/23/2003 - 2/26/03 DRILL & SURVEY 410' - 3907'.

2/27/2003 DRILL 3907'-4200'. RAN LOGS. START RUNNING 5-1/2" CASING.

2/28/2003 RIH W/ 5-1/2" 17# J55 LT&C CASING. CEMENT SHOE @ 4200' W/ 500 SX 50:50 POZ:CLASS C W/ 10% GEL + 5% SALT + 0.125#/SX CELLO FLAKE + 0.003 GPS FP-6L=217 BBLs 11.8 PPG SLURRY, YIELD=2.44 CF/SX. TAIL W/ 250 SX 50:50 POZ:CLASS C W/ 2% GEL + 5% SALT + 0.003 GPS FP-6L=57 BBLs 14.2 PPG SLURRY, YIELD=1.29 CF/SX. CIRC. 133 SX CMT TO PIT. RELEASE RIG @ 9:30 AM 2/28/03.

RECEIVED
Hobbs
OCD