

Office

Energy, Minerals and Natural Resources

June 19, 2008

District I.

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM

87505

RECEIVED

FEB 18 2009

HOBBSD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-27081

5. Indicate Type of Lease

STATE ☐ FEE ☐ PRIV ☒

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

WOOLWORTH ESTATE SWD

8. Well Number 001

9. OGRID Number

241472

10. Pool name or Wildcat

SAN ANDRES SWD. 7 PWS

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other (Disposal Well) SWD

2. Name of Operator

SID RICHARDSON / SOUTHERN UNION GAS SERVICES, LTD

3. Address of Operator

301 COMMERCE SUITE 700, FT WORTH, TX 76102

4. Well Location

Unit Letter E : 1570 feet from the N line and 800 feet from the W line

Section 33 Township 24S Range 37E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3268 GR

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 2/6/09, the above well was permanently plugged and abandoned using the following procedure:

- 1) Removed Baker AD-1 packer and 2 7/8" tubing from well.
- 2) Set 4 1/2" cement retainer at 4350 ft and squeezed 50 sx Class C cement into existing perforations at 4440-4562 ft. Spot 25 Sx Class C on top of cement retainer. Stuck tubing. (Craft Wireline tagged bottom of cement in tubing at 3730 ft, measured stuck tubing at 3550 ft, measured freepoint at 3517 ft, backed off tubing at 3487 ft.)
- 3) Circulated 12.5 ppb brine mud in 4 1/2" wellbore.
- 3) Placed 2, 25 sx balanced cement plugs in 4 1/2" casing at 2821 ft and 1302 ft
- 4) Circulated 8 bbls of Class C to surface from 525 ft as per M. Whitaker w/ NMOCD.
- 5) Removed wellhead and welded on cap 3 ft below ground level. Placed marker on well.

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OGD Web Page under  
Forms, www.emnr.state.nm.us/ogd.

Spud Date:

2/4/2009

Rig Release Date:

2/6/2009

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

President Geotex for SUGS

DATE

2/13/2009

Type or print name

Alberto A. Gutierrez

E-mail address:

aag@geotex.com

PHONE:

505 842 8000

For State Use Only

APPROVED BY:

TITLE

DISTRICT 1 SUPERVISOR

DATE

FEB 20 2009

Conditions of Approval (if any):

**Woolworth Estate SWD #1**  
**API 30-025027081**

**P&A Sketch**

