

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		RECEIVED State of New Mexico Energy, Minerals and Natural Resources MAR 12 2009 Oil Conservation Division HOBBS 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003 WELL API NO. 30-025-24866 5. Indicate Type of Lease STATE ☒ FEE ☐ State Oil & Gas Lease No. B-1167	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well. OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☐ WORK ☐ DEEPEN ☐ PLUG ☒ DIFF. WELL OVER BACK RESVR. ☐ OTHER _____				7. Lease Name or Unit Agreement Name Shell State	
2. Name of Operator HANSON OPERATING COMPANY, INC.				8. Well No. #1	
3. Address of Operator P. O. Box 1515, Roswell, New Mexico 88202-1515				9. Pool name or Wildcat San Andres ; Eunice ; SW	
4. Well Location Unit Letter <u>O</u> : <u>660</u> Feet From The <u>South</u> Line and <u>1650</u> Feet From The <u>East</u> Line Section <u>36</u> Township <u>21 South</u> Range <u>36 East</u> NMPM <u>Lea</u> County					
10. Date Spudded 11/05/1974		11. Date T.D. Reached 11/22/1974		12. Date Compl. (Ready to Prod.) 06/18/2008	
13. Elevations (DF& RKB, RT, GR, etc.) 3493.2' GL		14. Elev. Casinghead			
15. Total Depth 6855'		16. Plug Back T.D. 4070'		17. If Multiple Compl. How Many Zones? _____	
18. Intervals Drilled By		Rotary Tools 0-6855'		Cable Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name 4015' - 4055' San Andres					20. Was Directional Survey Made Yes
21. Type Electric and Other Logs Run CNL, DLL, ML/GR, GR/CBL					22. Was Well Cored No
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	1160'	11"	450	Circulated
5 1/2"	15.5#	6853'	7 7/8"	450	
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
25. TUBING RECORD					
SIZE	DEPTH SET	PACKER SET			
2 7/8"	4050'				
26. Perforation record (interval, size, and number) CIBP at 4070' 4015' - 4055' 35 holes					
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
DEPTH INTERVAL			AMOUNT AND KIND MATERIAL USED		
4015' - 4055'			4000 gal 20% acid		
28. PRODUCTION					
Date First Production 06/18/2008		Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>) Pumping, 2 1/2" x 16' Tubing Pump			Well Status (<i>Prod. or Shut-in</i>) Producing
Date of Test 06/28/2008	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 0	Gas - MCF 0
Flow Tubing Press.	Casing Pressure 40	Calculated 24-Hour Rate	Oil - Bbl. 0	Gas - MCF 0	Water - Bbl. 150
29. Disposition of Gas (<i>Sold, used for fuel, vented, etc.</i>)					Test Witnessed By
30. List Attachments					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature <i>Carol J. Smith</i>		Printed Name Carol J. Smith		Title Production Analyst	Date 03/10/2009
E-mail Address hanson@dfn.com					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1124'	T. Canyon
T. Salt	1244'	T. Strawn
B. Salt	2490'	T. Atoka
T. Yates	2645'	T. Miss
T. 7 Rivers	2902'	T. Devonian
T. Queen	3358'	T. Silurian
T. Grayburg	3630'	T. Montoya
T. San Andres	3992'	T. Simpson
T. Glorieta	5100'	T. McKee
T. Paddock	5161'	T. Ellenburger
T. Blinebry	5452'	T. Gr. Wash
T. Tubb	6247'	T. Delaware Sand
T. Drinkard	6497'	T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	1124	1124	Anhydrite				
1124	2490	1366	Base of Salt				
2490	2645	155	Yates				
2645	2902	257	Seven Rivers				
2902	3358	456	Queen				
3358	3630	272	Grayburg				
3630	3992	362	San Andres				
3992	5100	1108	Glorieta				
5100	5161	61	Paddock				
5161	5452	291	Blinebry				
5452	6247	795	Tubb				
6247	6497	250	Drinkard				