

District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM 87505

RECEIVED
OIL CONSERVATION DIVISION
MAR 03 2009
HOBBSON
220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-025-10305 /
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> /
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	E. W. Walden /
8. Well Number	4 /
9. OGRID Number	012024 /
10. Pool name or Wildcat	Tubb Oil & Gas (86440) /

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☒ Other ☐

2. Name of Operator
John H. Hendrix Corporation /

3. Address of Operator
P. O. Box 3040, Midland, TX 79702-3040

4. Well Location
Unit Letter C : 660 feet from the North line and 2130 feet from the West line
Section 15 Township 22S Range 37E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3417' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: return well to production ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MIRU. GIH w/ PKR
2. Swab-test production interval
3. If test results prove economical, return well to production
4. If test results prove uneconomical, prepare to P&A well as attached.

*Off plug
Add shoe plug 2800-2900*

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie H. Westbrook TITLE Vice President DATE 3/2/09

Type or print name Ronnie H. Westbrook E-mail address: ronniew@jhhc.org PHONE: 432-684-6631

For State Use Only

APPROVED BY: [Signature] TITLE PETROLEUM ENGINEER DATE MAR 23 2009
Conditions of Approval (if any):

EW Walden #4

660' FNL & 2130' FWL, Sec 15, T22S, R37E, Lea County, New Mexico

GR ELEV is 3417'

API No. 30-025-10305

13 3/4" hole
Red Bed to 148'
RB & Shale 148-1150'

T/Anhydrite 1150'

T/Salt 1275' 9 5/8" hole
B/Salt 2375'

6 3/4" hole

SURFACE PLUG 60'

10 3/4" 40# Csg @ 148' w/100 sx to surface

300' Surface Plug from 200' - 300'

Perforate @ 148' and pump 25 sx cement into intermediate csg

(ANHYDRITE PLUG 100' FROM 1100 - 1200')

Perf @ 1200' and pump 25 sx cement into intermediate csg




1975 Squeeze TOC @ 2140'

7 5/8" 26# Csg @ 2852' w/1800 sx

Add shoe plug

Plug at 3000' interval From 2720-2820'

Original TOC @ 4500' (temp survey)

	P&A Mud
	New Cement Plugs
	Cement Behind Casing

PLUG ABOVE PROD. INTERVAL 100' from 5920-5820'

Tubb Production Interval 5920-6172'

PROD. CSG SHOE PLUG 100' FROM 6208-6308'

RBP @ 6235'

Drinkard Perfs 6309-6412'

CIBP @ 6430' - 1977 PBD @ 6430'

5 1/2" 17# Csg @ 6539' w/200 sx

CIBP @ 6520'

Original Drinkard Perfs 6460-6518'

TD 6540'

Drawn	BY
3/2/2009	CDH

JOHN H. HENDRIX CORPORATION
P.O. BOX 3040
Midland, TX 79702-3040

EW Walden #4

660' FNL & 2130' FWL
SEC 15, T22S, R37E
Lea County New Mexico