Submit 3 Copies To Appropriate District State of New Mexico Office Energy, Minerals and Natural Res		m C-103 ine 19, 2008
District I 1625 N. French Dr., Hobbs, NM 87240 RECEIVED	WELL API NO.	19,2000
	ISION <u>30-025-35762</u>	
District III District III Di	Dr. 5. Indicate Type of Lease STATE X FEE	
District IV HOBBS()(1)	6. State Oil & Gas Lease No.	
1220 S St Francis Dr , Santa Fe, NM 87505	29053	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUC DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR PROPOSALS.)		t Name:
1. Type of Well: Oil Well Image: Construction of Well	8. Well Number	
2. Name of Operator	9. OGRID Number	
Energen Resources Corporation		<u></u>
3. Address of Operator 3300 N. "A" St., Bldg 4, Ste. 100, Midland, TX 79705	10. Pool name or Wildcat / Saunders, San Andres	
4. Well Location		
Unit Letter <u>I</u> : <u>1980</u> feet from the <u>South</u> line and <u>660</u> feet from the <u>East</u> line		
Section 5 Township 15-S Range	33-E NMPM County	Lea
11. Elevation (Show whether DR, RK		
4217' GL 4228' RKB		
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A		
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB		
_		
	R: Install pumping equipment	<u> </u>
 Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 		
03-03-09/03-06-09 MIRU PU and pump truck. ND wellhead, unset packer. Csg on slight vacuum. SLMOOH w/tbg and packer. RIH w/bull plugged 3-1/2" slotted Mother Hubbard w/2-7/8" welded on couplings, a dressed 2-7/8" x 5-1/2" TAC, new API seating nipple and 158 joints 2-7/7" J-55 6.5# EUE 8rd tbg. ND BOP, set TAC in 19K# tension, NU wellhead. 7' KB corrected EOT @ 5008', TAC is @ 4976, SN is @ 4976. PU RIH w/a 1-1/4" x 15' gas anchor on new 2-1/2" x 1-1/2" x 16' SV, 3' SM/.005 clearance plunger, RHBC pump, w/a 7/8" FHSM coupling, 6-1 1/2" Flexbar "C" weight bars w/SHSM couplings, 16' of 7/8" WFT KD-63 series pony rods and a 1-1/4" x 22' polish rod w/1-1/4" x 1-1/2" x 14' PR liner. L&P tbg good to 500#. Hung rods, spaced pump 1' off bottom.		
Spud Date: Rig Release Date	2:	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNATURE AND TITLE	Regulatory Analyst DATE03	8-17-09
Type or print name Tracie J Cherry E-mail address: PHONE 432/684-3692		
For State Use Only	TROLGUM ENGINEER MAI	222000
APPROVED BY MAR 2 3 2009 Conditions of Approval (if any):		

• 1