

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

RECEIVED

OIL CONSERVATION DIVISION

MAR 24 2009
1220 South St. Francis Dr.
Santa Fe, NM 87505

HOBBSOCD

WELL API NO. 30-025-24391
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: SEMGSAU
8. Well Number 708
9. OGRID Number 005380
10. Pool name or Wildcat Maljamar; Grayburg-San Andres
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other Injection ☒

2. Name of Operator

XTO Energy, Inc.

3. Address of Operator

200 N. Loraine, Ste. 800 Midland, TX 79701

4. Well Location

Unit Letter 0 : 100' feet from the South line and 2590' feet from the East line

Section 29 Township 17S Range 33E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Repair Injection & RWTI ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/30/08 MIRU PU. ND WH. NU BOP & rel pkr. POOH w/2-3/8" IPC tbg. LD BJ 5-1/2" pkr. Chg BOP rams from 2-3/8" to 2-7/8".

12/31/08 PU RIH w/BJ 5-1/2" RBP, BJ 5-1/2" pkr & 129 jts of 2-7/8" N80 WS tbg. Set RBP @ 4,177'. PUH w/5-1/2" pkr & set @ 4,159'. RU pmp trk. L&T RBP w/1 bbl of 1% KCL. L&T TCA w/1 bbl of 1% KCL wtr. Rel pkr, L&T TCA w/.5 bbl of 1% KCL wtr. RD. Rel pkr, RIH latched onto RBP & rel. POOH LD w/2-7/8" WS tbg & tools. Chg BOP rams from 2-7/8" to 2-3/8".

Procedure Cont'd. on next page.

Spud Date: 12/30/08

Rig Release Date: 03/11/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kristy Ward TITLE Regulatory Analyst DATE 03/19/09

Type or print name Kristy Ward E-mail address: kristy_ward@xtoenergy.com PHONE 432-620-6740

For State Use Only

APPROVED BY [Signature] TITLE DISTRICT 1 SUPERVISOR DATE MAR 25 2009

Conditions of Approval (if any):

SEMGS AU #708
Repair Injector & RWTI

- 1/1/2009** RU tbg tstr. RIH w/5-1/2" BJ 1X Nickle Coated pkr 2-3/8" on-off tool w/1.78 F profile nipple, 132 jts 2-3/8" 4.7#, J-55, EUE, 8rd IPC tbg & 2 - 2-3/8" x 10' 4.7#, J-55, EUE, 8rd IPC tbg subs. Set pkr @ 4,171.48'. RU pmp trk. Rel on-off tool & circ w/100 bbls of pkr fluid. ND BOP & NU WH. RU chart recorder for MIT. L & T TCA w/1 bbl of pkr fluid. RD. Call NMOCD to witness MIT test.
- 1/3/2009** RU M&S vac trk. Attempted L & T TCA w/.4 bbl of 1% KCL wtr. Attempted L & T TCA w/.2 bbl of 1% KCL wtr. Attempted L & T TCA w/.2 bbl of 1% KCL wtr. ND WH & NU BOP. Rel pkr & PUH w/2-3/8" IPC tbg sub. Set pkr @ 4,161'. Attempted L & T TCA w/.8 bbl of 1% KCL wtr. Rel pkr & PUH w/2-3/8" IPC tbg sub. Set pkr @ 4,151'. Attempted L & T TCA w/1 bbl of 1% KCL. Rel pkr. POOH w/2-3/8" IPC tbg & LD pkr. RD M&S equip. Leave well open to battery.
- 1/6/2009** RIH w/5-1/2" BJ 1X Nickle Coated pkr 2-3/8" w/pump out plug on btm, on-off tool w/1.78 F profile nipple, 132 jts 2-3/8" 4.7#, J-55, EUE, 8rd IPC tbg & 2 - 2-3/8" x 10' 4.7#, J-55, EUE, 8rd IPC tbg subs. Set pkr @ 4,171.48'. RU M&S pmp trk. Rel on-off tool & circ w/100 bbls of pkr fluid. Latched back onto on/off tool. ND BOP & NU WH. RU chart recorder for MIT. L & T TCA w/1 bbl of pkr fluid to 520 psig. RD. Call NMOCD for MIT tst. RDMO PU. RWTI.
- 3/7/2009** MIRU PU. ND WH, NU BOP & rel pkr. POOH w/2-3/8" IPC tbg. LD BJ 5-1/2" pkr.
- 3/10/2009** RIH w/5-1/2" BJ 1X Nickle Coated pkr 2-3/8" w/pump out plug on btm, on-off tool w/1.78 F profile nipple, 132 jts 2-3/8" 4.7#, J-55, EUE, 8rd IPC tbg & 1 - 2-3/8" x 10' 4.7#, J-55, EUE, 8rd IPC tbg sub. Set pkr @ 4,162.60'. RU pmp trk. Rel on-off tool & circ w/100 bbls of pkr fluid. Latched back onto on/off tool. ND BOP & NU WH. RU chart recorder for MIT. L & T TCA w/1 bbl of pkr fluid. RD. Call NMOCD for MIT tst.
- 3/11/2009** RD PU. RWTI.

R/Allen XTO NOON 3/9/99

