

DUPLICATE

RECEIVED
MAY 29 1944
HOOVER
FEDERAL BUREAU OF INVESTIGATION
U. S. DEPARTMENT OF JUSTICE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). **SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.**

AREA 640 ACRES
LOCATE WELL CORRECTLY

Gordon M. Cone

P.O. Box 597, Lovington, New Mexico

Company or Operator

Address

Beery State Lease Well No. 1-A in NE SW of Sec. 30, T. 18S

R. 37E N. M. P. M. Wildcat Field Lea County

Well is 3300 feet south of the North line and 3200 feet west of the East line of Sec. 30-18S-37E.

If State land the oil and gas lease is No. B-9828 Assignment No. _____

If patented land the owner is State Address

If Government land the permittee is _____ Address _____

The Lessee is Joe A. Beery Addison Beery Address 5431 Ashby, Houston, Texas.

Drilling commenced Nov. 16, 1943 Drilling was completed Feb. 8, 1944

Name of drilling contractor Suppes & Suppes, Address Tulsa, Okla.

Elevation above sea level at top of casing 372 feet.

The information given is to be kept confidential until _____ 19____

OIL SANDS OR ZONES

No. 1, from 4575 to 4580 No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5 from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 40 to 150 feet.

No. 2, from 4600 to Sulphur feet. 5 gallons hourly

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
1 5/8	12 1/2	202'	100	Halliburton		
8 5/8	8 1/4	2788'	100	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
 Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0' feet to 2788' feet, and from _____ feet to _____ feet
 Cable tools were used from 2788' feet to 4609' feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing _____, 19____
 The production of the first 24 hours was _____ barrels of fluid of which _____ % was oil: _____ %
 emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
 If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
 Rock pressure, lbs. per sq. in. _____

EMPLOYEES

A. J. Smith Tom Oglesby _____, Driller W. Davis, Tool Dresser _____, Driller
J. I. Garrett D. F.W. Jeffers _____, Driller R. Kennedy, Tool Dresser _____, Driller
John Hohenshet H. L. Thompson _____, A. V. Nickels, Tool Dresser _____

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 26th

day of May, 19 44

Mary Stinebaugh
 Notary Public

My Commission expires April 23, 1946

Lovington, New Mexico 5-26-44
 Place Date

Name Gordon M. Cone Gordon M Cone

Position Owner

Representing _____
 Company or Operator

Address Lovington, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	30		Caliche
30	50		Caliche
50	90		Sand
90	112		Anhy
112	186		Sand
186	200		Anhy
200	512		Red Rock
512	520		Anhy
520	575		Red Rock
575	595		Anhy
595	715		Red Rock
715	1060		Red Rock & Anhy
1060	1146		Anhy
1146	1590		Red Rock & Anhy
1590	1637		Anhy
1637	2400		Red Rock & anhy
2400	2673		Salt
2673	2885		Anhy
2885	2930		Red Rock
2930	3395		Anhy Show gas 3040 3045
3395	3400		Blue Shale
3400	3500		Lime
3500	3530		Red Rock & Anhy
3530	3675		Anhy
3675	3700		Red Rock & Anhy
3700	3755		Anhy
3755	3795		Sand
3795	3835		Anhy
3835	3870		Brown Lime
3870	3990		Lime & Anhy
3990	3995		Lime Gray
3995	4000		Lime Brown
4000	4080		Lime Gray
4080	4090		Lime Brown
4090	4160		Lime Gray
4160	4170		Shale
4170	4473		Lime Gray
4473	4475		Sand Gray
4475	4503		Lime Gray
4503	4505		Lime White
4505	4510		Lime White
4510	4515		Lime White
4515	4525		Lime Gray
4525	4540		Lime Gray
4540	4550		Lime Gray
4550	4565		Lime Gray
4565	4580		Lime Gray
4580	4590		Lime Gray Show of oil from 4575 - 4580
4590	4600		Lime Gray
4600	4604		Lime Gray
4604	4608		Sand & Gray Matter Cemented at 4608 feet