

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr., Hobbs, NM 87240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

RECEIVED

State of New Mexico
Conservation and Natural Resources

Form C-103
June 19, 2008

APR 16 2009

HOBBSOCD

CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-05162
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: Denton North Wolfcamp Agree #8910087370
8. Well Number Tract 13, Well #6
9. OGRID Number 019958
10. Pool name or Wildcat Denton Wolfcamp
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
Oil Well ☐ Gas Well ☐ Other injection ☒

2. Name of Operator
Stephens & Johnson Operating Co.

3. Address of Operator
P.O. Box 2249, Wichita Falls, TX 76307-2249

4. Well Location
Unit Letter H : 330 feet from the East line and 2210 feet from the North line
Section 27 Township 14S Range 37E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3-1-07 Set Arrow pkr. w/plug @ 9230'. } NO C-103 IN FILES
11-21-08 Set CIBP @ 9158' with 20' cmt. } ADD PLUG - 3000' Cased Hole
BOS 1. Set 50 sx. cmt. plug @ 4660-4470' to protect base of salt. 4775-4470 SHOE & LINER TOP
2. Set 35 sx cmt plug @ 2210-2110' to protect top of salt 3100' - 3000' BOS
3. Set 35 sx cmt. plug @ 530-430'. PERF & SQZ
4. Set 5 sx.cmt plug @ 10-0'. PERF WOC & TAG

The Oil Conservation Division **Must be notified**
24 hours prior to the beginning of plugging operations.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bob Gilmore TITLE Petroleum Engineer DATE Apr 13, 2009
Type or print name Bob Gilmore, P.E. E-mail address: bgilmore@sjoc.net PHONE 940-723-2166

For State Use Only

APPROVED BY MSB TITLE _____ DATE _____
Conditions of Approval (if any):

DENIED