

RECEIVED**APR 14 2009****HOBSOCD**

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-30459

5. Indicate Type of Lease

STATE ☒FEE ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Samson Resources

3. Address of Operator

200 N. Loraine St, Suite 1010, Midland, Texas 79701

4. Well Location

Unit Letter K: 1980 feet from the South line and 2310 feet from the West lineSection 23Township 22SRange 34E

NMPM

Lea

County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3,447 GR

Pit or Below-grade Tank Application ☐ or Closure ☒Pit type STEEL Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water

Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/20/09 MIRU. Notify NM OCD Buddy Hill

2/23/09 Set 5" CIBP & Cap w/ 3sx-35' @ 12,018' TOC @ 11,983'. Set 5" CIBP @ 11,860 & Cap w/ 3sx-35' TOC @ 11,825'. Set 7 5/8" CIBP @ 10,750'.

2/24/09 T.I.H. w/ tbg. Tag CIBP. Circulate hole w/ 10# MLF & Spot 25sx cmt. Cal. TOC @ 10,623'.

2/25/09 Spot 45sx cmt. @ 7,779'. Cal. TOC @ 7,531'. Pull tbg. to 5,059'. Spot 45sx cmt. WOC-Tag @ 4,837'. Pull tbg. to 3,590'. Spot 45sx cmt. Cal. TOC @ 3,342'. Pull tbg. to 1,745'. Spot 45sx cmt. Cal. TOC @ 1,482'. Pull tbg. to 1,273'. Spot 45sx cmt. WOC

2/26/09 Tag TOC @ 1,083'. Mark Whitaker updated. Spot 20sx cmt. @ 60' - Surface. RDMO

Samson will cut off W.H. & install Dry Hole Marker.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.emnrd.state.nm.us/oed.I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.SIGNATURE [Signature] TITLE P&A Manager (Basic Energy Services) DATE 02/27/09

Type or print name

Randall Minear

E-mail address:

Telephone No. 432-530-0907

For State Use Only

APPROVED BY:

Conditions of Approval (if any):

TITLE

PETROLEUM ENGINEER

DATE

APR 16 2009