Office	State of New Mexico	Form C-103
District I Energy, N	Vinerals and Natural Resources	June 19, 200
1625 N. French Dr., Hobbs, NM 88240 District II		WELL API NO. 30-025-00302
1301 W. Grand Ave., Artesia, NM 88210 OIL CO	INSERVATION DIVISION	5. Indicate Type of Lease
1000 Rio Brazos Rd Aztec NM 87410	20 South St. Francis Dr.	STATE X FEE
District IV	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Fiancis Dr., Santa Fe, NM 87505		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		7. Lease Name or Unit Agreement Name Rock Queen Unit
PROPOSALS.)	Other	8. Well Number 75
2. Name of Operator CELERO ENERGY II, LP		9. OGRID Number
3. Address of Operator 400 W. Illinois, Ste. 1601		247128 10. Pool name or Wildcat
Midland, TX 79701		Caprock; Queen
4. Well Location		
	from the South line and 990	0 feet from the East line
	mship 13S Range 32E	NMPM County Lea
	(Show whether DR, RKB, RT, GR, etc.	
4374' KB		
12. Check Appropriate B	ox to Indicate Nature of Notice,	Report or Other Data
NOTICE OF INTENTION T PERFORM REMEDIAL WORK D PLUG AND A		SEQUENT REPORT OF: RK 🛛 🖾 ALTERING CASING [
	I	RK [X] ALTERING CASING [ILLING OPNS.] P AND A [
PULL OR ALTER CASING MULTIPLE CO	1	— —
OTHER:	OTHER:	
13. Describe proposed or completed operations of starting any proposed work). SEE RULE	. (Clearly state all pertinent details, an	Id give pertinent dates, including estimated d ttach wellbore diagram of proposed complet
 Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A	ttach wellbore diagram of proposed complet
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ¹/₂" pkr to 30'. Found 4 ¹/₂" csg to 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A D leak at surface. Repaired leak & test	ttach wellbore diagram of proposed complet
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¾" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A o leak at surface. Repaired leak & testo O tbg w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'.	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¾" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Loss 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A o leak at surface. Repaired leak & testo O tbg w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'.	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¾" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A o leak at surface. Repaired leak & testo O tbg w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator &
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¾" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & testor b tbg w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir ' 8 5/8" & 4 ½" csg & the WH's. Ran 3	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 3 ½" lead impression block. Found tbg
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & tester 0 tbg w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir 78 5/8" & 4 ½" csg & the WH's. Ran 3 of lish @ 75.5', set off jars twice & fish 3	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 its of 7
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg world. 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A b leak at surface. Repaired leak & tester D tbg w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir 78 5/8" & 4 ½" csg & the WH's. Ran 3 fish @ 75.5', set off jars twice & fish amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 ¾" wash	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 2 2' of 2 7/8" mud anchor. Mud anchor pipe & 3 7/8" mill shoe. Tagged @ 3045'.
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A b leak at surface. Repaired leak & test D tbg w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir $E 5/8$ " & 4 $\frac{1}{2}$ " csg & the WH's. Ran 3 fish @ 75.5', set off jars twice & fish amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}$ " wash to 3039'. Unable to get below 3039' w	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 c 2' of 2 7/8" mud anchor. Mud anchor pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'.
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A b leak at surface. Repaired leak & test D to by w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir $E 5/8$ " & 4 $\frac{1}{2}$ " csg & the WH's. Ran 3 fish @ 75.5', set off jars twice & fish amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}$ " wash to 3039'. Unable to get below 3039' w per. Attempted to lower mill. Stopped	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 2' of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'.
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A b leak at surface. Repaired leak & test D to by w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir $E 5/8" \& 4 \frac{1}{2}" csg \&$ the WH's. Ran 3 D fish @ 75.5', set off jars twice & fish and amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}"$ wash to 3039'. Unable to get below 3039' w per. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corroo	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. 1 at 3030'. No recovery. Mill was not worn. led at 550' & from an area from 750' to
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 3030'. TOC=24 	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A b leak at surface. Repaired leak & test D to by w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir $E 5/8" \& 4 \frac{1}{2}" \cos g \&$ the WH's. Ran 3 D fish @ 75.5', set off jars twice & fish amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}"$ wash to 3039'. Unable to get below 3039' w per. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corrooc R6'. Ran packer. Tested csg from sur-	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 2 of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. led at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 1/2" pkr to 30'. Found 4 1/2" csg to 3/4" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 1/4" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 300". TOC=24 BPM at 200#. Pressure would go to 300# & fall peld. 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & test. b tog w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir ' $85/8" \& 4 \frac{1}{2}" csg \&$ the WH's. Ran 3 of fish @ 75.5', set off jars twice & fish is amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}"$ wash to 3039'. Unable to get below 3039' w beer. Attempted to lower mill. Stopped in surface to 3030'. Csg appears corroc (86'. Ran packer. Tested csg from sur- back below 200#, three different times b csg at 1 16" BPM at 200#.	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¼" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 c 2' of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. ded at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ c. Raised pkr to 487', tested annulus to 400#
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 3030'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in put Lower pkr to 740'. Unable to set. Start out hole. 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & test c to be w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir ' 8 5/8" & 4 $\frac{1}{2}$ " csg & the WH's. Ran 3 fish @ 75.5', set off jars twice & fish amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}$ " wash to 3039'. Unable to get below 3039' w er. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corroo 86'. Ran packer. Tested csg from sur- back below 200#, three different times n csg at 1./2" BPM at 200#. Appears to . Packer started dragging. Packer drug-	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & can 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 3 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 c 2' of 2 7/8" mul anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. led at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ Raised pkr to 487', tested annulus to 400# o be a hole at 550' based on csg inspection Ic g all of the way out of hole. Found rubber
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¾" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deer Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 3030'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in put Lower pkr to 740'. Unable to set. Start out hole gone. Attempted to run and set CIBP at 2970'. Total content of the set of the set of the set of the set of the set. Start out hole gone. 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & tests b tog w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir 78 5/8" & 4 ½" csg & the WH's. Ran 3 f ish @ 75.5', set off jars twice & fish a mp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 ¼" wash to 3039'. Unable to get below 3039' w ber. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corroor 86'. Ran packer. Tested csg from sur- back below 200#, three different times n csg at 1.½" BPM at 200#. Appears to . Packer Started dragging. Packer drug Unable to go below 550'. Stopped at 5	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & can 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 3 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 c 2' of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. led at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ c. Raised pkr to 487', tested annulus to 400# o be a hole at 550' based on csg inspection lo g all of the way out of hole. Found rubber 150'. Ran 3 3/4" tapered mill. Unable to rot
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 3030'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in Lower pkr to 740'. Unable to set. Start out hole gone. Attempted to run and set CIBP at 2970'. It thru spot at 550'. TOH. Ran tbg open ended to 60 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & test b to whotched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir ' 8 5/8" & 4 $\frac{1}{2}$ " csg & the WH's. Ran 3 fish @ 75.5', set off jars twice & fish imp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}$ " wash to 3039'. Unable to get below 3039' w ber. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corroo 86'. Ran packer. Tested csg from sur back below 200#, three different times n csg at 1. $\frac{1}{4}$ " BPM at 200#. Appears to . Packer started dragging. Packer drug Unable to go below 550'. Stopped at 5 510', able to get thru the spot. Raised t	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 2 of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. led at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ 5. Raised pkr to 487', tested annulus to 400# o be a hole at 550' based on csg inspection lo g all of the way out of hple. Found rubber 50'. Ran 3 3/4" tapered mill. Unable to rota bg to 500'. SION.
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¾" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deer Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 3030'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in put Lower pkr to 740'. Unable to set. Start out hole gone. Attempted to run and set CIBP at 2970'. Total content of the set of the set of the set of the set of the set. Start out hole gone. 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & test b to whotched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir ' 8 5/8" & 4 $\frac{1}{2}$ " csg & the WH's. Ran 3 fish @ 75.5', set off jars twice & fish imp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}$ " wash to 3039'. Unable to get below 3039' w ber. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corroo 86'. Ran packer. Tested csg from sur back below 200#, three different times n csg at 1. $\frac{1}{4}$ " BPM at 200#. Appears to . Packer started dragging. Packer drug Unable to go below 550'. Stopped at 5 510', able to get thru the spot. Raised t	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 2' of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. led at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ <u>c. Raised pkr to 487', tested</u> annulus to 400# o be a hole at 550' based on csg inspection lo g all of the way out of hole. Found rubber 50'. Ran 3 3/4" tapered mill. Unable to rota bg to 500'. SION.
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 3030'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in put Lower pk' to 740'. Unable to set. Start out hole, gone. Attempted to run and set CIBP at 2970'. It thru spot at 550'. TOH. Ran tbg open ended to 6 hereby certify that the information above is true and 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & test b to whotched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir ' 8 5/8" & 4 $\frac{1}{2}$ " csg & the WH's. Ran 3 fish @ 75.5', set off jars twice & fish imp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}$ " wash to 3039'. Unable to get below 3039' w ber. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corroo 86'. Ran packer. Tested csg from sur back below 200#, three different times n csg at 1. $\frac{1}{4}$ " BPM at 200#. Appears to . Packer started dragging. Packer drug Unable to go below 550'. Stopped at 5 510', able to get thru the spot. Raised t	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 2 of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. led at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ 5. Raised pkr to 487', tested annulus to 400# o be a hole at 550' based on csg inspection lo g all of the way out of hple. Found rubber 50'. Ran 3 3/4" tapered mill. Unable to rota bg to 500'. SION.
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 3030'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in Lower pkr to 740'. Unable to set. Start out hole gone. Attempted to run and set CIBP at 2970'. It thru spot at 550'. TOH. Ran tbg open ended to 60 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & test b to whotched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir ' 8 5/8" & 4 $\frac{1}{2}$ " csg & the WH's. Ran 3 fish @ 75.5', set off jars twice & fish imp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 $\frac{3}{4}$ " wash to 3039'. Unable to get below 3039' w ber. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corroo 86'. Ran packer. Tested csg from sur back below 200#, three different times n csg at 1. $\frac{1}{4}$ " BPM at 200#. Appears to . Packer started dragging. Packer drug Unable to go below 550'. Stopped at 5 510', able to get thru the spot. Raised t	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 2' of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. ded at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ 5. Raised pkr to 487', tested annulus to 400# o be a hole at 550' based on csg inspection lo g all of the way out of hple. Found rubber 50'. Ran 3 3/4" tapered mill. Unable to rota bg to 500'. SION.
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¾" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 300'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in Lower pkr to 740'. Unable to set. Start out hole gone. Attempted to run and set CIBP at 2970'. It thru spot at 550'. TOH. Ran tbg open ended to 6 hereby certify that the information above is true and IGNATURE	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b leak at surface. Repaired leak & tested b to gw/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir 78 5/8" & 4 ½" csg & the WH's. Ran 3 o fish @ 75.5', set off jars twice & fish 1 mp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 ¼" wash to 3039'. Unable to get below 3039' w ber. Attempted to lower mill. Stopped n surface to 3030'. Csg appears corroo 86'. Ran packer. Tested csg from sur- back below 200#, three different times n csg at 1.½" BPM at 200#. Appears to . Packer started dragging. Packer drug Unable to go below 550'. Stopped at 5 510', able to get thru the spot. Raised to d complete to the best of my knowledg	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & . an 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¼" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 3 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 c 2' of 2 7/8" mul anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. led at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ c. Raised pkr to 487', tested annulus to 400# o be a hole at 550' based on csg inspection lo g all of the way out of hole. Found rubber 50'. Ran 3 3/4" tapered mill. Unable to rota bg to 500'. SION. ge and belief. DATE _04/27/2009
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¼" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worf RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 3030'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in Duble to reach fish. Ran tsg open ended to 6 hereby certify that the information above is true and IGNATURE 	. (Clearly state all pertinent details, an 2 1103. For Multiple Completions: A b) leak at surface. Repaired leak & test c) the w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir ' 8 5/8" & 4 ½" csg & the WH's. Ran 3 o fish @ 75.5', set off jars twice & fish 1 amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 ¼" wash to 3039'. Unable to get below 3039' w ber. Attempted to lower mill. Stopped in surface to 3030'. Csg appears corroor 86'. Ran packer. Tested csg from sur- back below 200#, three different times in csg at 1.½" BPM at 200#. Appears to . Packer statted dragging. Packer dru Unable to go below 550'. Stopped at 5 510', able to get thru the spot. Raised t d complete to the best of my knowledg TITLE_Regulatory Analyst E-mail address: LHunt@celeroen	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & can 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 c 2' of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. at 3030'. No recovery. Mill was not worn. ded at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ c. Raised pkr to 487', tested annulus to 400# o be a hole at 550' based on csg inspection lo g all of the way out of hple. Found rubber 50'. Ran 3 3/4" tapered mill. Unable to rota bg to 500'. SION. ge and belief. DATE_04/27/2009 hergy.comPHONE: _(432)686-1883
 13. Describe proposed or completed operations of starting any proposed work). SEE RULE or recompletion. 4/22/09 - Ran 4 ½" pkr to 30'. Found 4 ½" csg to ¾" taper mill. Stop at 70'. TOH. Ran 2 3/8" OE tbg w/notched collar. RU swivel & C/O from 70' to 75.5'. Recovered very fine metal cuttings. Los stopped at 75.5'. 4/23/09 - Dug out cellar & replaced a few feet of looking up at 75.5'. TIH w/taper tap. Screw into 7/8" tbg, 1 - 2' x 2 7/8" tbg sub, 2 ¼" x 12' tbg pu appears to be broken off. TIH w/ 2 3/8" tbg worl RU swivel. Worked mill up & down from 3015' 4.24.09 - Lower mill to 3039'. Unable to go deep Unable to reach fish. Ran csg inspection log from 1350'+. Ran CBL from 2350' to 300'. TOC=24 BPM at 200#. Pressure would go to 300# & fall held. Lower packer to 618'. Pumped into hole in Lower pkr to 740'. Unable to set. Start out hole gone. Attempted to run and set CIBP at 2970'. It thru spot at 550'. TOH. Ran tbg open ended to 6 hereby certify that the information above is true and IGNATURE	. (Clearly state all pertinent details, an E 1103. For Multiple Completions: A b leak at surface. Repaired leak & test. b tog w/notched collar to 70'. TOH. R ' to 75', recovering "rust". Stop at 75'. st circulation the last one inch of millir '8 5/8" & 4 ½" csg & the WH's. Ran 3 of fish @ 75.5', set off jars twice & fish i amp, 1 - 3' x 2 7/8" perforated nipple & k string, DC's, jars, one jt of 3 ¼" wash to 3039'. Unable to get below 3039' w ber. Attempted to lower mill. Stopped in surface to 3030'. Csg appears corroc 86'. Ran packer. Tested csg from sur- back below 200#, three different times i csg.at 1.½" BPM at 200#. Appears to . Packer staffed dragging. Packer dru- Unable to go below 550'. Stopped at 5 510', able to get thru the spot. Raised t d complete to the best of my knowledg 	ttach wellbore diagram of proposed complet ed to 250#. Held okay. TIH w/tbg, DC's & can 1 11/16" collar locator. Stop at 70'. Ran TOH. Ran 3 ¾" taper mill & milled from 7 ng. TOH. Re-ran 1 11/16" collar locator & 8 ½" lead impression block. Found tbg started coming out of hole. Pulled 95 jts of 2 c 2' of 2 7/8" mud anchor. Mud anchor n pipe & 3 7/8" mill shoe. Tagged @ 3045'. //mill shoe. PU mill to 3015'. 1 at 3030'. No recovery. Mill was not worn. ded at 550' & from an area from 750' to face to 987'. Pumped down annulus at 1 ½ c. Raised pkr to 487', tested annulus to 400# o be a hole at 550' based on csg inspection lo g all of the way out of hole. Found rubber 50'. Ran 3 3/4" tapered mill. Unable to rota bg to 500'. SION. ge and belief. DATE 04/27/2009 hergy.com PHONE: (432)686-1883

`