

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
OCD-HOBBS
APR 28 2009
HOBBSOCD

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

OXY USA Inc.

16696

3a. Address

P.O. Box 50250, Midland, TX 79710-0250

3b. Phone No. (include area code)

432-685-5717

4. Location of Well (Footage, Sec., T, R., M, or Survey Description)

660 FSL 660 FWL SWSW(M) Sec 4 T24S R34E

5. Lease Serial No.

LC061374A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.

Bell Lake 28

9. API Well No.

30-025-38565

10. Field and Pool, or Exploratory Area

Salt Lake Delaware, South

11. County or Parish, State

Lea NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Acidize

☐ Alter Casing

☐ Casing Repair

☐ Change Plans

☐ Convert to Injection

☐ Deepen

☐ Fracture Treat

☐ New Construction

☐ Plug and Abandon

☐ Plug Back

☐ Production (Start/Resume)

☐ Reclamation

☐ Recomplete

☐ Temporarily Abandon

☐ Water Disposal

☐ Water Shut-Off

☐ Well Integrity

☒ Other Spud. Set

Casing & Cement

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

See Attached

ACCEPTED FOR RECORD

APR 26 2009

BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICE

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

David Stewart

Title

Sr. Regulatory Analyst

Date

4/15/09

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

PETROLEUM ENGINEER

Date

MAY 01 2009

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

BELL LAKE #28

SPUD WELL @ 2000HRS 6/11/08.

DRILL 17-1/2" SURFACE HOLE TO TD @ 1200'

RUN 13-3/8" 48# H-40 STC CASING & SET @ 1200'

CEMENT W/ 680sx PP C W/ 4% BENTONITE + 2% CACL2 + 1#/sx PHENO SEAL 13.5PPG 1.75 YIELD
FOLLOWED BY 400sx PP C W/ 2% CACL2 14.8PPG 1.35 YIELD. CIRC 350sx TO SURFACE. PLUG DOWN
NU BOP AND TEST

DRILLED 12-1/4" INTERMEDIATE HOLE TO TD @ 5095', 6/22/08.

RUN 8-5/8" 32# J55/k55 CASING & SET @ 5095'.

CEMENT W/ 1150sx IFC W/ 1#/sx PHENOSEAL @ 11.9 PPG, 2.48 YIELD FOLLOWED BY 200sx PP @ 14.8
PPG, 1.33 YIELD. DISPLACE, BUMP PLUG, CIRC 15BBLS CEMENT SLURRY TO SURFACE. 6/23/08.

NU BOP AND TEST

6/25/08, DRILLED 7-7/8" PRODUCTION HOLE TO TD @ 8968' 7/3/08

CIRC HOLE, RIH W/ OH LOGS

RUN 5-1/2", 17#, L80, LTC CASING & SET @ 8965'

CEMENT W/ 170sx IFH @ 11.9PPG, 2.49 YIELD FOLLOWED BY 550sx 50/50 PZ/P @ 14.1 PPG, 1.31 YIELD.
DISPLACE, BUMPED PLUG 7/4/08. CEMENT DID NOT CIRC.

ESTIMATED TOP OF CEMENT @ 4807'

RELEASE RIG AT 10:00HRS. 7/5/08