

Submit 3 Copies To Appropriate District Office.

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103
Revised June 10, 2003

WELL API NO.

30-025-30527

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Cooper

8. Well Number

1

9. OGRID Number

014462

10. Pool name or Wildcat

Skaggs Glorieta Northwest

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Me-Tex Oil & Gas, Inc.

3. Address of Operator

P.O. Box 2070, Hobbs, NM 88241-2070

4. Well Location

Unit Letter 2 : 660 feet from the North line and 1980 feet from the East line

Section 3 Township 20S Range 37E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3556 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Adding Perfs. within the same zone ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Rig up "lite prop" frac job. Frac Glorieta zone 5278' - 5298', est. 1800# 14/30 lite prop at 17.5 bpm and 4000 psi. Screened out @ 6,300 psi. Set pkr. and swabbed well to recover load.
2. R.I.H. with R.B.P. & set @ 5,272'; R.I.H. with 4" Heggs gun, 2 J.S.P.F., 180° phase. Perf. Glorieta added zones as follows: 5235', 37', 41', 44', 55', 58', 60', 62', 63', & 66' (20 holes).
3. Spot 2 bbls. 20% Hcl Acid across perfs. 5,266' - 5,180'; R.I.H. with 5-1/2" Arrow-Set pkr. & set @ 5,114'; comm. swbg.
4. Rig B.J. Services & acidized glorieta zone 5255' - 5266' w/ 3,500 gals. 20% Hcl acid & ball sealers, 4.8 bbls./min. T.P., 800-1000 psi; balled out with max. psr. 4050 psi.; swbd. for load recovery and put to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Tonia Harper

TITLE

Production Clerk

DATE December 15, 2003

Type or print name Tonia Harper

E-mail address: toniaharper@hotmail.com

Telephone No. 505-397-7750

(This space for State use)

APPROVED BY

Gary W. Wink

TITLE

DATE

Conditions of approval, if any:

