

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

RECEIVED

JUN 02 2009

HOBBSCO

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-025-26679 ✓
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input type="checkbox"/> ✓
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	East Vacuum GB/SA Unit Tract 3332 ✓
8. Well Number	002 ✓
9. OGRID Number	217817 ✓
10. Pool name or Wildcat	Vacuum; Grayburg-San Andres ✓
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	3932' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☒

2. Name of Operator ConocoPhillips Company /

3. Address of Operator 3300 N. "A" St., Bldg. 6
Midland, TX 79705

4. Well Location
Unit Letter A : 150 feet from the EAST line and 250 feet from the NORTH line
Section 33 Township 17S Range 35E NMPM County LEA ✓

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Bradenhead test previously submitted on 5/21/2009, because of failed test on 2/10/2009. Surface casing had hole between 6'-11'. Loaded well with 35 sx cement, WOC, circulate to surface. Install 2-7/8" tubing @ 4520'.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Jalyn N. Fiske

TITLE Regulatory Specialist

DATE 05/29/2009

Type or print name Jalyn N. Fiske

E-mail address: Jalyn.Fiske@conocophillips.com PHONE: (432)688-6813

For State Use Only

APPROVED BY:

[Signature]

TITLE

PETROLEUM ENGINEER

DATE

JUN 04 2009

Conditions of Approval (if any):