Submit 3 Copies To Appropriate District State of New Me Office Finergy Minerals and Natu	
	ral Resources June 19, 2008 WELL API NO.
District I 1625 N. French Dr., Hobbs, NM 8 PLOCATION District II 1301 W. Grand Ave., Artesia, NM 88210 1220 South St. Fra	N DIVISION 30-025-08331
District III July 1220 South St. 11d	incis Di.
1000 Rio Brazos Rd , Aztec, NM 87410N 02 2009 Santa Fe, NM 80 District IV	
1220 S St. Francis Dr., Santa Fe, MOBBSOCD 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WEL	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-10 PROPOSALS.)	
1. Type of Well: Oil Well X Gas Well Other	8. Well Number
2. Name of Operator	9. OGRID Number
Energen Resources Corporation 3. Address of Operator	162928 10. Pool name or Wildcat
3300 N A St., Bldg. 4, Ste. 100 Midland, Tx 79705	
4. Well Location	
Unit Letter D: 660 feet from the Nor	th line and 660 feet from the West line
Section 2 Township 15S	Range 33E NMPM County Lea
11. Elevation (Show whether	
4183'	
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS. P AND A
PULL OR ALTER CASING MULTIPLE COMPL	CASING/CEMEN Approved for plugging of well bore only.
DOWNHOLE COMMINGLE	Liability under bond is retained pending receipt 4
BOWWHOLE GOWHIN TOLL	of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
OTHER:	OTHER:
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
05/13/09 - MIRU Basic Rig. RIH to 8230'. SIFN.	
05/14/09 - Tag CIBP @ 9640'. Displace hole with gelled brine. Spot 25 sx cmt balance plug 9640'-9390'	
(Class C, 15 ppg, 1.32 yield). LD tbg to 6700'. Spot 25 sx balance plug 6700'-6450' (Class C, 15 ppg, 1.32 yield). POOH. RU WL, perf 4290' 4 SPF. Set pkr 3490'. Test annulas, broke circulation between 8-5/8"	
8 5-1/2", pump 60 sx (Class C). Displace to 4090' Sl	
05/15/09 - Tag plug @ 3947' & test. RU WL perf 5-1/2	
Class 'C'. Displace to 1300' SIFWE.	
05/18/09 - POOH w/tbg, RU WL. Tag plug @ 1250'. PU t 1.32 yield). Circulate cmt to surface. RDPU. Well P&A	to 360' perf @ 360 w/4 SPF. Pump 100 sx cmt (Neat, 15ppg
Spud Date: 5-12-51 Rig Relea	se Date: N/A
I hereby certify that the information above is true and complete to the	best of my knowledge and belief.
J. Ollins /	, -
SIGNATURE (X)a(in) Clyfl Yuf TITI	
Type or print name Tracie J Cherry E-mail address: PHONE 432/684-3692	
For State Use Only JUN 0 4 2009	
APPROVED BY Comp (1) TIT	LE DISTRICT 1 SUPERVISOR DATE DATE
Conditions of Approval (if any):	