

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

RECEIVED

OIL CONSERVATION DIVISION

JUN 23 2009 20 South St. Francis Dr.

Santa Fe, NM 87505

HOBBSCOCD

WELL API NO.
30-025-367885. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☒2. Name of Operator
TRILOGY OPERATING, INC3. Address of Operator
P.O. BOX 7606, MIDLAND, TEXAS 79708

7. Lease Name or Unit Agreement Name

ROBINSON

8. Well Number 1

9. OGRID Number
02160210. Pool name or Wildcat ☒
NADINE - BLINEBRY EAST

4. Well Location

Unit Letter L : 1972 feet from the SOUTH line and 342 feet from the WEST line
Section 19 Township 19S Range 39E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3575 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/02/09 - POOH w/ tbg - RUWL - drop gauge ring to 6150' - RIH w/ CIBP & set @ 6100' - dump bail 35' of cement on top of plug
RIH w/ tbg - circulate hole w/ brine gel as per NMOCD rep. POOH w/ tbg - RIH w/ WL and set CIBP @ 3000' - dump bail
35' of cement on top of plug.

6/03/09 - RUWL and cut off 5 1/2" casing @ 1800' - POOH and LD casing, RIH w/ tbg and pump 70 sxs cement (class C - neat) - WOC
3 hrs - RIH and tag TOC @ 1540'. RIH to 348' and pump 20 sxs cement (class C - neat), pull tbg to 62' and circulate 20 sxs
Cement to surface. Cut off well head and clean location - cap off w/ dry hole plate so farmer can plow field. Plugging was
Witnessed and approved by field inspector from NMOCD - Mr. Whitaker

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OQD Web Page under
Forms, www.emnrd.state.nm.us/oqd.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

PRESIDENT

DATE 6/19/09

Type or print name

Michael G Mooney

E-mail address: Mike@Trilogyoperating.com

PHONE: 432/686-2027

For State Use Only

APPROVED BY:

TITLE

DISTRICT 1 SUPERVISOR

DATE

JUN 24 2009

Conditions of Approval (if any):