

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N French Dr, Hobbs, NM 87401  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd, Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

RECEIVED

OIL CONSERVATION DIVISION  
JUN 24 2009  
220 South St. Francis Dr.  
Santa Fe, NM 87505

HOBSOCD

WELL API NO. 30-041-10168
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E10047
7. Lease Name or Unit Agreement Name: Todd Lower SA Unit
8. Well Number 365
9. OGRID Number 16696
10. Pool name or Wildcat Todd Lower San Andres (Assoc)

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other Injection <input checked="" type="checkbox"/>	2. Name of Operator OXY USA Inc.
3. Address of Operator P.O. Box 50250 Midland, TX 79710-0250	4. Well Location Unit Letter <u>E</u> : <u>1980</u> feet from the <u>north</u> line and <u>660</u> feet from the <u>west</u> line Section <u>36</u> Township <u>7S</u> Range <u>35E</u> NMPM County <u>Roosevelt</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4165'	

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms, [www.emnrd.state.nm.us/oed](http://www.emnrd.state.nm.us/oed).

See Attachment

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE David Stewart TITLE Sr. Regulatory Analyst DATE 6/22/09

Type or print name David Stewart

E-mail address: david\_stewart@oxy.com  
Telephone No. 432-685-5717

For State Use Only

APPROVED BY Tony W. Hill TITLE DISTRICT 1 SUPERVISOR DATE JUN 26 2009

Conditions of Approval, if any.

**TLSAU #365**

<b>Date</b>	<b>Remarks</b>
6/15/09	MI RU PU, NDWH, NU BOP TALLEY IN THE HOLE WITH 2 3/8" WORK STRING TAG @ 4112' CIRCULATE WITH 10 PPG MUD LAIDEN FLUID SPOT 25 SX CMT WITH 2% CACL2, POOH, WOC RIH & TAG CMT @ 3749'. PUH TO 3553', SPOT 25SX CMT W/ 2% CACL2 TO 3278'
6/16/09	POOH W/ TUBING, RIH W/ 4.5" AD-2 PACKER @ 1761' RIH W/ WIRELINE, PERFORATE @ 2130' SQUEEZE 45 SX CMT W/ 2% CACL2 SI, WOC. 2 HOURS TAG CMT @ 1960' MOVE PACKER UP HOLE, SET @ 803' RUN IN W/ WIRELINE, PERFORATE @1200' SQUEEZE 45 SX W/ 2% CACL2 SI, WOC. 2 HOURS, POOH W/ PACKER RIH W/ WIRELINE, TAG CMT @1010' PERFORATE @ 389' PUMP 100SX CMT AND CIRCULATE TO SURFACE ND BOP, TOP OFF CASING, RDPU