Form 3160-5 (August 1999)

applicant to conduct operations thereon

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No 1004-0135 Expires November 30,2000

SUNDRY NOTICES AND REPORTS ON WELLS					LC-069515		
Do not use this form for proposals to drill or to re-ented BSOCD abandoned well. Use Form 3160-3 (APD) for such proposals					6 If Indian, A	llottee or Tribe Nai	me
abandoned w							
					7 If Unit or C	A/Agraement Non	na and/or
SUBMIT IN TRIPLICATE - Other Instructions on reverse side					7 If Unit or CA/Agreement, Name and/or No		
					North El Mar Unit		
1 Type of Well					NM 70994X		
☐ Oil Well ☐ Gas Well ☐ Other					8 Well Name and No		
2 Name of Operator					North El Mar Unit #7		
Sahara Operating Company					9. API Well No		
3a Address 3b Phone No. (include area code)					30 025 08286		
P.O. Box 4130, Midland, TX 79704 432/697-0967					10 Field and Pool, or Exploratory Area		
4 Location of Well (Footage, Sec., T, R, M, or Survey Description)					El Mar (Delaware)		
660' FNL & 1980' FWL, Sec 25, T26S, R32E, NMPM					11 County or Parish, State		
Unit Letter "C"					Lea County, N.M.		
12 CHECK APPR	OPRIATE BOX(ES) TO) INDICATE N	LATURE OF N	JOTICE R	FPORT OR	OTHER DATA	Δ
TYPE OF SUBMISSION		O III DIOILLO II	TYPE OF A		Er oltr, olt	OTTIBIC BILLI	
	Acidize Deepen				(Start/Resume)	☐ Water Shut-0	
Notice of Intent	Alter Casing	Fracture Tre	onternant.	Reclamatio	` ′	Well Integrit	
	-			_			У
Subsequent Report	Casing Repair	New Constr	Construction Recomple		2	Other	
	Change Plans	Change Plans Plug and Al		Temporaril	y Abandon		
Final Abandonment Notice	Convert to Injection	Plug Back		☐ Water Disp	osal		-
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA Required subsequent reports shall be file within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Propose to P&A well as follows: 1. TIH and tag Retainer @ 3770' Circ hole w/mud 2. Perf 920', sqz 35 sx, tag 100' D/ag in/out of 4/2' Csg. 3. Perf 400', sqz 35 sx, tag 4. Perf 60', fill in/out to surface 5. install dry hole marker							
Wellbore as follows: 7-5/8" casing @ 345' w/175 sx, circ. 4-1/2" casing @ 4675' w/375 sx, TOC 2900' by temp survey. Well had water flow while drilling @ 3800', casing leak @ 3838-3867', squeezed under Cement Retainer @ 3770', retainer and squeeze job left in hole w/CIBP @ 4610' Perfs 4630-4644' Top of salt: 865'							
14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)							
Robert McAlpine			T.d. Y	Dragidant			
ROBERT IVICA		Title I	President			····	
Signature Date 6/10/2009							
THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
/	00					1 1,	2 89
				SEPS]]	Date 6-23	, ~)
Conditions of approval, if any are attached. Approval of this notice does not warrant or certify that							

Title 18 USC Section 1001 and Title 43 USC Section 1212, make it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction


North El Mar Unit #7 660' FNL & 1980' FWL, Sec 25 T26S, R32E, NMPM Unit Letter "C"

7-5/8" casing @ 345' w/175 sx, circ.

4-1/2" casing @ 4675' w/375 sx, TOC 2900' by temp survey.

Perfs 4630-4644' Well had water flow while drilling @ 3800'.

12-21-86	Set CIBP @ 4610'.
12-23-86	Ran 4-1/2" pkr, isolated casing leak
	3838-3867'. Ran and swung cement
	retainer @ 3770'
12-24-86	Set retainer, tested casing above to
	500# OK. Mixed and pumped 200 sx
	(47 bbls) class C w/2% CaCl2.
	Displaced to retainer.
12-29-86	Ran tbg to 3665'. Left retainer in
	hole.



1. El MAR Unit #7	SALT SECTIONS TOP 865
HOLE SIZE	1 pert @ 60° circ. infort BASE 4358
	RILLE
	CAVE/KARST
175	SPEC WATER
175 SX 41-40	
CASING SIZE 75/8" 24" TD 353	Le Pert @ 400 Sg. To 300
HOLESIZE	
	FORMATIONS Del 4/582
	1 Perfe 920 SQ, TO 820 -
Volume La Volume	in the same of the
The purple of the state of the	
275 54 700	
2900	
	CR 3770
T-55	CIEFO DIT
1	
CASING SIZE 4/2 9,5	PERFORATIONS 4630-4644
41.75	

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1 Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

- 2 <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed prior to commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E Greene St Carlsbad. New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To 1310

Reclamation (Interim/Final) Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Terry Gregston Environmental Protection Specialist 575-234-5958

Bobby Ballard Environmental Protection Specialist 575-234-2230

Randy Rust Environmental Protection Specialist 575-234-5943

Linda Denniston Environmental Protection Specialist 575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Justin Frye Environmental Protection Specialist 575-234-5922 Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Doug Hoag Civil Engineering Technician 575-234-5979