

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFORM APPROVED  
OMB NO. 1004-0135  
Expires July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*

JUN 26 2009

5. Lease Serial No.  
NMNM96244

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

8. Well Name and No  
LIVESTOCK FEDERAL 939. API Well No  
30-025-3801310. Field and Pool, or Exploratory  
DAGGER LAKE, Delaware11. County or Parish, and State  
LEA COUNTY, NM**SUBMIT IN TRIPLICATE - Other instructions on reverse side.**

1. Type of Well

☒ Oil Well ☐ Gas Well ☒ Other UNKNOWN OTH

2. Name of Operator

CHESAPEAKE OPERATING, INC.

Contact: LINDA GOOD

E-Mail: linda.good@chk.com

3a. Address

P.O. BOX 18496  
OKLAHOMA CITY, OK 73154-0496

3b. Phone No. (include area code)

Ph: 405-935-4275

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 9 T22S R33E SENW 1980FNL 1980FWL Unit F

## 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompletable horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletable in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

CHESAPEAKE, RESPECTFULLY, REQUESTS PERMISSION TO P&A THIS WELL PER THE FOLLOWING PLUGGING PROCEDURE BELOW: WE HAVE RECEIVED A "NOTICE OF WRITTEN ORDER" ON THIS WELL AND WOULD APPRECIATE A QUICK APPROVAL. THANK YOU.

1. NOTIFY THE BLM 24 HOURS IN ADVANCE PRIOR TO COMMENCING PLUG AND ABANDONMENT OPERATIONS.

2. HOLD TAILGATE SAFETY MEETING PRIOR TO BEGINNING WORK EACH MORNING AND AS REQUIRED FOR SPECIFIC OPERATIONS.

3. RACK AND TALLY 175 JOINTS OF 2-3/8" N-80 WORK STING.

4. PREPARE LOCATION. TEST ANCHORS.

RECEIVED

JUL 02 2009

HOBBSOCD

*\* See Attached Reclamation Procedure*

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #71215 verified by the BLM Well Information System.  
For CHESAPEAKE OPERATING, INC., sent to the Hobbs

Name (Printed/Typed) LINDA GOOD

Title SR. REGULATORY COMPLIANCE SPEC

Signature (Electronic Submission)

Date 06/22/2009

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By

*James R. Goss*

Title

SEAS

Date

6-22-09

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Carlsbad Field Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*\* OPERATOR-SUBMITTED \*\* OPERATOR-SUBMITTED \*\* OPERATOR-SUBMITTED \*\*

JUL 02 2009

**Additional data for EC transaction #71215 that would not fit on the form**

**32. Additional remarks, continued**

5. MIRU PU. NDWH. NU AND TEST BOP.
6. RIH W/GAUGE RING AND JUNK BASKET TO PBTD @ 4,915'.
7. LOAD WELL WITH PLUGGING MUD AND PRESSURE UP TO 500# AND TEST FOR LEAK-OFF.
- \* ~~8. RIH W/OPEN ENDED TUBING TO 4,915' AND DUMP BAIL 35' OF CEMENT ON THE CIBP @ 4,915'. WAIT ON CEMENT AND TAG PLUG. (TOP OF BELL CANYON @ 5,015')~~
- ~~9. PULL UPHOLE TO 4,827' AND DUMP BAIL A 100' CEMENT PLUG (35 SACK MINIMUM). WAIT ON CEMENT AND TAG PLUG. (BASE OF SALT @ 4,827')~~
- \* ~~10. PULL UPHOLE TO 1,140' AND DUMP BAIL A 100' CEMENT PLUG (35 SACK MINIMUM). WAIT ON CEMENT AND TAG PLUG. (FRESH WATER @ 1,140')~~
- \* ~~11. PULL UPHOLE TO 633' AND DUMP BAIL A 100' CEMENT PLUG (35 SACK MINIMUM). WAIT ON CEMENT AND TAG PLUG. (8-5/8" CASING SHOE @ 583').~~
- \* ~~12. PULL UPHOLE TO 500' AND DUMP BAIL A 100' CEMENT PLUG (35 SACK MINIMUM). WAIT ON CEMENT AND TAG PLUG. (TOP OF SALT @ 450')~~
- \* ~~13. PULL UPHOLE TO 71' AND DUMP BAIL A CEMENT PLUG TO SURFACE. TOP OFF CASING. TOH.~~
14. RDMO. INSTALL DRY HOLE MARKER AND CUT OFF DEAD MAN. RESTORE LOCATION.

(CHK PN 610903)

- \* 8. Spot 25 sx cnt. on the CIBP (covers Top of Bell Canyon @ 5015' and Base of Salt). WOC and tag.
- \* 9. Eliminate step.
- \* 10. Spot 25 sx cnt. plug. Tag is not required.
- \* 11. Spot 25 sx cnt. plug (~~Top of Salt~~)
- \* 12. Spot 25 sx cnt. plug (Top of Salt) WOC tag
- \* 13. Circulate Cmt to surface.



Livestock Federal 3-9  
Plug and Abandonment  
Lea County, NM

**Current Wellbore Information**

TD: 5,250' PBD: 4,915'

Casing	OD	Weight	Grade	Depth Set	TOC
Surface	8-5/8"	24#	NA	583'	Surface
Production	5-1/2"	15.5#	NA	5,250'	Surface

Perfs	Top Perf	Bottom Perf	Status	SPF
Bell Canyon	5,015'	5,065'	Plugged Off	NA

OIH	Size	Location
CIBP	5-1/2"	4,915'

Formation Tops	Location
Top of Salt	450'
Fresh Water	1,140'
Base of Salt	4,827'
Top of Bell Canyon	5,250'

GL: 3,617' KB: 12' KB Height: 3,629'

**Procedure**

1. Notify the BLM 24 hours in advance prior to commencing plug and abandonment operations.
2. Hold Tailgate Safety meeting prior to beginning work each morning and as required for specific operations.
3. Rack and tally 175 joints of 2-3/8" N-80 workstring.
4. Prepare location. Test anchors.
5. MIRU PU. NDWH. NU and test BOP.
6. RIH w/ gauge ring and junk basket to PBD @ 4,915'.
7. Load well with plugging mud and pressure up to 500# and test for leak-off.
8. RIH w/ open ended tubing to 4,915' and dump bail 35' of cement on the CIBP @ 4,915'. Wait on cement and tag plug. (Top of Bell Canyon @ 5,015')
9. Pull uphole to 4,827' and dump bail a 100' cement plug (35 sack minimum). Wait on cement and tag plug. (Base of Salt @ 4,827')
10. Pull uphole to 1,140' and dump bail a 100' cement plug (35 sack minimum). Wait on cement and tag plug. (Fresh water @ 1,140')
11. Pull uphole to 633' and dump bail a 100' cement plug (35 sack minimum). Wait on cement and tag plug. (8-5/8" Casing Shoe @ 583').
12. Pull uphole to 500' and dump bail a 100' cement plug (35 sack minimum). Wait on cement and tag plug. (Top of Salt @ 450')

13. Pull uphole to 71' and dump bail a cement plug to surface. Top off casing. TOH.

14. RDMO. Install dry hole marker and cut off dead man. Restore location.

**Contacts**

**Workover Foreman**

Lynard Barrera  
Office: 575-391-1462  
Cell: 575-631-4942

**Asset Manager**

Kim Henderson  
Office: 405-935-8583  
Cell: 405-312-1840

**Production Foreman**

Greg Skiles  
Office: 575-391-1462  
Cell: 575-631-1663




# Workover Proposal

LIVESTOCK FEDERAL 3-9

Field: Delaware Basin North Project - Sapphire Prospect  
County: LEA  
State: NEW MEXICO  
Location: SEC 9, 22S-33E, 1980 FNL & 1980 FWL  
Elevation: GL 3,617.00 KB 3,629.00  
KB Height: 12.00

Spud Date: 10/15/2006  
Initial Compl. Date:  
API #: 3002538013  
CHK Property #: 610903  
1st Prod Date:  
PBTD: Original Hole - 4915.0  
TD: 5,250.0





# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
www.blm.gov/nm



In Reply Refer To 1310

### Reclamation (Interim/Final) Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Environmental Protection Specialist  
575-234-5909, 575-361-2648 (Cell)

Cody Layton  
Natural Resource Specialist  
575-234-5959

Terry Gregston  
Environmental Protection Specialist  
575-234-5958

Trishia Bad Bear  
Natural Resource Specialist  
575-393-3612

Bobby Ballard  
Environmental Protection Specialist  
575-234-2230

Todd Suter  
Surface Protection Specialist  
575-234-5987

Randy Rust  
Environmental Protection Specialist  
575-234-5943

Doug Hoag  
Civil Engineering Technician  
575-234-5979

Linda Denniston  
Environmental Protection Specialist  
575-234-5974

Jennifer Van Curen  
Environmental Protection Specialist  
575-234-5905

Justin Frye  
Environmental Protection Specialist  
575-234-5922

**BUREAU OF LAND MANAGEMENT**  
**Carlsbad Field Office**  
**620 East Greene Street**  
**Carlsbad, New Mexico 88220**  
**575-234-5972**

**Permanent Abandonment of Federal Wells**  
**Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed prior to commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. **Dry Hole Marker:** All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. **Subsequent Plugging Reporting:** Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. **Trash:** All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.