

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

RECEIVED

JUL 15 2009

HOBBS

WELL API NO. 30 - 025 - 09466
13. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
13. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name John P. Combest "WN"
8. Well Number 3
9. OGRID Number 000778
10. Pool name or Wildcat Jalmat Tansil Yates SRQ (Gas)

SUNDRIED COPIES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator BP America Production Company	
3. Address of Operator P. O. Box 1089 Eunice, New Mexico 88231	
13. Well Location Unit Letter A : 760 feet from the North line and 600 feet from the East line Section 35 Township 23S Range 36E NMPM Lea County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3334.3' GR	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/>	
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____	
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

13. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- Approved for Plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) forms, www.emfr.state.nm.us, sec. 10-1-1.
- MIRU PU on 6/25/09. Installed BOP, POH & LD tubing. TIH w/ bit & scraper and tagged bottom @ 3393' = 67' of fill on top of CR @ 3460'. Discussed w/ Buddy Hill at NMOCD and received approval to delete requirement that cement retainer (CR) @ 3460' be capped w/ cement. POH w/ B&S.
 - Ran 5 1/2" CIBP on tbg and set @ 2900'. Loaded hole w/ water, tested CIBP & casing to 500 psi, failed. POH w/ setting tool and ran pkr to test CIBP & casing. CIBP tested to 500 psi, OK; found 5 1/2" casing leak between 37' - 70' below ground level. Discussed findings w/ Mark Whitaker at NMOCD and received approval to proceed with abandonment. POH & LD pkr.
 - TIH w/ tbg & spotted 25 sx Class "C" onto CIBP @ 2900'. TOC est @ 2660' - btm plug also covers B/Salt @ 2770'.
 - POH w/ tbg, RU WL equipment and ran CBL; tagged top of cement plug w/ WL @ 2579' - TOC in 8 5/8" x 5 1/2" annulus @ 2075' w/ possible bridging from 1654' - 1666'. Discussed findings w/ Mark Whitaker at NMOCD and received approval to proceed with abandonment. TIH w/ tbg and circulated hole with 9.0 ppg mud laden fluid. POH w/ tbg, RU WL & perfed 5 1/2" csg @ 1270'. RD WL, TIH w/ pkr to 1162', pumped through perfs @ 1270' & circulated 8 5/8" x 5 1/2" annulus clean. POH.
 - TIH w/ CR and set @ 1162'. Mixed & pumped 225 sx Class "C" through perfs @ 1270' and had good cement returns to surface via 8 5/8" x 5 1/2" annulus. Closed CR and filled 5 1/2" casing from 1162' to surface w/ total of 105 sx Class "C". This set plug across T/Salt @ 1220', across 8 5/8" surface casing shoe @ 1201', across top of Rustler @ 1166' and set the top plug; plug in place on 7/1/09. POH & LD all tubing. RD & MO PU on 7/2/09.
 - Cut-off casings, wellheads and anchors to 3' below GL and installed regulation Dry Hole Marker; wellbore abandonment completed 7/7/09. NMOCD will be notified when site is ready for final inspection following reclamation of location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE M. D. Westmoreland TITLE Wells Operations Superintendent DATE 7/14/09

Type or print name M. D. Westmoreland E-mail address: dan.westmoreland@bp.com Telephone No. 432/688-5245

For State Use Only

APPROVED BY: Cathy W. Hill TITLE DISTRICT 1 SUPERVISOR DATE 7-15-09

Conditions of Approval (if any):

John P. Combest "WN" #3

(Jalmat Yates Tansil SRQ Gas)

API No. 30 - 025 - 09466

760' FNL & 600' FEL
Section 35 - T23S - R36E
Lea County, New Mexico

FINAL P&A

July 7, 2009

RKB 10.0'

GL 3334.3'

