

Submit 3 copies to Appropriate District

Office

DISTRICT I

1625 N. French Dr., Hobbs NM 88240

DISTRICT II

1301 W. Grand Avenue, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

DISTRICT IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87504-2088

Form C-103

Revised March 25, 1999

WELL API NO. 30-025-29331
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Superior WA State
8. Well No. 3
9. Pool Name or Wildcat Wildcat San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South 4th Str., Artesia, NM 88210

4. Well Location
Unit Letter F : 1980 feet from the North line and 1980 feet from the West line
Section 11 Township 14S Range 33E NMPM County Lea

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4197' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12-5-03 to 12-11-03 Set 5-1/2" CIBP @ 5050' and pumped 35' cement on top. Pumped 25 sx plug 4295-4195'. WOC 4 hrs. RIH; did not tag plug. Pumped cement plug 4295-4195'. Tagged plug @ 4092'. Spotted 25 sx Class C Neat 1758-1517'. Spotted 25 sx Class C Neat 512-271'. Spotted 15 sx Class C Neat 94' to surface. Cut off wellhead. Installed dry hole marker.

Well plugged and abandoned. FINAL REPORT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Technician DATE 12/15/03

Type or print name Stormi Davis

(This space for State use)

APPROVED BY Paul F. Kautz TITLE PETROLEUM ENGINEER DATE JAN 05 2004

Conditions of approval, if any:

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

