

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Ave, Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S St Francis Dr, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources
RECEIVED
OIL CONSERVATION DIVISION
AUG 07 2009
HOBBS
1000 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
March 4, 2004

WELL API NO. 30-025-31291
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B7845
7. Lease Name or Unit Agreement Name Lovington Paddock Unit
8. Well Number 115
9. OGRID Number 241333
10. Pool name or Wildcat Lovington Paddock

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Chevron Midcontinent L.P.

3. Address of Operator
#15 Smith Rd., Midland, TX 79705

4. Well Location
Unit Letter O : 2560 feet from the East line and 145 feet from the South line
Section 36 Township 16-S Range 36-E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

Pit or Below-grade Tank Application (For pit or below-grade tank closures, a form C-144 must be attached)

Pit Location: UL O Sect 36 Twp 16-S Rng 36-E Pit type Steel Depth to Groundwater _____ Distance from nearest fresh water well Over 1000'
Distance from nearest surface water _____ Below-grade Tank Location UL _____ Sect _____ Twp _____ Rng _____ ;
2560 feet from the East line and 145 feet from the South line (Steel Tank)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE ☐ PLUG AND ABANDONMENT ☐
CASING TEST ☐
CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give period of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore log or recompletion.

1. Notify OCD 24 hrs prior to MI and RU
2. RIH and set CIBP at 5050' and spot 25sx cement plug from 5050'-4850' (Paddock).
3. Displace hole w/MLF, 9.5# Brine w/12.5# gel P/BBL.
4. Spot 25sx cement plug from 4650'-4450' (S.Andres)
5. Spot 40sx cement plug from 3315'-2980' (Yates/B.Salt).
6. Perforate and squeeze 115sx cement plug from 2270'-1825' (shoe/T-Salt/Rustler) WOC&Tag
7. Spot 40sx cement plug from 350'-surface. (Fr Wtr./surface) Tag.
8. Install dryhole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☒.

SIGNATURE M. Lee Roark TITLE Agent for Chevron USA, Inc. DATE 8-05-2009
Type or print name M. Lee Roark E-mail address: _____ Telephone No. 432-561-8600

(This space for State use)

APPROVED BY Matey H Brown TITLE Compliance Officer DATE 8/10/2009
Conditions of approval, if any: _____



New Mexico Office of the State Engineer Water Column/Average Depth to Water

(quarters are 1=NW 2=NE 3=SW 4=SE)

(quarters are smallest to largest) (NAD83 UTM in meters)

(In feet)

POD Number	Sub basin	Use	County	Q 64	Q 16	Q 4	Sec	Tws	Rng	X	Y	Depth Well	Depth Water	Water Column
L 01350 APPRO	PRO	LE		2	4	36	16S	36E		658901	3638899*	110	55	55
L 01371 APPRO	PRO	LE		4	3	4	36	16S	36E	658603	3638389*	115	45	70
L 01438 APPRO	PRO	LE		3	4	36	16S	36E		658504	3638490*	110	45	65
L 01557 APPRO	PRO	LE		4	3	3	36	16S	36E	657796	3638374*	110	40	70
L 04058 (EXPLORE 2	MUN	LE		2	3	1	36	16S	36E	657783	3639380*	230		
L 04058 (EXPLORE)	MUN	LE		2	1	1	36	16S	36E	657777	3639783*	230		
L 04058 S-24	MUN	LE		2	1	1	36	16S	36E	657777	3639783*	257	88	169
L 04058 S-25	MUN	LE		2	4	1	36	16S	36E	658187	3639387*	256	88	168
L 04058 S26	MUN	LE		4	4	2	36	16S	36E	658993	3639200*	237		

Average Depth to Water: 60 feet

Minimum Depth: 40 feet

Maximum Depth: 88 feet

Record Count: 9

PLSS Search:

Section(s): 36

Township: 16S

Range: 36E

*UTM location was derived from PLSS - see Help

The data is furnished by the NMOSE/ISC and is accepted by the recipient with the expressed understanding that the OSE/ISC make no warranties, expressed or implied, concerning the accuracy, completeness, reliability, usability, or suitability for any particular purpose of the data.

8/5/09 3:52 PM