Form 3160-5 (February 2005)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BURGALLOG LAND MANAGEMENT

OCD-HODBS

FORM APROVED OMB NO. 1004-0137 EXPIRES: March 31, 2007

	LAND MANAGEMENT	,		EXPIRES: March 31, 2007	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an				5. Lease Serial No. NM-81958	
abandoned well. Use Form 3160-3 (APD) for such proposals				6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICAT	E - Other instructions on	page 2			
				7. Unit or CA Agreement Name and No.	
1. Type of Well ☑ Oil Well ☐ Gas Well ☐	Other	/		8 Well Name and No.	
	_ Odiei	/		Uncle Sam 13C Fed 1	
2. Name of Operator DEVON ENERGY PRODUCTION COMPANY, LP		<i>'</i>		9. API Well No.	
3a, Address		3b. Phone No. (include area code)		30-025-30997	
20 North Broadway, Ste 1500, Oklahoma City, OK 73102		405-552-4615 10. Field and Pool, or Exploratory Area		10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Descrip		ition)		WEST CORBIN DELAWARE	
660' FNL 660' FEL 13 T18S R32E				11. County or Parish, State	
	/			Lea NM	
	ROPRIATE BOX(es) TO I	INDICATE NATURE OF NOTICE		RT OR OTHER DATA	
TYPE OS SUBMISSION		TYPE OF A			
☐ Notice of Intent	☐ Acidize ☐ Alter Casing		roductio eclamati	n (Start/Resume)	
☑ Subsequent Report	Casing Repair		ecomple		
Final Abandonment Notice	Change Plans		emporar	rily Abandon	
	Convert to Injection		Vater Dis		
				y proposed work and approximate duration thereof If the proposal littach the Bond under which the work will be performed or provide	
the Bond No on file with BLM/BIA Required subsequent repoint interval, a Form 3160-4 shall be filed once testing has been or				peration results in a multiple completion or recompletion in a new	
determined that the site is ready for final inspection)	ompleted Tillal Abandoninent Not	noco onan be med only anter an requirement	, moduling i	remaination, have been completed, and the operator has	
				RECEIVED	
				AUG 1 8 2009	
Actual Plug & Abandonment:				MARREAGE	
1 7/13/00 MIRLL BOOK w/rod num	on and 2 7/0" product	HOBBSOCD HOBBSOCD			
1. <u>7/13/09-</u> -MIRU. POOH w/rod pum 2. Set CIBP @ 4900'. (per Marlin De			tad 10t	# mud to surface	
3. Spot 25 sx cement on top of CIBF		Sa Oldi (@ 4300 . Olicala	ica ioi	Finds to surface.	
4. Spot 25 sx cement from 2460' to		@ 2610')			
5. Spot 25 sx cement @ 1674'. Tagged TOC @ 1500'. (top of salt @ 1600')			CCEPTED FOR RECORD		
6. Spot 50 sx cement from 496' to si	shoe @ 428')	110	JOET TED TOTT TEOORD		
7. 8/6/09Cut wellhead off. Set dry hole marker. Wellbore plugged & abandoned.					
				AUG 1 5 2009	
				A00 1 5 2009	
				16/2000	
				BUREAU OF LAND MANAGEMENT	
			1,	CARLSBAD FIELD OFFICE	
14. I hereby certify that the foregoing is true an	nd correct			CARESDAD FIELD OFFICE	
Name: Ronnie Slack	Title	Engineering Technicia	n		
Signature Rommie Slack					
Signature ROWN SYACK	Date	8/6/2009			
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by		METRICT 1 SUPERV	SOF	0.110.10.0000	
6	Title			Date AUG 19 2009	
Conditions of approval, if any are attached. Ap					
notice does not warrant or certify that the applic	~ 1				
equitable title to those rights in the subject leas entitle the applicant to conduct or operations th				v	
	2://42				

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212 make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

DEVON EN	ERGY PRODUCTION COMPANY LP
ell Name: UNCLE SAM 13C FEDERAL 1	Field: WEST CORBIN
ocation: 660' FNL & 660' FEL; SEC 13-T18S-R32	
evation: 3839' <i>G</i> L	Spud Date: 11/24/90 Compl Date: 12/22/90
PI#: 30-025-30997 Prepared by: Ronnie Slack	Date: 8/6/09 Rev:
PLUGGED & ABANDONED 8/6/09	Dry hole marker set (8/6/09)
12-1/4" hole 8-5/8", 32#, K55, LTC, @ 428' Cmt'd w/300 sx Cl C, circ to surface	Spot 50 sx cement from 496' to surface. (7/16/09)
	10 ppg mud Spot 25 sx cement 1674'. Tagged @ 1500' (7/16/09) (Top of salt @ 1600')
	10 ppg mud Spot 25 sx cement 2460' - 2666' (7/15/09) (Base of salt @ 2610')
<u>DELAWARE</u> 4970' - 4986' 4988' - 4998'	10 ppg mud (7) Spot 25 sx cement (7/15/09) CIBP @ 4900' (7/14/09)
7-7/8" Hole <u>5-1/2", 15.5#, K55, STC & LTC, @ 5300'</u> Cmt'd w/1275 sx, circulated to surface	5300' TD